

MAC12D, MAC12M, MAC12N

Preferred Device

Triacs

Silicon Bidirectional Thyristors

Designed for high performance full-wave ac control applications where high noise immunity and commutating di/dt are required.

Features

- Blocking Voltage to 800 Volts
- On-State Current Rating of 12 Amperes RMS at 70°C
- Uniform Gate Trigger Currents in Three Quadrants, Q1, Q2, and Q3
- High Immunity to dv/dt – 250 V/μs Minimum at 125°C
- High Commutating di/dt – 6.5 A/ms Minimum at 125°C
- Industry Standard TO-220 AB Package
- High Surge Current Capability – 100 Amperes
- Pb-Free Packages are Available*

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

| Rating | Symbol | Value | Unit |
|---|--|-------------|--------------------|
| Peak Repetitive Off-State Voltage (Note 1) (T _J = -40 to 125°C, Sine Wave, 50 to 60 Hz, Gate Open) | V _{DRM} , V _{RRM} | | V |
| | MAC12D | 400 | |
| | MAC12M | 600 | |
| | MAC12N | 800 | |
| On-State RMS Current (All Conduction Angles; T _C = 70°C) | I _{T(RMS)} | 12 | A |
| Peak Non-Repetitive Surge Current (One Full Cycle, 60 Hz, T _J = 125°C) | I _{TSM} | 100 | A |
| Circuit Fusing Consideration (t = 8.33 ms) | I ² t | 41 | A ² sec |
| Peak Gate Power (Pulse Width ≤ 1.0 μs, T _C = 80°C) | P _{GM} | 16 | W |
| Average Gate Power (t = 8.3 ms, T _C = 80°C) | P _{G(AV)} | 0.35 | W |
| Operating Junction Temperature Range | T _J | -40 to +125 | °C |
| Storage Temperature Range | T _{stg} | -40 to +150 | °C |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.


*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®

<http://onsemi.com>


TRIACS
12 AMPERES RMS
400 thru 800 VOLTS



MARKING DIAGRAM



TO-220AB
CASE 221A-09
STYLE 4



x = D, M, or N
A = Assembly Location
Y = Year
WW = Work Week
G = Pb-Free Package

PIN ASSIGNMENT

| | |
|---|-----------------|
| 1 | Main Terminal 1 |
| 2 | Main Terminal 2 |
| 3 | Gate |
| 4 | Main Terminal 2 |

ORDERING INFORMATION

| Device | Package | Shipping |
|---------|-----------------------|-----------------|
| MAC12D | TO-220AB | 50 Units / Rail |
| MAC12DG | TO-220AB (Pb-Free) | 50 Units / Rail |
| MAC12M | TO-220AB | 50 Units / Rail |
| MAC12MG | TO-220AB (Pb-Free) | 50 Units / Rail |
| MAC12N | TO-220AB | 50 Units / Rail |
| MAC12NG | TO-220AB (Pb-Free) | 50 Units / Rail |

Preferred devices are recommended choices for future use and best overall value.

MAC12D, MAC12M, MAC12N

THERMAL CHARACTERISTICS

| Characteristic | Symbol | Value | Unit |
|---|-----------------|-------|---------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 2.2 | $^{\circ}C/W$ |
| Junction-to-Ambient | $R_{\theta JA}$ | 62.5 | |
| Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 10 Seconds | T_L | 260 | $^{\circ}C$ |

ELECTRICAL CHARACTERISTICS ($T_J = 25^{\circ}C$ unless otherwise noted; Electricals apply in both directions)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

OFF CHARACTERISTICS

| | | | | | | |
|---|---|------------------------|--------|--------|-------------|----|
| Peak Repetitive Blocking Current ($V_D = \text{Rated } V_{DRM}, V_{RRM}, \text{ Gate Open}$) | $T_J = 25^{\circ}C$ $T_J = 125^{\circ}C$ | I_{DRM} I_{RRM} | - - | - - | 0.01 2.0 | mA |
|---|---|------------------------|--------|--------|-------------|----|

ON CHARACTERISTICS

| | | | | | |
|---|----------|-----|------|------|----|
| Peak On-State Voltage (Note 2) ($I_{TM} = \pm 17 A$) | V_{TM} | - | - | 1.85 | V |
| Gate Trigger Current (Continuous dc) ($V_D = 12 V, R_L = 100 \Omega$) | I_{GT} | 5.0 | 13 | 35 | mA |
| MT2(+), G(+) | | 5.0 | 13 | 35 | |
| MT2(+), G(-) | | 5.0 | 13 | 35 | |
| MT2(-), G(-) | | | | | |
| Hold Current ($V_D = 12 V, \text{ Gate Open, Initiating Current} = \pm 150 \text{ mA}$) | I_H | - | 20 | 40 | mA |
| Latch Current ($V_D = 24 V, I_G = 35 \text{ mA}$) | I_L | - | 20 | 50 | mA |
| MT2(+), G(+) | | - | 30 | 80 | |
| MT2(+), G(-) | | - | 20 | 50 | |
| MT2(-), G(-) | | | | | |
| Gate Trigger Voltage (Continuous dc) ($V_D = 12 V, R_L = 100 \Omega$) | V_{GT} | 0.5 | 0.78 | 1.5 | V |
| MT2(+), G(+) | | 0.5 | 0.70 | 1.5 | |
| MT2(+), G(-) | | 0.5 | 0.71 | 1.5 | |
| MT2(-), G(-) | | | | | |

DYNAMIC CHARACTERISTICS


| | | | | | |
|---|-------------|-----|-----|----|-----------|
| Rate of Change of Commutating Current ($V_D = 400 V, I_{TM} = 4.4 A, \text{ Commutating } dv/dt = 18 V/\mu s, \text{ Gate Open, } T_J = 125^{\circ}C, f = 250 \text{ Hz, No Snubber}$) | $(di/dt)_c$ | 6.5 | - | - | A/ms |
| Critical Rate of Rise of Off-State Voltage ($V_D = \text{Rated } V_{DRM}, \text{ Exponential Waveform, Gate Open, } T_J = 125^{\circ}C$) | dv/dt | 250 | 500 | - | $V/\mu s$ |
| Repetitive Critical Rate of Rise of On-State Current IPK = 50 A; PW = 40 μs ; $di_G/dt = 200 \text{ mA}/\mu s$; $f = 60 \text{ Hz}$ | di/dt | - | - | 10 | $A/\mu s$ |

2. Pulse Test: Pulse Width $\leq 2.0 \text{ ms}$, Duty Cycle $\leq 2\%$.


MAC12D, MAC12M, MAC12N

Voltage Current Characteristic of Triacs (Bidirectional Device)

| Symbol | Parameter |
|-----------|---|
| V_{DRM} | Peak Repetitive Forward Off State Voltage |
| I_{DRM} | Peak Forward Blocking Current |
| V_{RRM} | Peak Repetitive Reverse Off State Voltage |
| I_{RRM} | Peak Reverse Blocking Current |
| V_{TM} | Maximum On State Voltage |
| I_H | Holding Current |



Quadrant Definitions for a Triac



All polarities are referenced to MT1.
With in-phase signals (using standard AC lines) quadrants I and III are used.

MAC12D, MAC12M, MAC12N




Figure 1. Typical Gate Trigger Current versus Junction Temperature




Figure 2. Typical Gate Trigger Voltage versus Junction Temperature




Figure 3. Typical Holding Current versus Junction Temperature




Figure 4. Typical Latching Current versus Junction Temperature




Figure 5. Typical RMS Current Derating




Figure 6. On-State Power Dissipation

MAC12D, MAC12M, MAC12N




Figure 7. Typical On-State Characteristics





Figure 8. Typical Thermal Response

MAC12D, MAC12M, MAC12N

PACKAGE DIMENSIONS

TO-220AB
CASE 221A-09
ISSUE AA



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| DIM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.570 | 0.620 | 14.48 | 15.75 |
| B | 0.380 | 0.405 | 9.66 | 10.28 |
| C | 0.160 | 0.190 | 4.07 | 4.82 |
| D | 0.025 | 0.035 | 0.64 | 0.88 |
| F | 0.142 | 0.147 | 3.61 | 3.73 |
| G | 0.095 | 0.105 | 2.42 | 2.66 |
| H | 0.110 | 0.155 | 2.80 | 3.93 |
| J | 0.018 | 0.025 | 0.46 | 0.64 |
| K | 0.500 | 0.562 | 12.70 | 14.27 |
| L | 0.045 | 0.060 | 1.15 | 1.52 |
| N | 0.190 | 0.210 | 4.83 | 5.33 |
| Q | 0.100 | 0.120 | 2.54 | 3.04 |
| R | 0.080 | 0.110 | 2.04 | 2.79 |
| S | 0.045 | 0.055 | 1.15 | 1.39 |
| T | 0.235 | 0.255 | 5.97 | 6.47 |
| U | 0.000 | 0.050 | 0.00 | 1.27 |
| V | 0.045 | --- | 1.15 | --- |
| Z | --- | 0.080 | --- | 2.04 |

STYLE 4:

- PIN 1. MAIN TERMINAL 1
- PIN 2. MAIN TERMINAL 2
- PIN 3. GATE
- PIN 4. MAIN TERMINAL 2

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.