



4600X Series

Tubeaxial

119x119x38mm

- AC fans with external rotor shaded-pole motor. Impedance protected against overloading.
- Metal fan housing and impeller.
- Air intake over struts. Rotational direction CW looking at rotor.
- Mounting: Either face using four 3.7mm (.146") holes.
- Electrical connection: Terminals with 2 flat pins 2.8 x 0.5 mm.
- Fan housing with ground lug for screw M4 and UNC.
- UL, CSA, VDE approvals on some models, please contact application engineering.

| Part Number | CFM @ 0 | VAC | Hertz | Power (W) | dBA | Max Amb. Temp. C | Bearing Type | Features | Wgt. (lbs) |
|-------------|---------|-----|-------|-----------|-----|------------------|--------------|-----------|------------|
| 4600X | 106 | 115 | 50/60 | 18 | 50 | 60 | Sintec | Terminals | 1.19 |
| 4600XP | 106 | 115 | 50/60 | 18 | 50 | 60 | Sintec | Terminals | 1.19 |
| 4606X | 106 | 115 | 50/60 | 18 | 51 | 90 | Ball | Terminals | 1.19 |
| 4650X | 106 | 230 | 50/60 | 18 | 50 | 60 | Sintec | Terminals | 1.19 |
| 4656X | 106 | 230 | 50/60 | 18 | 51 | 90 | Ball | Terminals | 1.19 |

Note: 4600XP has a 5 year warranty.

