

# Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number : **744227S**


LF



Bezeichnung : **STROMKOMP. SMD LINE FILTER WE-SL2**  
 description : **COMMON MODE SMD LINE FILTER WE-SL2**

DATUM / DATE : 2004-10-11

## A Mechanische Abmessungen / dimensions :




A	<b>9,2 ± 0,3</b>	mm
B	<b>6,0 ± 0,3</b>	mm
C	<b>5,0 ± 0,3</b>	mm
D	<b>2,0 ref.</b>	mm
E	<b>2,54 ± 0,2</b>	mm
F	<b>5,7 ref.</b>	mm
G	<b>1,4 ref.</b>	mm
H	<b>1,0 ± 0,1</b>	

## B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	<b>0,1V / 1 KHz</b>	$L_{1-4,2-3}$	<b>51</b>	$\mu\text{H}$	$\pm 30\%$
Nennspannung / rated voltage		$U_{DC}$	<b>80</b>	V	
DC-Widerstand / DC-resistance		$R_{DC}$	<b>0,16</b>	$\Omega$	<b>max.</b>
Nennstrom / rated current		$I_{DC}$	<b>1,00</b>	A	<b>max.</b>
Impedanz / impedance		Z	<b>5500</b>	$\Omega$	<b>max.</b>

## C Lötpad / soldering spec. :



## D Prüfgeräte / test equipment :

**HP 4274 A** für/for L und/and Q  
**HP 34401 A** für/for  $I_{DC}$  und/and  $R_{DC}$

## E Testbedingungen / test conditions :

Lufffeuchtigkeit / humidity: 33%  
 Umgebungstemperatur / temperature: +20°C

## F Werkstoffe & Zulassungen / material & approvals :

Basismaterial / base material: Ferrit / ferrite  
 Draht / wire: Class F  
 Gehäuse / Housing: UL94-V0

## G Eigenschaften / granted properties :

Betriebstemp. / operating temperature: -40°C - + 125°C  
 Umgebungstemp. / ambient temperature: -40°C - + 85°C  
 It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.  
 Spannungsfestigkeit / High-Pot Test:(60Hz 3mA 3sec.) 500 VAC

Freigabe erteilt / general release:	<b>Kunde / customer</b>		
Datum / date	Unterschrift / signature		
Geprüft / checked	<b>Würth Elektronik</b>		
	Kontrolliert / approved		

### Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.com>



# Spezifikation für Freigabe / specification for release

Kunde / customer : \_\_\_\_\_  
 Artikelnummer / part number : **744227S** LF  
 Bezeichnung : **STROMKOMP. SMD LINE FILTER WE-SL2**  
 description : **COMMON MODE SMD LINE FILTER WE-SL2**



DATUM / DATE : 2004-10-11

## H Impedanzverlauf / impedance curve :



Freigabe erteilt / general release:	<b>Kunde / customer</b>				
	Datum / date	Unterschrift / signature	MST	Version 7	2004-10-11
	<b>Würth Elektronik</b>		MST	Version 6	2004-03-29
	Geprüft / checked	Kontrolliert / approved	MST	Version 5	2004-01-07
			AG	Version 4	2003-04-15
			MST	Version 3	2003-03-04
			RT	Version 2	2002-04-23
			MST	Version 1	2002-03-21
			Name	<b>Änderung / modification</b>	Datum / date

This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body. In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before use. It is essential to give consideration when to install a protective circuit at the design stage.

### Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400  
<http://www.we-online.com>