


UNCONTROLLED DOCUMENT

29F0429-0T0-10



PHYSICAL DIMENSIONS:

A	10.88 [.428]	+ 0.15 [.006]	
B	5.49 [.216]	+ 0.08 [.003]	
C	10.44 [.411]	+ 0.25 [.010]	
C1	11.43 [.450]	- MAX	
D	2.54 [.100]	+ 0.13 [.005]	
E	2.54 [.100]	+ 0.13 [.005]	
T1	3.17 [.125]	+ TYP.	
T2	0.64 [.025]	+ REF.	




ELECTRICAL CHARACTERISTICS:

Z @ 100MHz (Ω)	DCR (Ω)	Rated Current
Nominal	285	
Minimum	214	
Maximum	356	0.01
		8,000 mA


NOTES: UNLESS OTHERWISE SPECIFIED

1. BULK PACKED 1260 per CASE.
2. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
3. TERMINATION FINISH IS 100% TIN.

|Z| , R, AND X vs. FREQUENCY



HOLE PATTERN FOR THRU-HOLE INSERTION



AGILENT E4991A RF Impedance/Material Analyzer
HP 16194A Test Fixture

DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
D	UPDATE COMPANY LOGO	10/21/08	JRK	PROJECT/PART NUMBER: 29F0429-0T0-10	REV D	PART TYPE: ASSEMBLY	DRAWN BY: TMB
C	ADD ROHS SYMBOL UPDATE LOGO	05/02/07	JRK				
B	CHG T1 FROM .142, ADD NUMBERING TO HOLE PATTERN, ADD NOTE 3	06/23/04	JRK				
A	ORIGINAL DRAFT	02/20/04	TMB				
REV	DESCRIPTION	DATE	INT				
				DATE: 02/20/04	SCALE: NTS	SHEET: 2 of 3	
				CAD # 29F0429-0T0-10-D-2	TOOL # H0429		

