



Passives  
Dielectric Filters

◆ Site Map

◆ Contact TOKO

◆ Home

◆ Passives

◆ Semiconductors

◆ Wireless Modules


◆ About TOKO

## 4DFA

*Frequency Range:* 800-2500MHz

*Temperature Range:* -25°C to +85°C

### Dimensions



### SMD 2 Pole Designs

Part Number	Center Freq. (MHz)	Bandwidth ( $f_0$ +/- MHz)	I.L. (db max.)	Ripple (dB max.)	VSWR in BW	Selectivity dB min. @ MHz	Application
4DFA-836E-10	836.5	+/- 12.5	2.0	1.0	2.0	18( $f_0$ +/- 77.5)	Cellular-AMPS/TDMA/CDMA
4DFA-881E-10	881.5	+/- 12.5	2.0	1.0	2.0	18( $f_0$ +/- 77.5)	Cellular-AMPS/TDMA/CDMA
4DFA-964E-10	964.0	+/- 12.5	2.0	1.0	2.0	18( $f_0$ +/- 77.5)	Cellular-AMPS/TDMA/CDMA
4DFA-902E-10	902.5	+/- 12.5	2.5	1.0	2.0	18( $f_0$ +/- 77.5)	Cellular-NMT/GSM
4DFA-947E-10	947.5	+/- 12.5	2.5	1.0	2.0	18( $f_0$ +/- 77.5)	Cellular-NMT/GSM
4DFA-866A-10	866.0	+/- 2.0	3.0	1.0	2.0	30( $f_0$ +/- 105)	CT2
4DFA-886A-10	886.0	+/- 1.0	3.0	1.0	2.0	22( $f_0$ +/- 45)	Cordless Phone
4DFA-931A-10	931.0	+/- 1.0	3.0	1.0	2.0	22( $f_0$ +/- 45)	Cordless Phone, Paper
4DFA-906A-10	906.5	+/- 1.0	6.0	0.5	2.0	10,25( $f_0$ -21, +19)	Cordless Phone

4DFA-926A-10	926.5	+/- 1.0	6.0	0.5	2.0	25,10( $f_0$ -19, +40)	Cordless Phone
4DFA-904A-10	904.0	+/- 1.0	3.8	0.5	2.0	21,30( $f_0$ +21.5,+44)	Cordless Phone
4DFA-926A-11	926.5	+/- 1.0	3.8	0.5	2.0	21,30( $f_0$ -21.5, -44)	Cordless Phone
4DFA-915E-10	915.0	+/- 13.0	2.2	1.0	2.0	18( $f_0$ +/-77.5)	RF Data, Cordless,ISM
4DFA-1227B-10	1227.0	+/- 5.0	2.0	0.8	2.0	7,30( $f_0$ +/- 35,140)	GPS
4DFA-1227B-11	1227.0	+/- 5.0	1.2: 0.7 typ	0.5	2.0	15,20( $f_0$ +140,-140)	GPS
4DFA-1575B-10	1575.4	+/- 5.0	2.0: 1.4 typ	0.8	2.0	7,30( $f_0$ +/-35,140)	GPS
4DFA-1575B-12	1575.4	+/-5.0	1.2: 0.7 typ	0.5	2.0	17,20( $f_0$ +140,-140)	GPS
4DFA-1575B-14	1575.4	+/- 5.0	2.5: 1.8 typ	0.8	2.0	17( $f_0$ +/- 50)	GPS
4DFA-1890D-10	1890.0	+/- 10.0	2.0	1.0	2.0	20( $f_0$ +/-89)	DECT
<a href="#">4DFA-1903C-10</a>	1903.0	+/- 8.0	2.7	1.0	2.0	15,27( $f_0$ +/-50,100)	PHP
4DFA-2442P-10	2442.0	+/- 40.0	2.5	1.0	2.0	15( $f_0$ +/-250)	RF Data, ISM
4DFA-2450T-10	2450.0	+/- 50.0	2.0	1.0	2.0	22( $f_0$ -280)	RF Data, ISM
4DFA-2500A-10	2500.0	+/- 2.0	3.0	1.0	2.0	18,25( $f_0$ +/- 60,90)	RACS

[Passives](#) ~ [Semiconductors](#) ~ [Wireless](#) ~ [Site Map](#) ~ [Contact Toko](#) ~ [About Toko](#) ~ [What's New](#) ~ [Home](#)

Copyright © 2002 Toko America, Inc. All rights reserved.  
[Statement of Liability](#)