



METRIC STANDOFFS

MALE/FEMALE



| THREAD SIZE | TL | A |
|-------------|------|------|
| M2.5 | 4.0 | 5.0 |
| M3 | 8.0 | 8.0 |
| M4 | 10.0 | 11.0 |

FEMALE



| CHOICE OF: | | |
|---------------------------|--|---|
| Stainless: ASTM A581/A582 | Brass: ASTM-B16 Plating: Nickel (QQ-N-290) | Aluminum: ASTM B211 Plating: Clear Iridite (Mil-C-5541) |

| MALE/FEMALE | | | | FEMALE | | |
|-----------------------------------|----------------|-------------------|------|--------------------|----------------|-------------------|
| STAINLESS CAT. NO. | BRASS CAT. NO. | ALUMINUM CAT. NO. | L | STAINLESS CAT. NO. | BRASS CAT. NO. | ALUMINUM CAT. NO. |
| 4.5 HEX DIA. (M2.5 THREAD) | | | | | | |
| — | — | — | 5.0 | 24460 | 24380 | 24420 |
| — | — | — | 6.0 | 24461 | 24381 | 24421 |
| — | — | — | 8.0 | 24462 | 24382 | 24422 |
| 24283 | 24307 | 24331 | 10.0 | 24463 | 24383 | 24423 |
| 24284 | 24308 | 24332 | 12.0 | 24464 | 24384 | 24424 |
| 24285 | 24309 | 24333 | 15.0 | 24465 | 24385 | 24425 |
| 24286 | 24310 | 24334 | 18.0 | 24466 | 24386 | 24426 |
| 24287 | 24311 | 24335 | 20.0 | 24467 | 24387 | 24427 |
| 24288 | 24312 | 24336 | 25.0 | 24468 | 24388 | 24428 |
| 5.0 HEX DIA. (M3 THREAD) | | | | | | |
| — | — | — | 5.0 | 24470 | 24390 | 24430 |
| — | — | — | 6.0 | 24471 | 24391 | 24431 |
| — | — | — | 8.0 | 24472 | 24392 | 24432 |
| 24289 | 24313 | 24337 | 10.0 | 24473 | 24393 | 24433 |
| 24290 | 24314 | 24338 | 12.0 | 24474 | 24394 | 24434 |
| 24291 | 24315 | 24339 | 15.0 | 24475 | 24395 | 24435 |
| 24292 | 24316 | 24340 | 18.0 | 24476 | 24396 | 24436 |
| 24293 | 24317 | 24341 | 20.0 | 24477 | 24397 | 24437 |
| 24294 | 24318 | 24342 | 25.0 | 24478 | 24398 | 24438 |
| 5.5 HEX DIA. (M3 THREAD) | | | | | | |
| — | — | — | 5.0 | 24480 | 24400 | 24440 |
| — | — | — | 6.0 | 24481 | 24401 | 24441 |
| — | — | — | 8.0 | 24482 | 24402 | 24442 |
| 24295 | 24319 | 24343 | 10.0 | 24483 | 24403 | 24443 |
| 24296 | 24320 | 24344 | 12.0 | 24484 | 24404 | 24444 |
| 24297 | 24321 | 24345 | 15.0 | 24485 | 24405 | 24445 |
| 24298 | 24322 | 24346 | 18.0 | 24486 | 24406 | 24446 |
| 24299 | 24323 | 24347 | 20.0 | 24487 | 24407 | 24447 |
| 24300 | 24324 | 24348 | 25.0 | 24488 | 24408 | 24448 |
| 6.0 HEX DIA. (M4 THREAD) | | | | | | |
| — | — | — | 5.0 | 24490 | 24410 | 24450 |
| — | — | — | 6.0 | 24491 | 24411 | 24451 |
| — | — | — | 8.0 | 24492 | 24412 | 24452 |
| 24301** | 24325** | 24349** | 10.0 | 24493 | 24413 | 24453 |
| 24302* | 24326* | 24350* | 12.0 | 24494 | 24414 | 24454 |
| 24303 | 24327 | 24351 | 15.0 | 24495 | 24415 | 24455 |
| 24304 | 24328 | 24352 | 18.0 | 24496 | 24416 | 24456 |
| 24305 | 24329 | 24353 | 20.0 | 24497 | 24417 | 24457 |
| 24306 | 24330 | 24354 | 25.0 | 24498 | 24418 | 24458 |

* Internal Thread: 8.0mm deep ** Internal Thread: 6.0mm deep
 Note: Female standoffs longer than 19mm are tapped from both ends

METRIC NYLON STANDOFFS

Material: Nylon: 6/6, UL Rated 94V-2

MALE/FEMALE





| THREAD SIZE | A |
|-------------|-----|
| M3 | 8.0 |
| M4 | 9.5 |

FEMALE




| MALE/FEMALE CAT. NO. | L | FEMALE CAT. NO. |
|----------------------------|------|-----------------|
| 5.0 HEX (M3 THREAD) | | |
| — | 6.0 | 25508 |
| — | 8.0 | 25509 |
| 25501 | 10.0 | 25510 |
| 25502 | 12.0 | 25511 |
| 25503 | 15.0 | 25512 |
| 25504 | 18.0 | 25513 |
| 25505 | 20.0 | 25514 |
| 25506 | 25.0 | 25515 |
| 6.0 HEX (M4 THREAD) | | |
| — | 6.0 | 25528 |
| — | 8.0 | 25529 |
| 25521 | 10.0 | 25530 |
| 25522 | 12.0 | 25531 |
| 25523 | 15.0 | 25532 |
| 25524 | 18.0 | 25533 |
| 25525 | 20.0 | 25534 |
| 25526 | 25.0 | 25535 |

Note: Female standoffs longer than 19mm are tapped from both ends



METRIC NYLON LOCK-IN SUPPORT

- One end locks into chassis, the other end locks into the PC Board.




| CAT. NO. | L DIM |
|----------|-------|
| 8843 | 3.0 |
| 8844 | 4.0 |
| 8845 | 6.0 |
| 8846 | 8.0 |
| 8847 | 10.0 |
| 8848 | 12.0 |
| 8849 | 14.0 |
| 8850 | 16.0 |
| 8851 | 18.0 |

MATERIAL: Nylon 6/6, UL Rated 94V-0

METRIC SCREWS

Choice of: Steel, Zinc Plate • Nylon: 6/6, UL Rated 94V-2



| STEEL CAT. NO. | L | NYLON 6/6 CAT. NO. |
|--------------------|-------|--------------------|
| M2.5 THREAD | | |
| 29301 | 6.00 | 29331 |
| 29304 | 12.00 | 29334 |
| 29306 | 16.00 | 29336 |
| M3 THREAD | | |
| 29311 | 6.00 | 29341 |
| 29314 | 12.00 | 29344 |
| 29316 | 16.00 | 29346 |
| 29318 | 25.00 | 29348 |
| M4 THREAD | | |
| 29321 | 6.00 | 29351 |
| 29324 | 12.00 | 29354 |
| 29326 | 16.00 | 29356 |
| 29328 | 25.00 | 29358 |