


PART NO.	DIM. "A" ±.015(0.4)
CRLCBSR-3-01	3/16 (4.8)
CRLCBSR-4-01	1/4 (6.4)
CRLCBSR-5-01	5/16 (8.0)
CRLCBSR-6-01	3/8 (9.5)
CRLCBSR-8-01	1/2 (12.7)
CRLCBSR-12-01	3/4 (19.0)

- (4.0 ± 0.08) DIA. HOLE, IN A .063 (1.6) NOMINAL THICK BOARD

TO SNAP-LOCK IN A $.236\pm.003$ - (6.0 ± 0.08) DIA. HOLE, IN A

.031-.047 (0.8-1.2) PANEL THICKNESS

TO SNAP-LOCK IN A .157±.003



NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01).
FLAME RETARDANT, NYLON (RMS-19),
AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER, REPLACE "-01" WITH "-19"

2. MATERIAL: NYLON 4/6, HEAT STABILIZED, (RMS-109) AVAILABLE BY SPECIAL ORDER ONLY. TO ORDER, REPLACE "-01" WITH "-109".

3. COLOR: NATURAL.
BLACK, AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER, ADD "-B" TO PART NO.

F	ADDED NOTE 2 (RMS-109) BY SPECIAL ORDER	SM 06.06.02	TITLE: OI		DEVEDOE LOOKIN	0 000 001	INID LIQUE	T T DWG INT	
Ε	UPDATED NOTES AND CHANGED FILE NO.	SM U5.U6.U2		JPPED.	REVERSE LOCKIN	IG CBS, ROI	JND HOLE	(⊕) E	
D	DIM. TO S-L IN .24 (6.0) ADDED; TABLE REDUCED; UL NOTES ADDED	PB 07.10.95		1 "				(MM)	7000
			TOLERANCES	FILE #	CRLCBSR	DWN: P.B.	APP:	FINAL	
С	DIMS IN CHASSIS THKNS PUT TO 3 PLACES	PB 11.23.94	UNLESS NOTED	MAT'L:	SEE NOTES	DT: 07-29-94	DT:	PART #	PRINT
В	CONVERTED TO ACAD; DIM "A" WAS .411	PB 07.29.94	.XX=±.010	RE:		RICHC		1	TYPE
Α	COMLETE REDRAW, .40 WAS .39, .06	RT 03.10.94	.XXX=±.005	INE.	RICHCO, INC.			ISFF TARLE	ITPE
	WAS .07, RMS-01 WAS RMS-48		FRAC=1/64		,	PO BOX 804238,CHICAGO,60680		JOEL IMBEL	$I \cap A I$
REV	DESCRIPTION	ENGR DATE	ANG=1°			(773) 53	39-4060		

(10.0)