
4-40 THREAD






MATERIAL:

.062 (1.57) thick Steel, Zinc Plate

4-40 THREAD






MATERIAL:

.062 (1.57) thick Steel, Zinc Plate

4-40 THREAD





MATERIAL:


.047 (1.19) thick Brass, Tin Plate

CAT. NO. 616

6-32 THREAD



CAT. NO. 612



MATERIAL:


.032 (.81) thick Brass, Nickel Plate

6-32 THREAD



CAT. NO. 614

CAT. NO. 621




MATERIAL:

.032 (.81) thick Brass, Tin Plate

6-32 THREAD






MATERIAL:

.032 (.81) thick Brass, Tin Plate

6-32 THREAD




CAT. NO. 634



CAT. NO. 4334


.062 (1.57) thick Steel, Nickel Plate

MATERIAL:



CAT. NO. 708

6-32 THREAD




.062 (1.57) thick Steel, Nickel Plate

6-32 THREAD



CAT. NO. 630



MATERIAL:

.062 (1.57) thick Steel, Tin Plate


6-32 or 8-32 THREAD



4332


6-32

8-32



8-32 THREAD





CAT. NO. 611


MATERIAL: .037 (.94) thick Brass, Tin Plate

8-32 THREAD



CAT. NO. 631

CAT. NO. 617




.037 (.94) thick Steel, Tin Plate


Tel (718) 956-8900 • Fax (718) 956-9040 (800) 221-5510 • kec@keyelco.com

Nickel Plate

.062 (1.57) thick Brass,

KEYSTONE Rohs Compliant - ISO 9001 CERTIFIED





CAT.					D HOLE		E HOLE	T	
NO.	A	В	C	D	DIAMETER	E	DIAMETER	MATERIAL	FINISH
633	.375 (9.5)	.375 (9.5)	.281 (7.1)	.218 (5.5)	.140 (3.6)	.218 (5.5)	.140 (3.6)	.032 (.81) Brass	Nickel
613	.390 (9.9)	.453 (11.5)	.375 (9.5)	.234 (5.9)	.147 (3.7)	.299 (7.6)	.128 (3.3)	.032 (.81) Brass	Nickel
615	.420 (10.7)	.343 (8.7)	.281 (7.1)	.281 (7.1)	.144 (3.7)	.203 (5.2)	.128 (3.3)	.032 (.81) Brass	Tin
4335	.562 (14.3)	.562 (14.3)	.500 (12.7)	.412 (10.5)	.120 (3.0)	.411 (10.4)	.120 (3.0)	.062 (1.57) Steel	Nickel
4336	.562 (14.3)	.562 (14.3)	.500 (12.7)	.412 (10.5)	.144 (3.7)	.412 (10.5)	.144 (3.7)	.062 (1.57) Steel	Nickel
618	.628 (16.0)	.628 (16.0)	.375 (9.5)	.378 (9.6)	.169 (4.3)	.378 (9.6)	.169 (4.3)	.050 (1.27) Brass	Tin
619	.687 (17.4)	.687 (17.4)	.375 (9.5)	.500 (12.7)	.144 (3.7)	.500 (12.7)	.144 (3.7)	.032 (.81) Steel	Tin
4326	1.013 (25.7)	.487 (12.4)	.312 (7.9)	.816 (20.7)	.140 (3.6)	.332 (8.4)	.140 (3.6)	.050 (1.27) Steel	Nickel
620	1.156 (29.4)	.656 (16.7)	.375 (9.5)	.906 (23.0)	.169 (4.3)	.420 (10.7)	.169 (4.3)	.032 (.81) Steel	Tin

BOARD BRACKETS


Originally designed for our line of standardized terminal boards; these brackets can also be used in other applications.

Choice of Steel or Aluminum

MATERIALS:


.062 (1.57) thick Steel, Nickel Plate .062 (1.57) thick Aluminum

STEEL ALUMINUM					For Use With Board No.		ard No.'s
CAT. NO.	CAT. NO.	W	L	S	(Refer to page 130)		
1556	622	.375 (9.5)	1.625 (41.3)	1.000 (25.4)	15032	15072	15092
1567	623	.375 (9.5)	2.125 (54.0)	1.500 (38.1)	15033	15073	15093
1568	624	.375 (9.5)	2.625 (66.7)	2.000 (50.8)	15034	15074	15094
1569	625	.375 (9.5)	3.125 (79.4)	2.500 (63.5)	15035	15075	15095
1570	626	.281 (7.1)	1.187 (30.1)	.750 (19.1)	15022	15024	15030
1571	627	.281 (7.1)	1.625 (41.3)	1.187 (30.1)	15036	15076	15096









CAT. NO. 1564



MATERIAL:

CAT. NO. 4337

.080 (2.03) thick Aluminum

.203 [5.2]


THREADED PC MOUNT BRACKETS

• Snaps in for wave soldering • Reduces assembly time • Easily mount into predrilled or punched holes • Stable no rock design





SNAP-IN

PC MOUNT









CAT. NO. 7779

Tel (718) 956-8900 • Fax (718) 956-9040

(800) 221-5510 • kec@keyelco.com

KEYSTONE Rohs Compliant - ISO 9001 CERTIFIED

www.keyelco.com

31-07 20th Road - Astoria, NY 11105-2017