

Rail-to-rail input/output 8 MHz operational amplifiers

Features

- Rail-to-rail input and output
- Wide bandwidth
- Low power consumption: 1.1 mA max.
- Unity gain stability
- High output current: 35 mA
- Operating from 2.5 V to 5.5 V
- Low input bias current, 1 pA typ
- ESD internal protection ≥ 5 kV
- Latch-up immunity

Applications


- Battery-powered applications
- Portable devices
- Signal conditioning
- Active filtering
- Medical instrumentation
- Automotive applications

Description

The TSV911/2/4 family of single, dual and quad operational amplifiers offers low voltage operation and rail-to-rail input and output.

This family features an excellent speed/power consumption ratio, offering an 8 MHz gain-bandwidth product while consuming only 1.1 mA max at 5 V supply voltage. These op-amps are unity gain stable for capacitive loads up to 200 pF. They also feature an ultra-low input bias current.

These characteristics make the TSV911/2/4 family ideal for sensor interfaces, battery-supplied and portable applications, as well as active filtering.



1 Absolute maximum ratings and operating conditions

Table 1. Absolute maximum ratings (AMR)

| Symbol | Parameter | Value | Unit | |
|------------|-----------------------------------------------------------|------------------------------|------|---|
| V_{CC} | Supply voltage ⁽¹⁾ | 6 | V | |
| V_{id} | Differential input voltage ⁽²⁾ | $\pm V_{CC}$ | V | |
| V_{in} | Input voltage ⁽³⁾ | $V_{DD}-0.2$ to $V_{CC}+0.2$ | V | |
| T_{stg} | Storage temperature | -65 to +150 | °C | |
| R_{thja} | Thermal resistance junction to ambient ^{(4) (5)} | | °C/W | |
| | SOT23-5 | 250 | | |
| | SO-8 | 125 | | |
| | MiniSO-8 | 190 | | |
| | SO-14 | 103 | | |
| R_{thjc} | Thermal resistance junction to case ^{(4) (5)} | | °C/W | |
| | SOT23-5 | 81 | | |
| | SO-8 | 40 | | |
| | MiniSO-8 | 39 | | |
| | SO-14 | 31 | | |
| T_j | Maximum junction temperature | 150 | °C | |
| | | | | |
| ESD | HBM: human body model ⁽⁶⁾ | 5 | kV | |
| | MM: machine model ⁽⁷⁾ | 300 | V | |
| | CDM: charged device model ⁽⁸⁾ | SOT23-5, SO-8, MiniSO-8 | 1500 | V |
| | | TSSOP14 | 750 | |
| SO-14 | | 500 | | |
| | Latch-up immunity | 200 | mA | |

1. All voltage values, except differential voltage are with respect to network ground terminal.
2. Differential voltages are the non-inverting input terminal with respect to the inverting input terminal.
3. $V_{CC}-V_{in}$ must not exceed 6V.
4. Short-circuits can cause excessive heating and destructive dissipation.
5. R_{th} are typical values.
6. Human body model: A 100pF capacitor is charged to the specified voltage, then discharged through a 1.5kΩ resistor between two pins of the device. This is done for all couples of connected pin combinations while the other pins are floating.
7. Machine model: A 200pF capacitor is charged to the specified voltage, then discharged directly between two pins of the device with no external series resistor (internal resistor < 5Ω). This is done for all couples of connected pin combinations while the other pins are floating.
8. Charged device model: all pins and the package are charged together to the specified voltage and then discharged directly to the ground through only one pin. This is done for all pins.

Table 2. Operating conditions

| Symbol | Parameter | Value | Unit |
|------------|--------------------------------------|----------------------------------|------|
| V_{CC} | Supply voltage | 2.5 to 5.5 | V |
| V_{icm} | Common mode input voltage range | $V_{DD} - 0.1$ to $V_{CC} + 0.1$ | V |
| T_{oper} | Operating free air temperature range | -40 to +125 | °C |

2 Electrical characteristics

Table 3. Electrical characteristics at $V_{CC} = +2.5V$ with $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, R_L connected to $V_{CC}/2$, full temperature range (unless otherwise specified)⁽¹⁾

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-----------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|------|-------|------------|------------------------|
| DC performance | | | | | | |
| V_{io} | Offset voltage TSV91x | $T = 25^\circ C$ $T_{min} < T_{op} < T_{max}$ | - | 0.1 | 4.5 | mV |
| | TSV91xA | $T = 25^\circ C$ $T_{min} < T_{op} < T_{max}$ | - | - | 7.5 | |
| DV_{io}/DT | Input offset voltage drift | | - | 2 | - | $\mu V/^\circ C$ |
| I_{io} | Input offset current | $T = 25^\circ C$ $T_{min} < T_{op} < T_{max}$ | - | 1 | $10^{(2)}$ | pA |
| I_{ib} | Input bias current | $T = 25^\circ C$ $T_{min} < T_{op} < T_{max}$ | - | - | 100 | pA |
| CMR | Common mode rejection ratio $20 \log (\Delta V_{ic}/\Delta V_{io})$ | $0V$ to $2.5V$, $V_{out} = 1.25V$ | 58 | 75 | - | dB |
| A_{vd} | Large signal voltage gain | $R_L = 10k\Omega$, $V_{out} = 0.5V$ to $2V$, $T = 25^\circ C$ $T_{min} < T_{op} < T_{max}$ | 80 | 89 | - | dB |
| $V_{CC}-V_{OH}$ | High level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | | 15 | 40 | mV |
| V_{OL} | Low level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | - | 15 | 40 | mV |
| I_{out} | I_{sink} | $V_o = 2.5V$, $T = 25^\circ C$ $T_{min} < T_{amb} < T_{max}$ | 18 | 32 | - | mA |
| | I_{source} | $V_o = 0V$, $T = 25^\circ C$ $T_{min} < T_{amb} < T_{max}$ | 16 | - | - | |
| I_{CC} | Supply current (per operator) | No load, $V_{out} = V_{CC}/2$ | - | 0.78 | 1.1 | mA |
| AC performance | | | | | | |
| GBP | Gain bandwidth product | $R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$, $T = 25^\circ C$ | - | 8 | - | MHz |
| F_u | Unity gain frequency | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^\circ C$ | | 7.2 | | MHz |
| ϕ_m | Phase margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^\circ C$ | - | 45 | - | Degrees |
| G_m | Gain margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^\circ C$ | - | 8 | - | dB |
| SR | Slew rate | $R_L = 2k\Omega$, $C_L = 100pF$, $A_v = 1$, $T = 25^\circ C$ | - | 4.5 | - | $V/\mu s$ |
| e_n | Equivalent input noise voltage | $f = 10kHz$, $T = 25^\circ C$ | - | 21 | - | $\frac{nV}{\sqrt{Hz}}$ |
| THD+ e_n | Total harmonic distortion | $G = 1$, $f = 1kHz$, $R_L = 2k\Omega$, $Bw = 22kHz$, $T = 25^\circ C$, $V_{icm} = (V_{CC} + 1)/2$, $V_{out} = 1.1V_{pp}$ | - | 0.001 | - | % |

1. All parameter limits at temperatures other than $25^\circ C$ are guaranteed by correlation.
2. Guaranteed by design.

Table 4. Electrical characteristics at $V_{CC} = +3.3V$ with $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, R_L connected to $V_{CC}/2$, full temperature range (unless otherwise specified)⁽¹⁾

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-----------------------|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------|--------|------------|------------------------|
| DC performance | | | | | | |
| V_{io} | Offset voltage TSV91x | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 0.1 | 4.5 | mV |
| | TSV91xA | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | - | 7.5 | |
| DV_{io} | Input offset voltage drift | | - | 2 | - | $\mu V/^{\circ}C$ |
| I_{io} | Input offset current | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 1 | $10^{(2)}$ | pA |
| I_{ib} | Input bias current | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | - | 100 | |
| I_{ib} | Input bias current | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 1 | $10^{(2)}$ | pA |
| CMR | Common mode rejection ratio $20 \log (\Delta V_{ic}/\Delta V_{io})$ | $0V$ to $3.3V$, $V_{out} = 1.65V$ | 60 | 78 | - | |
| A_{vd} | Large signal voltage gain | $R_L = 10k\Omega$, $V_{out} = 0.5V$ to $2.8V$, $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | 80 | 90 | - | dB |
| $V_{CC}-V_{OH}$ | High level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | | 15 | 40 | |
| V_{OL} | Low level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | - | 45 | 150 | mV |
| I_{out} | I_{sink} | $V_o = 3.3V$, $T = 25^{\circ}C$ $T_{min} < T_{amb} < T_{max}$ | 18 | 32 | - | |
| | I_{source} | $V_o = 0V$, $T = 25^{\circ}C$ $T_{min} < T_{amb} < T_{max}$ | 16 | - | - | |
| I_{CC} | Supply current (per operator) | No load, $V_{out} = V_{CC}/2$ | - | 0.8 | 1.1 | mA |
| AC performance | | | | | | |
| GBP | Gain bandwidth product | $R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$, $T = 25^{\circ}C$ | - | 8 | - | MHz |
| F_u | Unity gain frequency | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 7.2 | - | MHz |
| ϕ_m | Phase margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 45 | - | Degrees |
| G_m | Gain margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 8 | - | dB |
| SR | Slew rate | $R_L = 2k\Omega$, $C_L = 100pF$, $A_v = 1$, $T = 25^{\circ}C$ | - | 4.5 | - | $V/\mu s$ |
| e_n | Equivalent input noise voltage | $f = 10kHz$, $T = 25^{\circ}C$ | - | 21 | - | $\frac{nV}{\sqrt{Hz}}$ |
| THD+ e_n | Total harmonic distortion | $G = 1$, $f = 1kHz$, $R_L = 2k\Omega$, $BW = 22kHz$, $V_{icm} = (V_{CC} + 1)/2$, $V_{out} = 1.9V_{pp}$, $T = 25^{\circ}C$ | - | 0.0007 | - | % |

1. All parameter limits at temperatures other than $25^{\circ}C$ are guaranteed by correlation.

2. Guaranteed by design.

Table 5. Electrical characteristics at $V_{CC} = +5V$ with $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, R_L connected to $V_{CC}/2$, full temperature range (unless otherwise specified)⁽¹⁾

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-----------------------|---------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------|--------|------------|------------------------|
| DC performance | | | | | | |
| V_{io} | Offset voltage TSV91x | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 0.1 | 4.5 | mV |
| | TSV91xA | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | - | 7.5 | |
| DV_{io} | Input offset voltage drift | | - | 2 | - | $\mu V/^{\circ}C$ |
| I_{io} | Input offset current | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 1 | $10^{(2)}$ | pA |
| | | | - | - | 100 | |
| I_{ib} | Input bias current | $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | - | 1 | $10^{(2)}$ | pA |
| | | | - | - | 100 | |
| CMR | Common mode rejection ratio $20 \log (\Delta V_{ic}/\Delta V_{io})$ | $0V$ to $5V$, $V_{out} = 2.5V$ | 62 | 82 | - | dB |
| SVR | Supply voltage rejection ratio $20 \log (\Delta V_{CC}/\Delta V_{io})$ | $V_{CC} = 2.5$ to $5V$ | 70 | 86 | - | dB |
| A_{vd} | Large signal voltage gain | $R_L = 10k\Omega$, $V_{out} = 0.5V$ to $4.5V$, $T = 25^{\circ}C$ $T_{min} < T_{op} < T_{max}$ | 80 | 91 | - | dB |
| | | | 75 | | | |
| $V_{CC}-V_{OH}$ | High level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | | 15 | 40 | mV |
| | | | | 45 | 150 | |
| V_{OL} | Low level output voltage | $R_L = 10k\Omega$ $R_L = 600\Omega$ | - | 15 | 40 | mV |
| | | | | 45 | 150 | |
| I_{out} | I_{sink} | $V_o = 5V$, $T = 25^{\circ}C$ $T_{min} < T_{amb} < T_{max}$ | 18 | 32 | - | mA |
| | I_{source} | $V_o = 0V$, $T = 25^{\circ}C$ $T_{min} < T_{amb} < T_{max}$ | 16 | - | - | |
| | | | 18 | 35 | - | |
| | | | 16 | - | - | |
| I_{CC} | Supply current (per operator) | No load, $V_{out} = 2.5V$ | - | 0.82 | 1.1 | mA |
| AC performance | | | | | | |
| GBP | Gain bandwidth product | $R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$, $T = 25^{\circ}C$ | - | 8 | - | MHz |
| F_u | Unity gain frequency | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 7.5 | - | MHz |
| ϕ_m | Phase margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 45 | - | Degrees |
| G_m | Gain margin | $R_L = 2k\Omega$, $C_L = 100pF$, $T = 25^{\circ}C$ | - | 8 | - | dB |
| SR | Slew rate | $R_L = 2k\Omega$, $C_L = 100pF$, $A_v = 1$, $T = 25^{\circ}C$ | - | 4.5 | - | $V/\mu s$ |
| e_n | Equivalent input noise voltage | $f = 1kHz$, $T = 25^{\circ}C$ | - | 27 | - | $\frac{nV}{\sqrt{Hz}}$ |
| | | $f = 10kHz$, $T = 25^{\circ}C$ | - | 21 | - | |
| THD+ e_n | Total harmonic distortion | $G = 1$, $f = 1kHz$, $R_L = 2k\Omega$, $Bw = 22kHz$, $T = 25^{\circ}C$, $V_{icm} = (V_{CC} + 1)/2$, $V_{out} = 3.6V_{pp}$ | - | 0.0004 | - | % |

1. All parameter limits at temperatures other than $25^{\circ}C$ are guaranteed by correlation.
2. Guaranteed by design.

Figure 1. Input offset voltage distribution at T = 25°C




Figure 2. Input offset voltage distribution at T = 125°C




Figure 3. Supply current vs. input common mode voltage at V_{CC} = 2.5V




Figure 4. Supply current vs. input common mode voltage at V_{CC} = 5V




Figure 5. Output current vs. output voltage at V_{CC} = 2.5V




Figure 6. Output current vs. output voltage at V_{CC} = 5V




Figure 7. Voltage gain and phase vs frequency at $V_{CC}= 2.5V$ and $V_{icm}= 0.5V$




Figure 8. Voltage gain and phase vs frequency at $V_{CC}= 5.5V$ and $V_{icm}= 0.5V$




Figure 9. Phase margin vs. capacitive load




Figure 10. Phase margin vs. output current




Figure 11. Positive slew rate




Figure 12. Negative slew rate




Figure 13. Distorsion + noise vs. frequency




Figure 14. Distorsion + noise vs. output voltage




Figure 15. Noise vs. frequency





Figure 16. Phase margin vs. capacitive load and serial resistor



3 Package information

In order to meet environmental requirements, STMicroelectronics offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an STMicroelectronics trademark. ECOPACK specifications are available at: www.st.com.

Note: All packages are Moisture Sensitivity Level 1 as per Jedec J-STD-020-C, except SO-14 which is Jedec level 3.

3.1 SOT23-5 package information

Figure 17. SOT23-5 package mechanical drawing




Table 6. SOT23-5 package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|-------|------|-------|
| | Millimeters | | | Mils | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 0.90 | | 1.45 | 35.4 | | 57.1 |
| A1 | 0.00 | | 0.15 | 0.00 | | 5.9 |
| A2 | 0.90 | | 1.30 | 35.4 | | 51.2 |
| b | 0.35 | | 0.50 | 13.7 | | 19.7 |
| C | 0.09 | | 0.20 | 3.5 | | 7.8 |
| D | 2.80 | | 3.00 | 110.2 | | 118.1 |
| E | 2.60 | | 3.00 | 102.3 | | 118.1 |
| E1 | 1.50 | | 1.75 | 59.0 | | 68.8 |
| e | | 0.95 | | | 37.4 | |
| e1 | | 1.9 | | | 74.8 | |
| L | 0.35 | | 0.55 | 13.7 | | 21.6 |

3.2 MiniSO-8 package information

Figure 18. MiniSO-8 package mechanical drawing




Table 7. MiniSO-8 package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 1.1 | | | 0.043 |
| A1 | 0 | | 0.15 | 0 | | 0.006 |
| A2 | 0.75 | 0.85 | 0.95 | 0.030 | 0.033 | 0.037 |
| b | 0.22 | | 0.40 | 0.009 | | 0.016 |
| c | 0.08 | | 0.23 | 0.003 | | 0.009 |
| D | 2.80 | 3.00 | 3.20 | 0.11 | 0.118 | 0.126 |
| E | 4.65 | 4.90 | 5.15 | 0.183 | 0.193 | 0.203 |
| E1 | 2.80 | 3.00 | 3.10 | 0.11 | 0.118 | 0.122 |
| e | | 0.65 | | | 0.026 | |
| L | 0.40 | 0.60 | 0.80 | 0.016 | 0.024 | 0.031 |
| L1 | | 0.95 | | | 0.037 | |
| L2 | | 0.25 | | | 0.010 | |
| k | 0° | | 8° | 0° | | 8° |
| ccc | | | 0.10 | | | 0.004 |

3.3 SO-8 package information

Figure 19. SO-8 package mechanical drawing




Table 8. SO-8 package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 1.75 | | | 0.069 |
| A1 | 0.10 | | 0.25 | 0.004 | | 0.010 |
| A2 | 1.25 | | | 0.049 | | |
| b | 0.28 | | 0.48 | 0.011 | | 0.019 |
| c | 0.17 | | 0.23 | 0.007 | | 0.010 |
| D | 4.80 | 4.90 | 5.00 | 0.189 | 0.193 | 0.197 |
| H | 5.80 | 6.00 | 6.20 | 0.228 | 0.236 | 0.244 |
| E1 | 3.80 | 3.90 | 4.00 | 0.150 | 0.154 | 0.157 |
| e | | 1.27 | | | 0.050 | |
| h | 0.25 | | 0.50 | 0.010 | | 0.020 |
| L | 0.40 | | 1.27 | 0.016 | | 0.050 |
| k | 1° | | 8° | 1° | | 8° |
| ccc | | | 0.10 | | | 0.004 |

3.4 TSSOP14 package information

Figure 20. TSSOP14 package mechanical drawing




Table 9. TSSOP14 package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|----------|------|--------|------------|--------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 1.2 | | | 0.047 |
| A1 | 0.05 | | 0.15 | 0.002 | 0.004 | 0.006 |
| A2 | 0.8 | 1 | 1.05 | 0.031 | 0.039 | 0.041 |
| b | 0.19 | | 0.30 | 0.007 | | 0.012 |
| c | 0.09 | | 0.20 | 0.004 | | 0.0089 |
| D | 4.9 | 5 | 5.1 | 0.193 | 0.197 | 0.201 |
| E | 6.2 | 6.4 | 6.6 | 0.244 | 0.252 | 0.260 |
| E1 | 4.3 | 4.4 | 4.48 | 0.169 | 0.173 | 0.176 |
| e | | 0.65 BSC | | | 0.0256 BSC | |
| K | 0° | | 8° | 0° | | 8° |
| L1 | 0.45 | 0.60 | 0.75 | 0.018 | 0.024 | 0.030 |

3.5 SO-14 package information

Figure 21. SO-14 package mechanical drawing




Table 10. SO-14 package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 1.75 | | | 0.068 |
| a1 | 0.1 | | 0.2 | 0.003 | | 0.007 |
| a2 | | | 1.65 | | | 0.064 |
| b | 0.35 | | 0.46 | 0.013 | | 0.018 |
| b1 | 0.19 | | 0.25 | 0.007 | | 0.010 |
| C | | 0.5 | | | 0.019 | |
| c1 | 45° (typ.) | | | | | |
| D | 8.55 | | 8.75 | 0.336 | | 0.344 |
| E | 5.8 | | 6.2 | 0.228 | | 0.244 |
| e | | 1.27 | | | 0.050 | |
| e3 | | 7.62 | | | 0.300 | |
| F | 3.8 | | 4.0 | 0.149 | | 0.157 |
| G | 4.6 | | 5.3 | 0.181 | | 0.208 |
| L | 0.5 | | 1.27 | 0.019 | | 0.050 |
| M | | | 0.68 | | | 0.026 |
| S | 8° (max.) | | | | | |

4 Ordering information

Table 11. Order codes⁽¹⁾

| Order code | Temperature range | Package | Packing | Marking |
|---------------------------------------------------------|--------------------------------|--------------------------------|------------------------|---------|
| TSV911ID TSV911IDT | -40°C to +125°C | SO-8 | Tube or Tape & reel | V911I |
| TSV911AID TSV911AIDT | | | | V911AI |
| TSV911ILT | | SOT23-5 | Tape & reel | K127 |
| TSV911AILT | | | | K128 |
| TSV912IST | | | | K125 |
| TSV912AIST | | MiniSO-8 | | K126 |
| TSV912ID TSV912IDT | | SO-8 | Tube or Tape & reel | V912I |
| TSV912AID TSV912AIDT | | | | V912AI |
| TSV914IPT | | TSSOP14 | Tape & reel | V914I |
| TSV914AIPT | | | | V914AI |
| TSV914ID TSV914IDT | | SO-14 ⁽¹⁾ | | V914I |
| TSV914AID TSV914AIDT | | | | V914AI |
| TSV911IYD ⁽²⁾ TSV911IYDT ⁽²⁾ | | SO-8 Automotive grade level | Tube or Tape & reel | V911IY |
| TSV911AIYD ⁽²⁾ TSV911AIYDT ⁽²⁾ | | | | V911AY |
| TSV912IYD ⁽²⁾ TSV912IYDT ⁽²⁾ | | | | V912IY |
| TSV912AIYD ⁽²⁾ TSV912AIYDT ⁽²⁾ | | | | V912AY |
| TSV914IYD ⁽²⁾ TSV914IYDT ⁽²⁾ | | | | V914IY |
| TSV914AIYD ⁽²⁾ TSV914AIYDT ⁽²⁾ | | | | V914AY |
| TSV914ID TSV914IDT | | SO-14 ⁽¹⁾ | | V914I |
| TSV914AID TSV914AIDT | | | | V914AI |
| TSV911IYD ⁽²⁾ TSV911IYDT ⁽²⁾ | SO-8 Automotive grade level | Tube or Tape & reel | V911IY | |
| TSV911AIYD ⁽²⁾ TSV911AIYDT ⁽²⁾ | | | V911AY | |
| TSV912IYD ⁽²⁾ TSV912IYDT ⁽²⁾ | SO-8 Automotive grade level | Tube or Tape & reel | V912IY | |
| TSV912AIYD ⁽²⁾ TSV912AIYDT ⁽²⁾ | | | V912AY | |
| TSV914IYD ⁽²⁾ TSV914IYDT ⁽²⁾ | SO-14 ⁽¹⁾ | | V914IY | |
| TSV914AIYD ⁽²⁾ TSV914AIYDT ⁽²⁾ | | | V914AY | |

1. All packages are Moisture Sensitivity Level 1 as per Jec J-STD-020-C, except SO-14 which is Jec level 3.

2. Qualification and characterization according to AEC Q100 and Q003 or equivalent, advanced screening according to AEC Q001 & Q 002 or equivalent are on-going.

5 Revision history

Table 12. Document revision history

| Date | Revision | Changes |
|-------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 28-Aug-2006 | 1 | First release. |
| 07-Jun-2007 | 2 | Modified ESD CDM parameter for SO-14 package in Table 1: Absolute maximum ratings (AMR) . Noise parameters updated in Section 2: Electrical characteristics . Added limits in temperature in Section 2: Electrical characteristics . Added automotive grade level description in Table 11: Order codes . Added footnote about SO-14 package in Table 11: Order codes . Added Figure 16: Phase margin vs. capacitive load and serial resistor . |
| 11-Feb-2008 | 3 | Updated footnotes for ESD parameters in Table 1: Absolute maximum ratings (AMR) . Corrected MiniSO-8 package information in Table 7: MiniSO-8 package mechanical data . Added missing markings for order codes TSV911AILT and TSV912AILT in Table 11: Order codes . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2008 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com