

Not Recommended for New Designs

This product was manufactured for Maxim by an outside wafer foundry using a process that is no longer available. It is not recommended for new designs. The data sheet remains available for existing users.

A Maxim replacement or an industry second-source may be available. Please see the QuickView data sheet for this part or contact technical support for assistance.

For further information, [contact Maxim's Applications Tech Support](#).



High-Precision, Low-Voltage, Micropower Op Amp

MAX480

General Description

The MAX480 is a precision micropower operational amplifier with flexible power-supply capability. Its guaranteed 140 μ V maximum offset voltage (25 μ V typ) is the lowest of any micropower op amp. Similarly, input bias current, input offset current, and drift specifications are within tight limits.


Both the input and output voltage ranges include the negative supply rail, allowing maximum signal range capability in single-supply applications. The MAX480 operates with either a single supply ranging from +1.6V to +36V or dual supplies from ± 0.8 V to ± 18 V. The MAX480 consumes less than 20 μ A, allowing operation in excess of 10,000 hours from a 250mA-hr lithium coin cell. Even with a minimal quiescent current, the amplifier sinks or sources 5mA from its output.

The MAX480 is available in 8-pin DIP and SO packages in commercial, extended, and military temperature ranges.

Applications

Precision Micropower Amplifiers
 Micropower Signal Processing
 Battery-Powered Analog Circuits

Typical Operating Circuit




Features

- ◆ **Single- or Dual-Supply Operation: +1.6V to +36V, ± 0.8 V to ± 18 V**
- ◆ **True Single-Supply Operation: Input and Output Voltage Ranges Include Ground**
- ◆ **2.0 μ V/ $^{\circ}$ C Max Offset Voltage Drift**
- ◆ **20 μ A Max Supply Current**
- ◆ **5mA Min Output Drive**
- ◆ **140 μ V Max Input Offset Voltage**
- ◆ **3nA Max Input Bias Current**
- ◆ **500V/mV Min Open-Loop Gain**
- ◆ **Standard 741 Pinout with Nulling to V-**

Ordering Information

| PART | TEMP RANGE | PIN-PACKAGE |
|-----------|---------------------------------------|---------------|
| MAX480CPA | 0 $^{\circ}$ C to +70 $^{\circ}$ C | 8 Plastic DIP |
| MAX480CSA | 0 $^{\circ}$ C to +70 $^{\circ}$ C | 8 SO |
| MAX480EPA | -40 $^{\circ}$ C to +85 $^{\circ}$ C | 8 Plastic DIP |
| MAX480ESA | -40 $^{\circ}$ C to +85 $^{\circ}$ C | 8 SO |
| MAX480MJA | -55 $^{\circ}$ C to +125 $^{\circ}$ C | 8 CERDIP |

Pin Configuration



Maxim Integrated Products 1

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

High-Precision, Low-Voltage, Micropower Op Amp

ABSOLUTE MAXIMUM RATINGS

| | |
|--|--------------------------|
| Supply Voltage (V+ to V-) | ±18V |
| Differential Input Voltage | (V- - 20V) to (V+ + 20V) |
| Common-Mode Input Voltage | (V- - 20V) to (V+ + 20V) |
| Output Short-Circuit Duration | Indefinite |
| Continuous Power Dissipation | |
| Plastic DIP (derate 9.09mW/°C above +70°C) | 727mW |
| SO (derate 5.88mW/°C above +70°C) | 471mW |
| CERDIP (derate 8.0mW/°C above +70°C) | 640mW |

Operating Temperature Ranges

| | |
|--|-----------------|
| MAX480C_A | 0°C to +70°C |
| MAX480E_A | -40°C to +85°C |
| MAX480MJA | -55°C to +125°C |
| Junction Temperature (T _J) | -65°C to +150°C |
| Storage Temperature Range | -65°C to +150°C |
| Lead Temperature (soldering, 10sec) | +300°C |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V_S = ±1.5V to ±15V, T_A = +25°C, unless otherwise noted.)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS |
|------------------------------------|-------------------|--|------------------------|-----|-------|-------|
| Input Offset Voltage | V _{OS} | | | 25 | 140 | μV |
| Input Offset Current | I _{OS} | V _{CM} = 0 | | 0.2 | 4 | nA |
| Input Bias Current | I _B | V _{CM} = 0 | | 1 | 10 | nA |
| Large-Signal Voltage Gain | A _{VO} | V _S = ±15V, V _O = ±10V | R _L = 100kΩ | 500 | 1200 | V/mV |
| | | | R _L = 10kΩ | 200 | 600 | |
| | | V ₊ = 5V, V ₋ = 0, 1V < V _O < 4V | R _L = 2kΩ | 75 | 250 | |
| | | | R _L = 10kΩ | 100 | 400 | |
| Input Voltage | IVR | V ₊ = 5V, V ₋ = 0 | 0/4 | | V | |
| | | V _S = ±15V (Note 1) | -15/13.5 | | | |
| Output Voltage Swing | V _O | V _S = ±15V | R _L = 10kΩ | ±14 | ±14.2 | V |
| | | | R _L = 2kΩ | ±10 | ±12 | |
| | V _{OH} | V ₊ = 5V, V ₋ = 0, R _L = 2kΩ | 4.0 | 4.2 | | |
| | V _{OL} | V ₊ = 5V, V ₋ = 0, R _L = 10kΩ | | 100 | 500 | μV |
| Common-Mode Rejection Ratio | CMRR | V ₊ = 5V, V ₋ = 0, 0 < V _{CM} < 4V | 85 | 110 | dB | |
| | | V _S = ±15V, -15V < V _{CM} < 13.5V | 90 | 130 | | |
| Power-Supply Rejection Ratio | PSRR | | | 1.0 | 12 | μV/V |
| Slew Rate | SR | V _S = ±15V | | 12 | | V/ms |
| Supply Current | I _{SY} | V _S = ±1.5V | | 9 | 15 | μA |
| | | V _S = ±15V | | 14 | 20 | |
| Capacitive Load Stability | | A _V = +1V/V, no oscillations (Note 2) | | 650 | | pF |
| Input Noise Voltage | e _{np-p} | f _O = 0.1Hz to 10Hz, V _S = ±15V | | 3 | | μVp-p |
| Differential-Mode Input Resistance | R _{IN} | V _S = ±15V | | 30 | | MΩ |
| Common-Mode Input Resistance | R _{INCM} | V _S = ±15V | | 20 | | GΩ |

High-Precision, Low-Voltage, Micropower Op Amp

MAX480

ELECTRICAL CHARACTERISTICS

($V_S = \pm 1.5V$ to $\pm 15V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.)

| PARAMETER | SYMBOL | CONDITIONS | MAX480C | | | MAX480E | | | MAX480M | | | UNITS |
|------------------------------|------------|---|--------------------|------------|------------|----------|------------|------------|----------|------------|-------------------|-------|
| | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| Input Offset Voltage | V_{OS} | | 40 | 220 | | 50 | 250 | | 70 | 300 | μV | |
| Input Offset Voltage Drift | TCV_{OS} | (Note 2) | 0.3 | 2.0 | | 0.3 | 2.0 | | 0.3 | 2.0 | $\mu V/^{\circ}C$ | |
| Input Offset Current | I_{OS} | $V_{CM} = 0$ | 0.2 | 5.0 | | 0.3 | 7.0 | | 0.5 | 10.0 | nA | |
| Input Bias Current | I_B | $V_{CM} = 0$ | 1 | 15 | | 2 | 20 | | 3 | 30 | nA | |
| Large-Signal Voltage Gain | A_{VO} | $V_S = \pm 15V$, $V = \pm 10V$ | $R_L = 100k\Omega$ | 350 | 950 | | 350 | 800 | | 60 | 400 | V/mV |
| | | | $R_L = 10k\Omega$ | 130 | 400 | | 130 | 400 | | 45 | 240 | |
| | | | $R_L = 2k\Omega$ | 55 | 125 | | 55 | 150 | | 30 | 110 | |
| | | $V_+ = 5V$, $V_- = 0$, $1V < V_O < 4V$ | $R_L = 100k\Omega$ | 50 | 360 | | 50 | 280 | | 35 | 200 | |
| | | | $R_L = 10k\Omega$ | 30 | 150 | | 30 | 140 | | 22 | 110 | |
| Input Voltage Range | IVR | $V_+ = 5V$, $V_- = 0$ | 0/3.5 | | | 0/3.5 | | | 0/3.5 | | V | |
| | | $V_S = \pm 15V$ (Note 1) | -15/13.5 | | | -15/13.5 | | | -15/13.5 | | | |
| Output Voltage Swing | V_O | $V_S = \pm 15V$ | $R_L = 10k\Omega$ | ± 13.5 | ± 14 | | ± 13.5 | ± 14 | | ± 13.5 | ± 13.7 | V |
| | | | $R_L = 2k\Omega$ | ± 9.5 | ± 11.8 | | ± 9.5 | ± 11.8 | | ± 10.5 | ± 11.5 | |
| | V_{OH} | $V_+ = 5V$, $V_- = 0$ $R_L = 2k\Omega$ | 3.9 | 4.1 | | 3.9 | 4.1 | | 3.9 | 4.1 | | |
| Common-Mode Rejection Ratio | CMRR | $V_+ = 5V$, $V_- = 0$, $0 < V_{CM} < 3.5V$ | 85 | 110 | | 85 | 110 | | 80 | 105 | dB | |
| | | $V_S = \pm 15V$, $-15V < V_{CM} < 13.5V$ | 90 | 120 | | 90 | 120 | | 85 | 115 | | |
| Power-Supply Rejection Ratio | PSRR | | 1.0 | 12 | | 1.0 | 12 | | 3.2 | 15 | $\mu V/V$ | |
| Supply Current | I_{SY} | $V_S = \pm 1.5V$ | 12 | 25 | | 13 | 25 | | 15 | 25 | μA | |
| | | $V_S = \pm 15V$ | 16 | 30 | | 17 | 30 | | 19 | 30 | | |

Note 1: Guaranteed by CMRR test.


Note 2: Guaranteed by design.

High-Precision, Low-Voltage, Micropower Op Amp


Typical Operating Characteristics

($T_A = +25^\circ\text{C}$, unless otherwise noted.)


INPUT OFFSET VOLTAGE vs. TEMPERATURE




INPUT OFFSET CURRENT vs. TEMPERATURE




INPUT BIAS CURRENT vs. TEMPERATURE




SUPPLY CURRENT vs. TEMPERATURE




OPEN-LOOP GAIN vs. SINGLE-SUPPLY VOLTAGE




OPEN-LOOP GAIN AND PHASE SHIFT vs. FREQUENCY




CLOSED-LOOP GAIN vs. FREQUENCY



OUTPUT VOLTAGE SWING vs. LOAD RESISTANCE



OUTPUT VOLTAGE SWING vs. LOAD RESISTANCE









High-Precision, Low-Voltage, Micropower Op Amp

MAX480

Typical Operating Characteristics (continued)

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



High-Precision, Low Voltage, Micropower Op Amp




Figure 1. Offset Nulling Circuit




Figure 2. Burn-In Circuit

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to www.maxim-ic.com/packages.)

TOP VIEW

FRONT VIEW

SIDE VIEW

NOTES:

1. D&E DO NOT INCLUDE MOLD FLASH.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED 0.15mm (.006").
3. LEADS TO BE COPLANAR WITHIN 0.10mm (.004").
4. CONTROLLING DIMENSION: MILLIMETERS.
5. MEETS JEDEC MS012.
6. N = NUMBER OF PINS.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.053 | 0.069 | 1.35 | 1.75 |
| A1 | 0.004 | 0.010 | 0.10 | 0.25 |
| B | 0.014 | 0.019 | 0.35 | 0.49 |
| C | 0.007 | 0.010 | 0.19 | 0.25 |
| e | 0.050 BSC | | 1.27 BSC | |
| E | 0.150 | 0.157 | 3.80 | 4.00 |
| H | 0.228 | 0.244 | 5.80 | 6.20 |
| L | 0.016 | 0.050 | 0.40 | 1.27 |

VARIATIONS:

| DIM | INCHES | | MILLIMETERS | | N | MS012 |
|-----|--------|-------|-------------|-------|----|-------|
| | MIN | MAX | MIN | MAX | | |
| D | 0.189 | 0.197 | 4.80 | 5.00 | 8 | AA |
| D | 0.337 | 0.344 | 8.55 | 8.75 | 14 | AB |
| D | 0.386 | 0.394 | 9.80 | 10.00 | 16 | AC |

DALLAS SEMICONDUCTOR **MAXIM**

PROPRIETARY INFORMATION

TITLE:
PACKAGE OUTLINE, .150" SOIC

| | | |
|----------|---------------------------------|------------|
| APPROVAL | DOCUMENT CONTROL NO. 21-0041 | REV. B 1/1 |
|----------|---------------------------------|------------|

SOICN, EPS

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

6 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**