

# 500MHz, 2200V/ $\mu$ s Gain of 2, Single Supply Triple Video Amplifier with Input Bias Control

## FEATURES

- **-3dB Small-Signal Bandwidth: 500MHz**
- **-3dB 2V<sub>P-P</sub> Large-Signal Bandwidth: 400MHz**
- **Slew Rate: 2200V/ $\mu$ s**
- **Fixed Gain of 2, No External Resistors Required**
- **AC Coupling with Programmable DC Input Bias**
- **Output Swings to 0.8V of Supply Rails**
- **Full Video Swing with 5V Single Supply**
- Diff Gain: 0.02%
- Diff Phase: 0.05°
- Enable/Shutdown Pin
- High Output Current:  $\pm 100$ mA
- Supply Range: 3V to 7.5V
- Operating Temperature Range: -40°C to 85°C
- Available in 16-Lead SSOP and 5mm  $\times$  3mm DFN Packages

## APPLICATIONS

- LCD Video Projectors
- RGB HD Video Amplifiers
- Coaxial Cable Drivers
- Low Supply ADC Drivers

## DESCRIPTION

The LT<sup>®</sup>6557 is a high speed triple video amplifier with an internal fixed gain of 2 and a programmable DC input bias voltage. This amplifier features a 400MHz 2V<sub>P-P</sub> signal bandwidth, 2200V/ $\mu$ s slew rate and a unique ability to drive heavy output loads to 0.8V of the supply rails, making the LT6557 ideal for a single 5V supply, wideband video application. With just one resistor, the inputs of all three amplifiers can be programmed to a common voltage level, simplifying and reducing the need for external circuitry in the AC-coupled applications. Without the programmable resistor, the input bias circuit becomes inactive, allowing the use of an external clamp circuit or direct coupled input.


The LT6557 has separate power supply and ground pins for each amplifier to improve channel separation and to ease power supply bypassing. The LT6557 provides uncompromised performance in many high speed applications where a low voltage, single supply is required.

The LT6557 is available in 16-lead SSOP and 5mm  $\times$  3mm DFN packages.


LT, LT, LTC and LTM are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

## TYPICAL APPLICATION

AC-Coupled Triple Video Driver





Fast Large-Signal Transient Response



**ABSOLUTE MAXIMUM RATINGS** (Note 1)

|  |                   |                                      |                |
|--|-------------------|--------------------------------------|----------------|
| Total Supply Voltage ( $V_S^+$ to GND) ..... | 7.5V              | Junction Temperature                 |                |
| Input Current.....                           | $\pm 10\text{mA}$ | SSOP .....                           | 150°C          |
| Output Current (Note 2) .....                | $\pm 70\text{mA}$ | DFN.....                             | 125°C          |
| Output Short-Circuit Duration (Note 2) ..... | Indefinite        | Storage Temperature Range            |                |
| Operating Temperature Range (Note 3) ...     | -40°C to 85°C     | SSOP .....                           | -65°C to 150°C |
| Specified Temperature Range (Note 4) ....    | -40°C to 85°C     | DFN.....                             | -65°C to 125°C |
|  |                   | Lead Temperature (Soldering, 10 sec) |                |
|  |                   | SSOP .....                           | 300°C          |

**PACKAGE/ORDER INFORMATION**

|   |                 |  |                   |
|---|-----------------|--|-------------------|
|  <p>GN PACKAGE<br/>16-LEAD PLASTIC SSOP<br/><math>T_{JMAX} = 150^\circ\text{C}</math>, <math>\theta_{JA} = 110^\circ\text{C/W}</math></p> |                 |  <p>DHC PACKAGE<br/>16-LEAD (5mm x 3mm) PLASTIC DFN<br/><math>T_{JMAX} = 125^\circ\text{C}</math>, <math>\theta_{JA} = 40^\circ\text{C/W}</math><br/>EXPOSED PAD (PIN 17) IS GND, MUST BE SOLDERED TO PCB</p> |                   |
| ORDER PART NUMBER   | GN PART MARKING | ORDER PART NUMBER  | DHC PART MARKING* |
| LT6557CGN   | 6557            | LT6557CDHC   | 6557              |
| LT6557IGN   | 6557I           | LT6557IDHC   | 6557              |

**Order Options** Tape and Reel: Add #TR  
 Lead Free: Add #PBF Lead Free Tape and Reel: Add #TRPBF  
 Lead Free Part Marking: <http://www.linear.com/leadfree/>

Consult LTC Marketing for parts specified with wider operating temperature ranges. \*The temperature grade is identified by a label on the shipping container.

**ELECTRICAL CHARACTERISTICS** The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at  $T_A = 25^\circ\text{C}$ .  $V_S = 5\text{V}$ ,  $R_L = 150\Omega$  to  $V_S/2$ ,  $V_{EN} = 0.4\text{V}$ ,  $R_{BCV} = \text{open}$ , unless otherwise noted.

| SYMBOL   | PARAMETER            | CONDITIONS   | MIN      | TYP        | MAX       | UNITS                          |
|----------|----------------------|--|----------|------------|-----------|--------------------------------|
| $V_{OS}$ | Input Offset Voltage | $V_{IN} = 1.25\text{V}$                                      |          | 12<br>15   | 40<br>50  | mV<br>mV                       |
| $I_{IN}$ | Input Current        | $V_{IN} = 1.25\text{V}$                                      |          | 35<br>45   | 70<br>100 | $\mu\text{A}$<br>$\mu\text{A}$ |
| $R_{IN}$ | Input Resistance     | $V_{IN} = 0.75\text{V}$ to $1.75\text{V}$ , BCV (Pin 6) Open | 90<br>50 | 200<br>150 |           | k $\Omega$<br>k $\Omega$       |
| $C_{IN}$ | Input Capacitance    | $f = 1\text{MHz}$  |          | 1.5        |           | pF                             |

6557fa

**ELECTRICAL CHARACTERISTICS** The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at  $T_A = 25^\circ\text{C}$ .  $V_S = 5\text{V}$ ,  $R_L = 150\Omega$  to  $V_S/2$ ,  $V_{EN} = 0.4\text{V}$ ,  $R_{BCV} = \text{open}$ , unless otherwise noted.

| SYMBOL        | PARAMETER                                  | CONDITIONS   | MIN | TYP                    | MAX                      | UNITS       |                                |
|---------------|--|--|-----|------------------------|--------------------------|-------------|--------------------------------|
| $A_V$ ERR     | Gain Error                                 | $V_{IN} = 0.75\text{V to } 1.75\text{V}$                                   | ●   | $\pm 0.5$<br>$\pm 0.5$ | $\pm 2.5$<br>$\pm 3.0$   | %<br>%      |                                |
| $A_V$ MATCH   | Gain Match Between Channels                | $V_{IN} = 0.75\text{V to } 1.75\text{V}$                                   | ●   | $\pm 0.4$<br>$\pm 0.4$ | $\pm 2.75$<br>$\pm 3.25$ | %<br>%      |                                |
| $V_{IN(DC)}$  | Input Voltage Bias                         | $R_{BCV} = 348\Omega$  | ●   | 1.0<br>0.8             | 1.25<br>1.10             | 1.5<br>1.7  | V<br>V                         |
| PSRR          | Power Supply Rejection Ratio               | $V_S = 4\text{V to } 6\text{V}$ , $V_{IN} = 1.25\text{V}$                  | ●   | 42<br>38               | 50<br>47                 |             | dB<br>dB                       |
| $V_{OL}$      | Output Voltage Swing Low                   |  | ●   | 0.8<br>0.9             | 0.9<br>1.0               |             | V<br>V                         |
| $V_{OH}$      | Output Voltage Swing High                  |  | ●   | 4.1<br>4.0             | 4.2<br>4.1               |             | V<br>V                         |
| $I_S$         | Supply Current per Amplifier               | $V_{EN} = 0.4\text{V}$ , $R_L = \infty$ , Includes $I_S$ of $V^+$ (Pin 15) | ●   |                        | 22.5<br>25.0             | 25<br>29    | mA<br>mA                       |
|               | Total Supply Current (Disabled)            | $V_{EN} = \text{Open}$ , $R_L = \infty$                                    | ●   |                        | 10<br>10                 | 450<br>1000 | $\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{EN}$      | Enable Pin Current                         | $V_{EN} = 0.4\text{V}$   | ●   | -250<br>-300           | -125<br>-150             |             | $\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{SC}$      | Short-Circuit Current                      |  | ●   | $\pm 70$<br>$\pm 40$   | $\pm 100$<br>$\pm 90$    |             | mA<br>mA                       |
| SR            | Slew Rate                                  | $V_{OUT} = 1.25\text{V to } 3.75\text{V}$ (Note 5)                         |     | 1400                   | 2200                     |             | V/ $\mu\text{s}$               |
| -3dB BW       | -3dB Bandwidth                             | $V_{OUT} = 2V_{P-P}$   |     |                        | 400                      |             | MHz                            |
|               |  | $V_{OUT} = 0.2V_{P-P}$   |     |                        | 500                      |             | MHz                            |
| 0.1dB BW      | Gain Flatness $\pm 0.1\text{dB}$ Bandwidth | $V_{OUT} = 2V_{P-P}$   |     |                        | 120                      |             | MHz                            |
| FPBW          | Full Power Bandwidth                       | $V_{OUT} = 2V_{P-P}$ (Note 6)  |     | 220                    | 350                      |             | MHz                            |
| XTalk         | All Hostile Crosstalk                      | $f = 10\text{MHz}$ , $V_{OUT} = 2V_{P-P}$                                  |     |                        | -80                      |             | dB                             |
|               |  | $f = 100\text{MHz}$ , $V_{OUT} = 2V_{P-P}$                                 |     |                        | -55                      |             | dB                             |
| $t_S$         | Settling Time                              | To 1%, $V_{OUT} = 1.5\text{V to } 3.5\text{V}$                             |     |                        | 4                        |             | ns                             |
|               |  | To 0.1%  |     |                        | 7                        |             | ns                             |
| $t_r$ , $t_f$ | Rise Time, Fall Time                       | 10% to 90%, $V_{OUT} = 1.5\text{V to } 3.5\text{V}$                        |     |                        | 875                      |             | ps                             |
| $\Delta G$    | Differential Gain                          | NTSC Signal  |     |                        | 0.02                     |             | %                              |
| $\Delta\Phi$  | Differential Phase                         | NTSC Signal  |     |                        | 0.05                     |             | Deg                            |
| HD2           | 2nd Harmonic Distortion                    | $f = 10\text{MHz}$ , $V_{OUT} = 2V_{P-P}$                                  |     |                        | -68                      |             | dBc                            |
| HD3           | 3rd Harmonic Distortion                    | $f = 10\text{MHz}$ , $V_{OUT} = 2V_{P-P}$                                  |     |                        | -75                      |             | dBc                            |

**Note 1:** Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

**Note 2:** A heat sink may be required to keep the junction temperature below the Absolute Maximum Rating.

**Note 3:** The LT6557C is guaranteed functional over the temperature range of  $-40^\circ\text{C}$  and  $85^\circ\text{C}$ .

**Note 4:** The LT6557C is guaranteed to meet specified performance from  $0^\circ\text{C}$  to  $70^\circ\text{C}$ . The LT6557C is designed, characterized and expected to

meet specified performance from  $-40^\circ\text{C}$  to  $85^\circ\text{C}$  but is not tested or QA sampled at these temperatures. The LT6557I is guaranteed to meet specified performance from  $-40^\circ\text{C}$  to  $85^\circ\text{C}$ .


**Note 5:** Slew rate is 100% production tested on the R channel and measured on the rising edge of the output signal. The slew rate of the falling edge and of the G and B channels is guaranteed through design and characterization.

**Note 6:** Large-signal bandwidth is calculated from slew rate:  


$$\text{FPBW} = \text{SR}/(\pi \cdot V_{P-P})$$

# TYPICAL PERFORMANCE CHARACTERISTICS


**Gain Error Distribution**




**Gain Error Matching Distribution**




**Voltage Gain vs Temperature**




**Supply Current per Amplifier vs Supply Voltage**




**Supply Current per Amplifier vs Temperature**




**Supply Current per Amplifier vs EN Voltage**




**EN Pin Current vs EN Pin Voltage**



**Input Referred Offset Voltage vs Temperature**




**Input Bias Current vs Input Voltage**




# TYPICAL PERFORMANCE CHARACTERISTICS

**Output Voltage vs Input Voltage**




6557 G10

**Output Voltage Swing vs Load Current (Output High)**




6557 G11

**Output Voltage Swing vs Load Current (Output Low)**




6557 G12

**Input Bias Voltage vs Resistance at BCV Pin**




6557 G13

**Input Bias Voltage vs Temperature**




6557 G14

**Bias Control Voltage vs Temperature**




6557 G15

**Frequency Response**




6557 G16

**Frequency Response of Three Amplifiers**



6557 G17


**Gain Flatness vs Frequency**



6557 G18


TYPICAL PERFORMANCE CHARACTERISTICS

Frequency Response with Capacitive Loads




6557 G25

Large-Signal Group Delay




6557 G26

Crosstalk Between Amplifiers vs Frequency




6557 G19

Output Impedance vs Frequency




6557 G20

Input Impedance vs Frequency




6557 G21

PSRR vs Frequency




6557 G22

Distortion vs Frequency




6557 G23

Distortion vs Frequency




6557 G24

Input Referred Noise Spectral Density




6557 G27


## TYPICAL PERFORMANCE CHARACTERISTICS




6557 G28



6557 G29



6557 G30



6557 G31

## PIN FUNCTIONS

**EN (Pin 1):** Enable Control Pin. The part is enabled when this pin is pulled low. An internal pull-up resistor of 40k will turn the part off if this pin is unconnected.

**GND (Pin 2):** Ground Reference for Enable Pin (Pin 1) and Bias Control Voltage Pin (Pin 16). This pin must be connected externally to ground.

**IN R (Pin 3):** Red Channel Input. This pin has a nominal impedance of 200k $\Omega$  with input bias circuit inactive, Pin 16 open.

**GND R (Pin 4):** Ground of Red Channel Amplifier. This pin is not internally connected to other ground pins and must be connected externally to ground.

**IN G (Pin 5):** Green Channel Input. This pin has a nominal impedance of 200k $\Omega$  with input bias circuit inactive, Pin 16 open.

**GND G (Pin 6):** Ground of Green Channel Amplifier. This pin is not internally connected to other ground pins and must be connected externally to ground.

**IN B (Pin 7):** Blue Channel Input. This pin has a nominal impedance of 200k $\Omega$  with input bias circuit inactive, Pin 16 open.

**GND B (Pin 8):** Ground of Blue Channel Amplifier. This pin is not internally connected to other ground pins and must be connected externally to ground.

## PIN FUNCTIONS

**V<sup>+</sup> B (Pin 9):** Positive Supply Voltage of Blue Channel Amplifier. This pin is not internally connected to other supply voltage pins and must be externally connected to the supply voltage bus with proper bypassing for best performance, see Power Supply Considerations.

**OUT B (Pin 10):** Blue Channel Output.

**V<sup>+</sup> G (Pin 11):** Positive Supply Voltage of Green Channel Amplifier. This pin is not internally connected to other supply voltage pins and must be externally connected to the supply voltage bus with proper bypassing for best performance, see Power Supply Considerations.

**OUT G (Pin 12):** Green Channel Output.

**V<sup>+</sup> R (Pin 13):** Positive Supply Voltage of Red Channel Amplifier. This pin is not internally connected to other supply voltage pins and must be externally connected to

the supply voltage bus with proper bypassing for best performance, see Power Supply Considerations.

**OUT R (Pin 14):** Red Channel Output.

**V<sup>+</sup> (Pin 15):** Positive Supply Voltage of Control Circuitry. This pin is not internally connected to other supply voltage pins and must be externally connected to supply voltage bus with proper bypassing for best performance, see Power Supply Considerations.

**BCV (Pin 16):** Bias Control Voltage. A resistor connected between Pin 16 and Pin 2 (GND) will generate a DC voltage bias at the inputs of the three amplifiers for AC coupling application, see Programmable Input Bias.

**Exposed Pad (Pin 17, DFN Package):** Ground. This pad must be soldered to PCB and is internally connected to GND (Pin 2).

## APPLICATIONS INFORMATION

### Power Supply Considerations

The LT6557 is optimized to provide full video signal swing output when operated from a standard 5V single supply. Due to the supply current involved in ultrahigh slew rate amplifiers like the LT6557, selection of the lowest workable supply voltage is recommended to minimize heat generation and simplify thermal management. Temperature rise at the internal devices ( $T_J$ ) must be kept below 150°C (SSOP package) or 125°C (DFN package), and can be estimated from the ambient temperature ( $T_A$ ) and power dissipation ( $P_D$ ) as follows:

$$T_J = T_A + P_D \cdot 40^\circ\text{C/W for DFN package}$$

or

$$T_J = T_A + P_D \cdot 110^\circ\text{C/W for SSOP package}$$

$$\text{where } P_D = (I_S + 0.5 \cdot I_O) \cdot V_{S(\text{TOTAL})}$$

The latter equation assumes (conservatively) that the output swing is small relative to the supply and RMS load current ( $I_O$ ) is bidirectional (as with AC coupling).

The grounds are separately pinned for each amplifier to minimize crosstalk.

Operation from split supplies can be accomplished by connecting the LT6557 ground pins to the negative rail. Since the amplifier gain is referenced to its ground pins, the actual signals are referenced to the negative rail, in this case, and DC coupled applications need to take this into consideration. With dual supplies, recommended voltages range from nominal  $\pm 2.5\text{V}$  to  $\pm 3.3\text{V}$ .

The ultrahigh frequency (UHF) operating range of the LT6557 requires that careful printed circuit layout practices be followed to obtain maximum performance. Trace lengths between power pins and bypass capacitors should be minimized ( $< 0.1$  inch) and one or more dedicated ground planes should be employed to minimize parasitic inductance. Poor layout or breadboarding methods can seriously impact amplifier stability, frequency response and crosstalk performance. A 2.2 $\mu\text{F}$  and a 10 $\mu\text{F}$  bypass capacitor is recommended for the LT6557 supply bus, plus a 10nF high frequency bypass capacitor at each individual power pin.



## APPLICATIONS INFORMATION

### Programmable Input Bias

The LT6557 contains circuitry that provides a user-programmed bias voltage to the inputs of all three amplifier sections. The internal biasing feature is designed to minimize external component count in AC-coupled applications, but may be defeated if external biasing is desired. Figure 1 shows the simplified equivalent circuit feeding the noninverting input of each amplifier. A programming resistor from Pin 16 to GND (Pin 2) establishes the nominal




Figure 1. Simplified Programmable Input Bias Circuit Diagram






Figure 2. Simplified Shutdown Circuit Diagram



(3a) Open Drain or Open Collector



(3b) CMOS Gate with Shared Supply

Figure 3. Suitable Shutdown Pin Drive Circuits

no-signal amplifier input bias condition according to the following relationship:

$$V_{\text{BIAS(IN)}} = \frac{V_{\text{PIN16}} \cdot 9.1\text{k}}{R_{\text{SET}}}$$


where  $V_{\text{PIN16}} = 0.048\text{V}$  typical.

For single 5V supply operation, a 400Ω programming resistor is generally optimal. In applications that demand maximum amplifier linearity, or if external biasing is preferred (in DC-coupled applications, for example), the internal biasing circuitry may be disabled by leaving Pin 16 open. With Pin 16 open, input loading is approximately 200kΩ.

### Shutdown Control


The LT6557 may be placed into a shutdown mode, where all three amplifier sections are deactivated and power supply draw is reduced to approximately 10μA. When the EN pin is left open, an internal 40k pull-up resistor brings the pin to V+ and the part enters the shutdown mode. Pulling the pin more than approximately 1.5V below V+ will enable the LT6557 (see Figure 2 for equivalent circuit). The pull-down current required to activate the part is typically 125μA. In most applications, the EN pin is simply connected to ground (for continuous operation) or driven directly by a CMOS-level logic gate (see Figure 3 for examples). Response time is typically 50ns for enabling, and 1μs for shutdown. In shutdown mode, the feedback resistors remain connected between the output pins and the individual ground (or V- connected) pins.

# SIMPLIFIED SCHEMATIC



# PACKAGE DESCRIPTION


**GN Package**  
**16-Lead Plastic SSOP (Narrow .150 Inch)**  
 (Reference LTC DWG # 05-08-1641)




NOTE:  
 1. CONTROLLING DIMENSION: INCHES  
 2. DIMENSIONS ARE IN  $\frac{\text{INCHES}}{\text{(MILLIMETERS)}}$   
 3. DRAWING NOT TO SCALE  
 \*DIMENSION DOES NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.006" (0.152mm) PER SIDE  
 \*\*DIMENSION DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD FLASH SHALL NOT EXCEED 0.010" (0.254mm) PER SIDE

# PACKAGE DESCRIPTION

**DHC Package**  
**16-Lead Plastic DFN (5mm × 3mm)**  
 (Reference LTC DWG # 05-08-1706)




**RECOMMENDED SOLDER PAD PITCH AND DIMENSIONS**



- NOTE:
1. DRAWING PROPOSED TO BE MADE VARIATION OF VERSION (WJED-1) IN JEDEC PACKAGE OUTLINE MO-229
  2. DRAWING NOT TO SCALE
  3. ALL DIMENSIONS ARE IN MILLIMETERS
  4. DIMENSIONS OF EXPOSED PAD ON BOTTOM OF PACKAGE DO NOT INCLUDE MOLD FLASH. MOLD FLASH, IF PRESENT, SHALL NOT EXCEED 0.15mm ON ANY SIDE
  5. EXPOSED PAD SHALL BE SOLDER PLATED
  6. SHADED AREA IS ONLY A REFERENCE FOR PIN 1 LOCATION ON THE TOP AND BOTTOM OF PACKAGE

## TYPICAL APPLICATION

### Split Supply Operation with DC Bias Servo



## RELATED PARTS

| PART NUMBER   | DESCRIPTION                                       | COMMENTS  |
|---------------|---|---|
| LT1399        | 300MHz Triple Current Feedback Amplifier          | 0.1dB Gain Flatness to 150MHz, Shutdown                         |
| LT1675        | 250MHz Triple RGB Multiplexer                     | 100MHz Pixel Switching, 1100V/μs Slew Rate, 16-Lead SSOP        |
| LT6550/LT6551 | 3.3V Triple and Quad Video Buffers                | 110MHz Gain of 2 Buffers in MS Package                          |
| LT6553        | 650MHz Gain of 2 Triple Video Amplifier           | Optimized for Driving 75Ω Cables                                |
| LT6554        | 650MHz Gain of 1 Triple Video Amplifier           | Performance Similar to the LT6553 with $A_V = 1$ , 16-Lead SSOP |
| LT6555        | 650MHz Gain of 2 Triple Video Multiplexer         | Optimized for Driving 75Ω Cables                                |
| LT6556        | 750MHz Gain of 1 Triple Video Multiplexer         | High Slew Rate 2100V/μs   |
| LT6558        | 550MHz, 2200V/μs Gain of 1 Triple Video Amplifier | Single Supply with Input Bias Control                           |