

Selection Guide

RCM2000/3000 RabbitCore™

Shared Features of the RCM2000/3000 RabbitCore Series

Feature	RCM2XXX	RCM3XXX
EMI Reduction	Spectrum spreader for reduced EMI (<i>radiated emissions</i>)	
Serial Rate	Max. asynchronous burst rate = CLK/32	Max. asynchronous burst rate = CLK/8
Backup Battery	Connection for user-supplied battery (<i>to support RTC and SRAM</i>)	
Slave Interface	Permits use as master or intelligent peripheral with Rabbit-based or other master controller	
Real-Time Clock	Yes, battery backable	
Timers	Five 8-bit timers (<i>four cascadable from the first</i>) and one 10-bit timer with 2 match registers	Ten 8-bit timers (<i>six cascadable from the first</i>) and one 10-bit timer with 2 match registers
Watchdog	Yes	
Humidity	5–95% (<i>non-condensing</i>)	
Pulse-Width Modulation	N/A	8-bit free running counter and four 10-bit pulse-width registers
Input Capture	N/A	2-channel input capture can be used to time input signals from various port pins.
Quadrature Decoder	N/A	2-channel quadrature decoder accepts inputs from external incremental encoder modules.

continued next page ►►

Distinguishing Features of the RCM2000 RabbitCore Series

Feature	RCM2000	RCM2010	RCM2020	RCM2100	RCM2110	RCM2120	RCM2130	RCM2200	RCM2210	RCM2250	RCM2260	RCM2300
CPU Speed	25.8 MHz		18.4 MHz	22.1 MHz								
Ethernet	None			10Base-T RJ-45, 2 LEDs		None		10Base-T RJ-45, 2 LEDs	10Base-T raw signals	10Base-T RJ-45, 2 LEDs	10Base-T raw signals	None
Flash Memory	256K			512K	256K	512K	256K			512K		256K
SRAM	512K	128K		512K	128K	512K	128K			512K		128K
Extended Memory	None											
Analog Inputs	None											
General Purpose I/O*	40 parallel I/O • 26 configurable I/O • 8 fixed inputs• 6 fixed outputs			34 parallel I/O • 20 configurable I/O • 8 fixed inputs • 6 fixed outputs		40 parallel I/O • 26 configurable I/O • 8 fixed inputs• 6 fixed outputs		26 parallel I/O • 16 configurable I/O • 7 fixed inputs • 3 fixed outputs			29 parallel I/O • 17 config. I/O • 8 fixed inputs • 4 fixed outputs	
Add'l Inputs	2 Startup Mode, Reset											
Add'l Outputs	Watchdog, Reset						Status, Reset					
External I/O	13 address, 8 data, I/O Read-Write, Buffer Enable			13 buffered address lines, 8 buffered data lines, I/O Read-Write, Buffer Enable			4 address, 8 data, I/O Read-Write					
Serial Ports	Four 5 V CMOS-compatible • 4 configurable as asynchronous • 2 configurable as clocked serial (<i>SP1</i>)						Four 5 V CMOS-compatible • 4 configurable as asynchronous • 2 configurable as clocked serial (<i>SP1</i>)**					
Power	4.75–5.25 V DC • 130 mA		4.75–5.25 V DC • 98 mA		4.75–5.25 V DC • 140 mA			4.75–5.25 V DC • 134 mA			4.75–5.25 V DC • 108 mA	
Operating Temp.	–40°C to +85°C			–40°C to +70°C		–40°C to +80°C		–40°C to +70°C			–40°C to +85°C	
Board Size	2.3" x 1.9" x 0.5" (58 x 48 x 13 mm)			3.5" x 2.0" x 0.86" (89 x 51 x 22 mm)		3.5" x 2.0" x 0.5" (89 x 51 x 13 mm)		2.3" x 1.6" x 0.86" (59 x 41 x 22 mm)			1.60" x 1.15" x 0.47" (41 x 29 x 12 mm)	
Connectors	2 x 20, 2 mm IDC headers						2 x 13, 2 mm IDC headers					
Part Number	101-0404	101-0405	101-0383	101-0434	101-0435	101-0436	101-0446	101-0454	101-0488	101-0494	101-0955	101-0453
Development Kit Part Number	U.S.101-0398 Int'l 101-0399			U.S. 101-0451 Int'l 101-0452			U.S. 101-0475 Int'l 101-0478			U.S. 101-0480 Int'l 101-0481		

* Grouped in 8-bit ports and shared with serial ports

**1 clocked line available only on programming header

Distinguishing Features of the RCM3000 RabbitCore Series

Feature	RCM3000	RCM3010	RCM3100	RCM3110	RCM3200	RCM3210	RCM3220	RCM3300	RCM3310	RCM3360	RCM3370	
CPU Speed	29.4 MHz				44.2 MHz	29.4	44.2 MHz					
Ethernet	10Base-T, RJ-45, 2 LEDs		None		10/100Base-T, RJ-45, 3 LEDs		None	10/100Base-T, RJ-45, 3 LEDs				
Flash Memory	512K (2 x 256K)	256K	512K (2 x 256K)	256K	512K	256K	512K					
SRAM	512K	128K	512K	128K	512K program + 256K data	128K	512K program + 256K data	512K program + 512K data				
Extended Memory	None							8 MB Serial Flash	4MB Serial Flash	16 MB NAND Flash (<i>chip</i>)	None	
	Removable Flash Memory											
Analog Inputs	None											
General Purpose I/O*	52 digital I/O • 44 configurable I/O • 4 fixed inputs • 4 fixed outputs		54 digital I/O • 46 configurable I/O • 4 fixed inputs • 4 fixed outputs		52 digital I/O • 44 configurable I/O • 4 fixed inputs • 4 fixed outputs			49 parallel digital I/O • 43 configurable I/O • 3 fixed inputs • 3 fixed outputs		52 parallel digital I/O • 44 configurable I/O • 4 fixed inputs • 4 fixed outputs		
Add't Inputs	2 Startup Mode, Reset											
Add't Outputs	Status, Reset											
External I/O	6 address (<i>shared with I/O</i>), 8 data, plus I/O Rd, I/O Wr							5 address (<i>shared with I/O</i>), 8 data, plus I/O Rd, I/O Wr				
Serial Ports	Six 3.3 V CMOS-compatible: • 6 configurable as asynchronous (<i>with IrDA</i>) • 4 configurable as clocked serial (<i>SPI</i>) • 2 configurable as SDLC/HDLC							Five 3.3 V CMOS-compatible: • 5 configurable as asynchronous (<i>with IrDA</i>), • 3 configurable as clocked serial (<i>SPI</i>) • 2 configurable as SDLC/HDLC • 1 asynchronous serial port (<i>programming</i>)		Six 3.3 V CMOS-compatible: • 6 configurable as asynchronous (<i>with IrDA</i>) • 4 configurable as clocked serial (<i>SPI</i>) • 2 configurable as SDLC/HDLC • 1 asynchronous serial port dedicated (<i>programming</i>)		
Power	3.15–3.45 V DC • 150 mA		3.15–3.45 V DC • 75 mA		3.15–3.45 V DC • 255 mA			3.15–3.45 V DC • 350 mA @ 3.3 V				
Operating Temp.	–40°C to +70°C		–40°C to +85°C		–40°C to +70°C							
Board Size	2.73" × 1.85" × 0.86" (69 x 47 x 22 mm)		1.85" × 1.65" × 0.55" (47 x 42 x 14 mm)		2.73" × 1.85" × 0.86" (69 x 47 x 22 mm)							
Connectors	Two 2 x 17, 2 mm IDC headers											
Part Number	101-0507	101-0508	101-0517	101-0518	101-0520	101-0521	101-0522	101-0691	101-0698	101-0949	101-0950	
Development Kit Part Number	U.S. 101-0523 Int'l 101-0524		U.S. 101-0533 Int'l 101-0534		U.S. 101-0552 Int'l 101-0553			U.S. 101-0704 Int'l 101-0705		U.S. 101-0953 Int'l 101-0954		

* Grouped in 8-bit ports and shared with serial ports

continued next page ►►

Feature	RCM3400	RCM3410	RCM3600	RCM3610	RCM3700	RCM3710	RCM3720
CPU Speed	29.4 MHz		22.1 MHz				
Ethernet	Reference Design for 10/100Base-T Mac ID installed		None		10Base-T, RJ-45		
Flash Memory	512K	256K	512K	256K	512K	256K	512K
SRAM	512K	256K	512K	128K	512K	128K	256K
Extended Memory	None				1MB Serial Flash		
Analog Inputs	8 channels single-ended (11-bit) or 4 channels differ. (12-bit), Prog. gain 1, 2, 4, 5, 8, 10, 16, and 20 V/V.		None				
General Purpose I/O*	47 digital I/O • 41 configurable I/O • 3 fixed inputs • 3 fixed outputs		33 parallel digital I/O lines • 31 configurable I/O • 2 fixed outputs				
Add't Inputs	2 Startup Mode, Reset In, CONVERT		Reset			None	
Add't Outputs	Status, Reset Out, BVREF		None				
External I/O	6 address (shared with I/O), 8 data, plus I/O Rd, I/O Wr		5 address (shared with I/O), 8 data, plus I/O Rd, I/O Wr				
Serial Ports	Five 3.3 V CMOS-compatible: • 4 configurable as asynchronous (with IrDA), • 3 as clocked serial (SPI), 2 as SDLC/HDLC (with IrDA) • 1 asynchronous serial port (programming) • Support for MIR/SIR IrDA transceiver		Four 3.3 V CMOS-compatible: • 4 configurable as asynchronous (with IrDA) • 3 as clocked serial (SPI) and 1 as SDLC/HDLC (with IrDA), or 1 SPI and 2 SDLC/HDLC • 1 asynchronous serial port (programming)				
Power	3.0–3.45 V DC • 97 mA @ 29.4 MHz/2.8–3.45 V DC • 57 mA @ 14.7 MHz		4.75-12.6 VDC • 60 mA @ 22.1 MHz; 38 mA @ 11.06 MHz		4.75-5.25 VDC • 100 mA @ 22.1 MHz 78 mA @ 11.06 MHz		
Operating Temp.	–40°C to +85°C				–40°C to +70°C		
Board Size	1.38" × 1.16" × 0.31" (35 x 29 x 7.4 mm)		2.10" × 1.20" × 0.62" (53 x 30 x 16 mm)		2.95" × 1.20" × 0.88" (75 x 30 x 22 mm)		
Connectors	Two 2 x 17, 1.27 mm IDC Headers		Single 2 x 20, 0.1" IDC header				
Part Number	101-0561	101-0562	101-0672	101-0673	101-0674	101-0675	101-0961
Development Kit Part Number	U.S. 101-0587 Int'l 101-0588		U.S. 101-0678 Int'l 101-0679		U.S. 101-0680 Int'l 101-0681		U.S. 101-0963 Int'l 101-0964

* Grouped in 8-bit ports and shared with serial ports