



# ZGP323H OTP MCU Family

## Product Brief

PB015009-0208

### Overview

Zilog’s ZGP323H is an OTP-based member of the family of general-purpose microcontrollers. With 237 B of general-purpose RAM and up to 32 KB of OTP, Zilog’s CMOS microcontrollers offer fast-executing use of memory, sophisticated interrupts, input/output bit manipulation, automated pulse generation/reception, and internal key-scan pull-up transistors. ZGP323H is compatible with Zilog’s ZGR163L/ZGR323L families.

### Product Block Diagram

Watchdog Timer		Up to 32 KB OTP	Power-On Reset
T8 Timer Capture & Transmit		Z8® Core	2 Comparators
T16 Timer Capture & Transmit			Low Battery Voltage Detection
237 Bytes RAM		High Battery Voltage Detection	
Port 0 8 I/O	Port 1 8 I/O	Port 2 8 I/O	Port 3 8 I/O

### Features


Key features of ZGP323H MCU include:

- 2.0 V to 5.5 V operation
- Low power consumption—11 mW (typical @3V)
- Three standby modes:
  - STOP—2 µA (typical)

- HALT—0.8 mA (typical)
- Low voltage reset
- Special architecture to automate both generation and reception of complex pulses or signals:
  - One programmable 8-bit counter/timer with two capture registers and two load registers
  - One programmable 16-bit counter/timer with one capture register and two reload registers
  - Programmable input glitch filter for pulse reception
- Six priority interrupts:
  - Three external
  - Two assigned to counter/timers
  - One low-voltage detection interrupt
- Low-voltage and high-voltage detection flags
- Programmable Watchdog Timer (WDT)
- Power-On Reset (POR) circuits
- Two independent comparators with programmable interrupt polarity
- Programmable EPROM options:
  - Port 0: 0–3 pull-up transistors
  - Port 0: 4–7 pull-up transistors
  - Port 1: 0–3 pull-up transistors
  - Port 1: 4–7 pull-up transistors
  - Port 2: 0–7 pull-up transistors
  - EPROM Protection
  - WDT enabled at POR
- Standard (0 °C to +70 °C), Extended (-40 °C to +105 °C), and Automotive (-40 °C to +125 °C) temperature ranges

## Architecture

Figure 1 displays ZGP323H architecture.



Note: Refer to the specific package for available pins.

**Figure 1. Architectural Diagram**

## Ordering Information

Order the tools from Zilog®, providing the part numbers as given below:

<b>32 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH4832G	48-pin SSOP 32K OTP
ZGP323HSP4032G	40-pin PDIP 32K OTP
ZGP323HSK2832E	28-pin CDIP* 32K OTP
ZGP323HSK4032E	40-pin CDIP* 32K OTP
ZGP323HSH2832G	28-pin SSOP 32K OTP
ZGP323HSP2832G	28-pin PDIP 32K OTP
ZGP323HSS2832G	28-pin SOIC 32K OTP
ZGP323HSH2032G	20-pin SSOP 32K OTP
ZGP323HSK2032E	20-pin CDIP* 32K OTP
ZGP323HSP2032G	20-pin PDIP 32K OTP
ZGP323HSS2032G	20-pin SOIC 32K OTP
<b>32 KB Extended Temperature: -40 °C to +105 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HEH4832G	48-pin SSOP 32K OTP
ZGP323HEP4032G	40-pin PDIP 32K OTP
ZGP323HEH2832G	28-pin SSOP 32K OTP
ZGP323HEP2832G	28-pin PDIP 32K OTP
ZGP323HES2832G	28-pin SOIC 32K OTP
ZGP323HEH2032G	20-pin SSOP 32K OTP
ZGP323HEP2032G	20-pin PDIP 32K OTP
ZGP323HES2032G	20-pin SOIC 32K OTP
<b>32 KB Automotive Temperature: -40 °C to +125 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HAH4832G	48-pin SSOP 32K OTP
ZGP323HAP4032G	40-pin PDIP 32K OTP
ZGP323HAH2832G	28-pin SSOP 32K OTP
ZGP323HAP2832G	28-pin PDIP 32K OTP
ZGP323HAS2832G	28-pin SOIC 32K OTP
ZGP323HAH2032G	20-pin SSOP 32K OTP
ZGP323HAP2032G	20-pin PDIP 32K OTP

ZGP323HAS2032G	20-pin SOIC 32K OTP
<b>16 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH4816G	48-pin SSOP 16K OTP
ZGP323HSP4016G	40-pin PDIP 16K OTP
ZGP323HSH2816G	28-pin SSOP 16K OTP
ZGP323HSP2816G	28-pin PDIP 16K OTP
ZGP323HSS2816G	28-pin SOIC 16K OTP
ZGP323HSH2016G	20-pin SSOP 16K OTP
ZGP323HSP2016G	20-pin PDIP 16K OTP
ZGP323HSS2016G	20-pin SOIC 16K OTP
<b>16 KB Extended Temperature: -40 °C to +105 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HEH4816G	48-pin SSOP 16K OTP
ZGP323HEP4016G	40-pin PDIP 16K OTP
ZGP323HEH2816G	28-pin SSOP 16K OTP
ZGP323HEP2816G	28-pin PDIP 16K OTP
ZGP323HES2816G	28-pin SOIC 16K OTP
ZGP323HEH2016G	20-pin SOIC 16K OTP
ZGP323HES2016G	20-pin SSOP 16K OTP
ZGP323HEP2016G	20-pin PDIP 16K OTP
<b>16 KB Automotive Temperature: -40 °C to +125 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HAH4816G	48-pin SSOP 16K OTP
ZGP323HAP4016G	40-pin PDIP 16K OTP
ZGP323HAH2816G	28-pin SSOP 16K OTP
ZGP323HAP2816G	28-pin PDIP 16K OTP
ZGP323HAS2816G	28-pin SOIC 16K OTP
ZGP323HAH2016G	20-pin SSOP 16K OTP
ZGP323HAP2016G	20-pin PDIP 16K OTP
ZGP323HAS2016G	20-pin SOIC 16K OTP
<b>8 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH4808G	48-pin SSOP 8K OTP
ZGP323HSP4008G	40-pin PDIP 8K OTP

<b>8 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH2808G	28-pin SSOP 8K OTP
ZGP323HSP2808G	28-pin PDIP 8K OTP
ZGP323HSS2808G	28-pin SOIC 8K OTP
ZGP323HSH2008G	20-pin SSOP 8K OTP
ZGP323HSP2008G	20-pin PDIP 8K OTP
ZGP323HSS2008G	20-pin SOIC 8K OTP
<b>8 KB Extended Temperature: -40 °C to +105 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HEH4808G	48-pin SSOP 8K OTP
ZGP323HEP4008G	40-pin PDIP 8K OTP
ZGP323HEH2808G	28-pin SSOP 8K OTP
ZGP323HEP2808G	28-pin PDIP 8K OTP
ZGP323HES2808G	28-pin SOIC 8K OTP
ZGP323HEH2008G	20-pin SSOP 8K OTP
ZGP323HEP2008G	20-pin PDIP 8K OTP
ZGP323HES2008G	20-pin SOIC 8K OTP
<b>8 KB Automotive Temperature: -40 °C to +125 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HAH4808G	48-pin SSOP 8K OTP
ZGP323HAP4008G	40-pin PDIP 8K OTP
ZGP323HAH2808G	28-pin SSOP 8K OTP
ZGP323HAP2808G	28-pin PDIP 8K OTP
ZGP323HAS2808G	28-pin SOIC 8K OTP
ZGP323HAH2008G	20-pin SSOP 8K OTP
ZGP323HAP2008G	20-pin PDIP 8K OTP
ZGP323HAS2008G	20-pin SOIC 8K OTP
<b>4 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH4804G	48-pin SSOP 4K OTP
ZGP323HSP4004G	40-pin PDIP 4K OTP
ZGP323HSH2804G	28-pin SSOP 4K OTP
ZGP323HSP2804G	28-pin PDIP 4K OTP
ZGP323HSS2804G	28-pin SOIC 4K OTP

<b>4 KB Standard Temperature: 0 °C to +70 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HSH2004G	20-pin SSOP 4K OTP
ZGP323HSP2004G	20-pin PDIP 4K OTP
ZGP323HSS2004G	20-pin SOIC 4K OTP
<b>4 KB Extended Temperature: –40 °C to +105 °C</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323HEH4804G	48-pin SSOP 4K OTP
ZGP323HEP4004G	40-pin PDIP 4K OTP
ZGP323HEH2804G	28-pin SSOP 4K OTP
ZGP323HEP2804G	28-pin PDIP 4K OTP
ZGP323HES2804G	28-pin SOIC 4K OTP
ZGP323HEH2004G	20-pin SSOP 4K OTP
ZGP323HEP2004G	20-pin PDIP 4K OTP
ZGP323HES2004G	20-pin SOIC 4K OTP
Note: 4 KB Automotive Temperature: –40 °C to +125 °C	
<b>Part Number</b>	<b>Description</b>
ZGP323HAH4804G	48-pin SSOP 4K OTP
ZGP323HAP4004G	40-pin PDIP 4K OTP
ZGP323HAH2804G	28-pin SSOP 4K OTP
ZGP323HAP2804G	28-pin PDIP 4K OTP
ZGP323HAS2804G	28-pin SOIC 4K OTP
ZGP323HAH2004G	20-pin SSOP 4K OTP
ZGP323HAP2004G	20-pin PDIP 4K OTP
ZGP323HAS2004G	20-pin SOIC 4K OTP
<b>Development Tools</b>	
<b>Part Number</b>	<b>Description</b>
ZGP323ICE02ZEMG	ZGP323 In-Circuit Emulator
ZLP323ICE01ZAC*	40/48-Pins Accessory Kit
Note: *This kit has been replaced by an improved version, ZCRMZNICE02ZACG.	
ZCRMZNICE02ZACG	40/48-Pin Accessory Kit
ZGP32300200ZPR (USB)	Programming system



- ▶ **Notes:** \* Windowed Cerdip. These units are intended to be used for engineering code development only. Zilog® does not recommend/guarantee this package for production use.

Zilog Developer Studio II (ZDS II) Integrated Development Environment, ZDS II—Crimzon+GP, is also available.



**Warning:** DO NOT USE IN LIFE SUPPORT

### **LIFE SUPPORT POLICY**

ZILOG'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF ZILOG CORPORATION.

### **As used herein**

Life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness.

### **Document Disclaimer**

©2008 by Zilog, Inc. All rights reserved. Information in this publication concerning the devices, applications, or technology described is intended to suggest possible uses and may be superseded. ZILOG, INC. DOES NOT ASSUME LIABILITY FOR OR PROVIDE A REPRESENTATION OF ACCURACY OF THE INFORMATION, DEVICES, OR TECHNOLOGY DESCRIBED IN THIS DOCUMENT. ZILOG ALSO DOES NOT ASSUME LIABILITY FOR INTELLECTUAL PROPERTY INFRINGEMENT RELATED IN ANY MANNER TO USE OF INFORMATION, DEVICES, OR TECHNOLOGY DESCRIBED HEREIN OR OTHERWISE. The information contained within this document has been verified according to the general principles of electrical and mechanical engineering.

Z8 GP and Crimzon are the trademarks or registered trademarks of Zilog, Inc. All other product or service names are the property of their respective owners.