

Product Brief

**Intel® Pentium® 4 Processors
with Hyper-Threading Technology**

Embedded Computing



Intel® Pentium® 4 Processors with Hyper-Threading Technology for Embedded Computing

Product Overview

Intel® Pentium® 4 processors with Hyper-Threading Technology¹ (HT Technology) provide increased system responsiveness in multi-tasking environments and are ideal for next-generation multi-threaded applications. Platforms based on Intel Pentium 4 processors with HT Technology can help reduce the total cost of ownership for a new generation of advanced, highly differentiated embedded products by providing performance headroom, robust I/O, scalability, and quality.

Manufactured on 65-nanometer (nm) process technology with a reduced thermal design power (TDP) of 65W, the 3.4 GHz Intel Pentium 4 processor 651^A with HT Technology offers 2 MB of L2 cache. In addition, based on 90-nm process technology, the Intel Pentium 4 processors 551^A and 531^A with HT Technology simplify the transition to 64-bit computing for embedded customers developing with Intel® 64 architecture¹ (Intel® 64).

With an 800 MHz front-side bus and a choice of 1 MB and 2 MB of Level 2 Advanced Transfer Cache, Intel Pentium 4 processors with HT Technology enable highly differentiated and scalable embedded solutions within the growing communications, interactive client, and industrial automation market segments.

Intel Pentium 4 processors 651, 551 and 531, available in LGA-775 package with integrated heat spreader, are all validated with the Intel® 915GV and Intel® 945G Express chipsets. In addition, processor 651 extends the selection of Intel Pentium 4 processor-based platforms to include the Intel® Q965 Express chipset, while processors 551 and 531 provide support for the Intel® 865G chipset.

The 3.0 GHz Intel Pentium 4 processor with HT Technology, available in µPGA-478 package, is validated with Intel 865G and Intel® 875P chipsets.



Rapid platform development is supported by the latest operating systems and Intel® architecture development tools. In addition, Intel offers validated design schematics, based on the Intel Pentium 4 processor with HT Technology, to rapidly meet unique product application requirements. Board solutions are also available from third-party providers.

Product Highlights

- 800 MHz front-side bus delivering 6.4 GB of data per second
- HT Technology provides increased system responsiveness in multi-tasking environments and supports next-generation multi-threaded applications
- Enhancements to the Intel NetBurst® microarchitecture provide software and architectural scalability
- 64-bit computing with Intel 64 enables faster access to DDR2 memory with Intel Pentium 4 processors 651, 551 and 531 with HT Technology
- Support for uni-processor designs
- Fully compatible with existing Intel architecture-based software

Product Highlights (continued)

- Enhanced floating-point and multi-media unit expands floating-point registers to a full 128-bit and adds an additional register for data movement
 - 144 Streaming SIMD Extensions 2 (SSE2) instructions
 - 13 Streaming SIMD Extensions 3 (SSE3) instructions
- Execute Disable Bit can prevent certain classes of malicious "buffer overflow" attacks when combined with a supporting operating system
- μPGA-478 package plugs into a standard PGA-478 socket for full scalability with other Intel® processors including Intel Pentium 4, Intel® Celeron® D, and Intel® Celeron® processors
- Embedded lifecycle support
- Along with a strong ecosystem of hardware and software vendors, including members of the Intel® Communications Alliance (intel.com/go/ica), Intel helps cost-effectively meet development challenges and speed time-to-market

Intel® Pentium® 4 Processors with Hyper-Threading Technology for Embedded Computing

Product Number	Core Speed	Front-Side Bus Speed	L2 Cache	Thermal Design Power	Voltage ²	Tcase ³	Package	Process Technology
HH80552PG0962M	3.4 GHz	800 MHz	2 MB	65W	1.2000-1.3375V	5-69.2° C	LGA-775	65nm
HH80547PG0961MM	3.4 GHz	800 MHz	1 MB	84W	1.2000-1.4250V	5-67.7° C	LGA-775	90nm
HH80547PG0801MM	3.0 GHz	800 MHz	1 MB	84W	1.2000-1.4250V	5-67.7° C	LGA-775	90nm
NE80546PG0801M	3.0 GHz	800 MHz	1 MB	89W	1.25-1.4 V	5-69.1° C	FC-μPGA4	90nm

¹ Intel® 64 requires a system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel 64. Processor will not operate (including 32-bit operation) without an Intel 64 -enabled BIOS. Performance will vary depending on your hardware and software configurations. See <http://developer.intel.com/technology/intel64/index.htm> for more information including details on which processors support Intel 64 or consult with your system vendor for more information.

² Variable VID voltage. The Intel Pentium 4 processor with HT Technology ships with different voltage settings. For more detailed information, please refer to our Web site at <http://developer.intel.com/design/intarch/pentium4/pentium4.htm>

³ Tcase specification is based on Intel thermal profile. See processor data sheet for details.

⁴ Hyper-Threading Technology requires a computer system with an Intel® Pentium® 4 processor supporting Hyper-Threading Technology and an HT Technology-enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See http://www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology.

⁵ Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details.

Intel Access

- Embedded Intel® Architecture Home Page: intel.com/design/intarch
 Developer's Site: developer.intel.com
 Intel in Communications: intel.com/communications
 General Information Hotline: (800) 628-8686 or (916) 356-3104 5 a.m. to 5 p.m. PST
 Intel® Literature Center: (800) 548-4725 7 a.m. to 7 p.m. CST (U.S. and Canada)
 International locations please contact your local sales office.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO SALE AND/OR USE OF INTEL PRODUCTS, INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT. INTEL MAY MAKE CHANGES TO SPECIFICATIONS, PRODUCT DESCRIPTIONS, AND PLANS AT ANY TIME, WITHOUT NOTICE.

Intel Corporation may have patents or pending patent applications, trademarks, copyrights, or other intellectual property rights that relate to the presented subject matter. The furnishing of documents and other materials and information does not provide any license, express or implied, by estoppel or otherwise, to any such patents, trademarks, copyrights, or other intellectual property rights. Intel products are not intended for use in medical, life saving, life sustaining, critical control or safety systems, or in nuclear facility applications. Intel® Pentium 4 processors with Hyper-Threading Technology may contain design defects or errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available upon request.

Intel, the Intel logo, Intel. Leap ahead., Intel. Leap ahead. logo, Pentium, Celeron, and Intel NetBurst are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2006 Intel Corporation. All rights reserved.

Printed in USA

1206/KSC/OCG/XX/PDF

 Please Recycle

300921-006US

