



June 2008

# FSA2270T Low-Voltage, Dual-SPDT (0.4 $\Omega$ ) Analog Switch with Negative Swing Audio Capability

## **Features**

- 0.4Ω Typical On Resistance (R<sub>ON</sub>) for +3.0V Supply
- 0.25Ω Maximum R<sub>ON</sub> Flatness for +3.0V Supply
- -3db Bandwidth: > 50MHz
- Low-I<sub>CCT</sub> Current Over Expanded Control Input Range
- Packaged in 10-Lead UMLP
- Power-Off Protection on Common Ports
- Broad V<sub>CC</sub> Operating Range: 1.65 to 4.3V
- Noise Immunity Termination Resistors
- Low Electrostatic Discharge (ESD)
  - Human Body Model (JEDEC: JESD22-A114)
    - Power to GND 16kVI/O to GND 11kVAll other pins 8kV
  - Charged Device Model (JEDEC: JESD22-A101)

# **Applications**

- Cell Phone, PDA, Digital Camera, and Notebook
- LCD Monitor, TV, and Set-Top Box

## Description

The FSA2270T is a high-performance, dual Single-Pole Double-Throw (SPDT) analog switch with negative swing audio capability. The FSA2270T features ultra-low  $R_{\text{ON}}$  of  $0.4\Omega$  (typical) at 3.0V V $_{\text{CC}}$ . The FSA2270T operates over a wide V $_{\text{CC}}$  range of 1.65V to 4.3V, is fabricated with submicron CMOS technology to achieve fast switching speeds, and is designed for break-before-make operation. The select input is TTL-level compatible.

The FSA2270T features very low quiescent current even when the control voltage is lower than the  $V_{\rm CC}$  supply. This feature suits mobile handset applications by allowing direct interface with baseband processor general-purpose I/Os with minimal battery consumption.

The FSA2270T includes termination resistors that improve noise immunity during overshoot excursions, off-isolation coupling, or "pop-minimization."

### **IMPORTANT NOTE:**

For additional performance information, please contact <a href="mailto:analogswitch@fairchildsemi.com">analogswitch@fairchildsemi.com</a>.

# **Ordering Information**

Part Number	Top Mark	© Eco Status	Package Description
FSA2270TUMX	нк	Green	10-Lead, Quad Ultrathin Molded Leadless Package (UMLP), 1.4 x 1.8mm, 0.4mm pitch

For Fairchild's definition of "green" Eco Status, please visit: <a href="http://www.fairchildsemi.com/company/green/rohs\_green.html">http://www.fairchildsemi.com/company/green/rohs\_green.html</a>.

## **Analog Symbol**




Figure 1. FSA2270T





#### **TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks

ACEX® Build it Now™ CorePLUS™ CorePOWER™ CROSSVOLT™ CTL TM

Current Transfer Logic™ EcoSPARK<sup>®</sup>

EfficentMax™ EZSWITCH™ \*

Fairchild<sup>®</sup>

Fairchild Semiconductor® FACT Quiet Series™

FACT® FAST® FastvCore™ FlashWriter®\* FPS™ F-PFS™ FRFET®

Global Power Resources

Green FPS™ Green FPS™e-Series™

GTO™ IntelliMAX™ ISOPLANAR™ MegaBuck™

MICROCOUPLER™ MicroFET™ MicroPak™ MillerDrive™ MotionMax™ Motion-SPM™

OPTOLOGIC® OPTOPLANAR® PDP SPM™ Power-SPM™ PowerTrench®

Programmable Active Droop™ QFET®

QSTM Quiet Series™ RapidConfigure™

Saving our world, 1mW at a time™ SmartMax ™

SMART START™

SPM®

STEALTH™ SuperFET™ SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS™ SyncFET™ SYSTEM ®

The Power Franchise®



TinyBoost™ TinyBuck™ TinyLogic<sup>®</sup> TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ μSerDes™

UHC' Ultra FRFET™ UniFET™ **VCXTM** 

VisualMax™

\* EZSWITCH™ and FlashWriter® are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN, FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

#### As used herein

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### PRODUCT STATUS DEFINITIONS

#### Definition of Terms

Datasheet Identification	Product Status	Definition	
Advance Information	Formative / In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.	
Preliminary	First Production	This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.	
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.	
Obsolete Not In Production		This datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.	

Rev. 134