

# TLP706

## Intelligent power module signal isolation

### Industrial inverters

### Motor drive

The Toshiba TLP706 consists of a GaAlAs light-emitting diode and an integrated high-gain, high-speed photodetector. The TLP706 is suitable for isolating input control signals to intelligent power modules. This unit is a 6-pin SDIP. The TLP706 is 50% smaller than the 8-PIN DIP and meets the reinforced insulation class requirements of international safety standards. Therefore the mounting area can be reduced in equipment requiring safety standard certification.

The detector has a totem pole output stage to provide both source and sink driving. The detector IC has an internal shield that provides a guaranteed common-mode transient immunity of 10 kV/μs.

The TLP706 is buffer logic type. For inverter logic type, the TLP702 is in line-up.

- Buffer logic type (totem pole output)
- Pb Free
- Guaranteed performance over temperature : -40~100°C
- Power supply voltage : 4.5~20 V
- Input current: I<sub>FHL</sub> = 5 mA (Max.)
- Switching time ( t<sub>pLH</sub> / t<sub>pHL</sub> ) : 600 ns (Max.)
- Common-mode transient immunity : ±10 kV/μs (Min)
- Isolation voltage : 5000 V<sub>rms</sub> (Min)
- UL Recognized :UL1577, File No.E67349
- Option (D4)

TÜV Approved : DIN EN60747-5-2  
No.R50033433

Maximum Operating Insulation Voltage : 890V<sub>PK</sub>

Highest Permissible Over Voltage : 8000V<sub>PK</sub>

**(Note) : When a EN60747-5-2 approved type is needed,**


**Please designate "Option(D4)"**

- Construction Mechanical Rating

	7.62 mm pich standard type	10.16 mm pich TLPXXXF type
Creepage Distance	7.0 mm (Min)	8.0 mm (Min)
Clearance	7.0 mm (Min)	8.0 mm (Min)
Insulation Thickness	0.4 mm (Min)	0.4 mm (Min)


### Truth Table

Input	LED	Tr1	Tr2	Output
H	ON	ON	OFF	H
L	OFF	OFF	ON	L




Weight : 0.26 g (typ.)

### Pin Configuration (Top View)



### Schematic



0.1 μF bypass capacitor must be connected between pins 6 and 4. (Note 4)

## Absolute maximum ratings (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current (Ta ≤ 85°C)	I <sub>F</sub>	20	mA
	Forward Current Derating (Ta > 85°C)	ΔI <sub>F</sub> /ΔTa	-0.5	mA/°C
	Peak Transient Forward Current (Note 1)	I <sub>FPT</sub>	1	A
	Reverse Voltage	V <sub>R</sub>	5	V
	Junction Temperature	T <sub>J</sub>	125	°C
DETECTOR	Output Current 1 (Ta ≤ 25°C)	I <sub>O1</sub>	15/-15	mA
	Output Current 2 (Ta ≤ 100°C)	I <sub>O2</sub>	4.5/-4.5	mA
	Peak Output Current	I <sub>OP</sub>	20/-20	mA
	Output Voltage	V <sub>O</sub>	-0.5~20	V
	Supply Voltage	V <sub>CC</sub>	-0.5~20	V
	Junction Temperature	T <sub>J</sub>	125	°C
Operating Temperature Range		Topr	-40~100	°C
Storage Temperature Range		Tstg	-55~125	°C
Lead Solder Temperature (10 s)		Tsol	260	°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%, Ta = 25°C) (Note 2)		BVs	5000	V <sub>rms</sub>

## Recommended Operating Conditions

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Input Current, ON	I <sub>F</sub> (ON)	7	-	12	mA
Input Voltage, OFF	V <sub>F</sub> (OFF)	0	-	0.8	V
Supply Voltage (*) ( Note 3, Note 4 )	V <sub>CC</sub>	4.5	-	20	V

Recommended operating conditions are given as a design guideline to obtain expected performance of the device. Additionally, each item is an independent guideline respectively. In developing designs using this product, please confirm specified characteristics shown in this document.

(\*) This item denotes operating ranges, not meaning of recommended operating conditions.

Note1 : Pulse width PW ≤ 1 μs, 300 pps.

Note2 : Device Considered a two terminal device : pins 1,2 and 3 shorted together and pins 4,5 and 6 shorted together.

Note3 : The detector of this product requires a power supply voltage (V<sub>CC</sub>) of 4.5 V or higher for stable operation.

If the V<sub>CC</sub> is lower than this value, an output may be unstable. Be sure to use the product after checking the supply current, and the operation of a power-on/-off.

Note4 : A ceramic capacitor (0.1 μF) should be connected from pin 6 to pin 4 to stabilize the operation of the high gain linear amplifier. Failure to provide the bypassing may impair the switching property. The total lead length between capacitor and coupler should not exceed 1 cm.

## Electrical Characteristics

(Unless otherwise specified,  $T_a = -40 \sim 100^\circ\text{C}$ ,  $V_{CC} = 4.5 \sim 20\text{ V}$ .)

CHARACTERISTIC	SYMBOL	TEST CIRCUIT	CONDITION	MIN.	TYP. *	MAX.	UNIT	
Input forward voltage	$V_F$	—	$I_F = 5\text{ mA}$ , $T_a = 25^\circ\text{C}$	—	1.6	1.7	V	
Temperature coefficient of forward voltage	$\Delta V_F / \Delta T_a$	—	$I_F = 5\text{ mA}$	—	-2.0	—	mV/ $^\circ\text{C}$	
Input reverse current	$I_R$	—	$V_R = 5\text{ V}$ , $T_a = 25^\circ\text{C}$	—	—	10	$\mu\text{A}$	
Input capacitance	$C_T$	—	$V = 0\text{ V}$ , $f = 1\text{ MHz}$ , $T_a = 25^\circ\text{C}$	—	30	—	pF	
Logic LOW output voltage	$V_{OL}$	1	$I_{OL} = 3.5\text{ mA}$ , $V_F = 0.8\text{ V}$	—	0.1	0.35	V	
Logic HIGH output voltage	$V_{OH}$	2	$I_{OH} = -3.5\text{ mA}$ , $I_F = 5\text{ mA}$	$V_{CC} = 5\text{ V}$	2.4	3.1	—	V
				$V_{CC} = 20\text{ V}$	17.4	18.1	—	
Logic LOW supply current	$I_{CCL}$	3	$V_F = 0\text{ V}$	$V_{CC} = 20\text{ V}$ $T_a = -40 \sim 100^\circ\text{C}$	—	4.0	6.0	mA
				$V_{CC} = 5\text{ V}$ $T_a = 25^\circ\text{C}$	—	3.6	4.5	
Logic HIGH supply current	$I_{CCH}$	4	$I_F = 5\text{ mA}$	$V_{CC} = 20\text{ V}$ $T_a = -40 \sim 100^\circ\text{C}$	—	3.1	6.0	mA
				$V_{CC} = 5\text{ V}$ $T_a = 25^\circ\text{C}$	—	2.8	4.5	
Logic LOW short circuit output current	$I_{OSL}$	5	$V_F = 0.8\text{ V}$ $V_{CC} = V_O = 20\text{ V}$	7	37	—	mA	
Logic HIGH short circuit output current	$I_{OSH}$	6	$I_F = 5\text{ mA}$ , $V_O = \text{GND}$ $V_{CC} = 20\text{ V}$	-7	-40	—	mA	
Input current logic HIGH output	$I_{FLH}$	—	$I_O = -3.5\text{ mA}$ , $V_O > 2.4\text{ V}$ $V_{CC} = 5\text{ V}$	—	0.5	5	mA	
Input voltage logic LOW output	$V_{FHL}$	—	$I_O = 3.5\text{ mA}$ , $V_O < 0.4\text{ V}$	0.8	—	—	V	
Input current hysteresis	$I_{HYS}$	—	$V_{CC} = 5\text{ V}$	—	0.05	—	mA	

\*All typical values are at  $T_a = 25^\circ\text{C}$ .

## Isolation Characteristics ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Capacitance input to output	$C_S$	$V = 0\text{ V}$ , $f = 1\text{ MHz}$ (Note 2)	—	1.0	—	pF
Isolation resistance	$R_S$	R.H. $\leq 60\%$ , $V_S = 500\text{ V}$ (Note 2)	$1 \times 10^{12}$	$10^{14}$	—	$\Omega$
Isolation voltage	$BV_S$	AC, 1 minute	5000	—	—	$V_{rms}$
		AC, 1 second, in oil	—	10000	—	Vdc
		DC, 1 minute, in oil	—	10000	—	


## Switching Characteristics

(Unless otherwise specified,  $T_a = -40 \sim 100^\circ\text{C}$ ,  $V_{CC} = 4.5 \sim 20 \text{ V}$ .)


CHARACTERISTIC	SYMBOL	TEST CIRCUIT	CONDITION	MIN.	TYP. *	MAX.	UNIT
Propagation delay time to logic HIGH output	$t_{pLH}$	7	$I_F = 0 \rightarrow 5 \text{ mA}$ , $C_L = 100 \text{ pF}$ $V_{CC} = 20 \text{ V}$	50	250	600	ns
Propagation delay time to logic LOW output	$t_{pHL}$		$I_F = 5 \rightarrow 0 \text{ mA}$ , $C_L = 100 \text{ pF}$ $V_{CC} = 20 \text{ V}$	50	260	600	ns
Switching time dispersion Between ON and OFF	$ t_{pHL} - t_{pLH} $		$I_F = 0 \sim 5 \text{ mA}$ , $C_L = 100 \text{ pF}$ $V_{CC} = 20 \text{ V}$	—	—	550	ns
Output rise time	$t_r$		$I_F = 0 \rightarrow 5 \text{ mA}$ , $V_{CC} = 20 \text{ V}$	—	175	—	ns
Output fall time	$t_f$		$I_F = 5 \rightarrow 0 \text{ mA}$ , $V_{CC} = 20 \text{ V}$	—	95	—	ns
Propagation delay time to logic HIGH output	$t_{pLH}$	8	$I_F = 0 \rightarrow 5 \text{ mA}$	50	—	600	ns
Propagation delay time to logic LOW output	$t_{pHL}$		$I_F = 5 \rightarrow 0 \text{ mA}$	50	—	600	ns
Common-mode transient Immunity at LOW level output	$CM_L$	9	$V_{CM} = 1000 \text{ Vp-p}$ , $I_F = 0 \text{ mA}$ , $V_{CC} = 20 \text{ V}$ , $T_a = 25^\circ\text{C}$	10000	—	—	V/us
Common-mode transient Immunity at HIGH level output	$CM_H$		$V_{CM} = 1000 \text{ Vp-p}$ , $I_F = 5 \text{ mA}$ , $V_{CC} = 20 \text{ V}$ , $T_a = 25^\circ\text{C}$	-10000	—	—	V/us

\*All typical values are at  $T_a = 25^\circ\text{C}$ .


**TEST CIRCUIT 1 :  $V_{OL}$**




**TEST CIRCUIT 2 :  $V_{OH}$**




**TEST CIRCUIT 3 :  $I_{CCL}$**




**TEST CIRCUIT 4 :  $I_{CCH}$**





**TEST CIRCUIT 5 :  $I_{OSL}$**





**TEST CIRCUIT 6 :  $I_{OSH}$**





**TEST CIRCUIT 7: Switching Time Test Circuit**



**TEST CIRCUIT 8: Switching Time Test Circuit**



**TEST CIRCUIT 9: Common-Mode Transient Immunity Test Circuit**



$$CM_L = \frac{800(V)}{t_r(\mu s)} \quad CM_H = -\frac{800(V)}{t_f(\mu s)}$$

CM<sub>L</sub> (CM<sub>H</sub>) is the maximum rate of rise (fall) of the common mode voltage that can be sustained with the output voltage in the low (high) state.

**RESTRICTIONS ON PRODUCT USE**

030619EBC

- The information contained herein is subject to change without notice.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.  
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.