



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP240V10RT3U

BP240V10RT3U - External Battery Pack for UPS System

Highlights

- Extends runtime of compatible Tripp Lite UPS Systems with 240VDC external battery connection
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower or stack adaptable
- 2 year warranty



Description

Tripp Lite's BP240V10RT3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connectors for simple installation. Additional output connector allows multiple BP240V10RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU6000RT3U, SU6000RT3UXR, SU6000RT3UHV, SU10KRT3U, SU10KRT3UHV, SU10K3/1INTPM and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP240V10RT3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP240V10RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs
Connects to UPS via	Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)
DC system voltage	240VDC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	176
Unit weight (lbs)	152.5
Unit Dimensions (HWD/in)	5.25 x 17.5 x 22.5
Material of construction	Black steel cabinet
Form factors supported	Stacking upright tower and 3U rackmount form factors supported
CERTIFICATIONS	
Certifications	Tested to UL, cUL, CE, NOM
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2491.