



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: BP36V42-3U

BP36V42-3U - External Battery Pack for UPS System

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 36V DC external battery connector
- Provides daisy-chain compatibility for multiple connected battery packs
- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP36V42-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP36V42-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

Compatible UPS systems - SMART1500RML2Ua, SMX1500RTL2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- External battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Attractive all-black color scheme
- Additional output connector allows multiple battery packs to be daisy-chained to the UPS for even longer extended run operation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs

Connects to UPS via	Detachable cable with UPS specific DC connector (36 in length, 6 gauge)
DC system voltage	36V DC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	165.35
Shipping weight (kg)	75.1
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.6 x 58.42 x 80.01
Unit weight (lbs)	127.87
Unit weight (kg)	58.1
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.3 x 44.45 x 63.5
Material of construction	Steel
Form factors supported	Stacking, upright tower and 3U rackmount form factors supported
WARRANTY	
Product warranty	2 year
Optional coverage	3 and 5 year warranty extensions available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3018.