



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP48V24-2U

BP48V242U - External Battery Pack for UPS System

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 48VDC external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP48V242U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - SMART2200RMXL2U, SMART2600RM2U & SMART3000RM2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP48V242U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

NOTE: LIMIT OF 1 BP48V242U PER UPS, USE BP48V60RT3U FOR MULTI-PACK COMPATIBILITY

Specifications

BATTERY	
Connects to UPS via	Attached cable with blue 175 amp male DC connector
DC system voltage	48V DC

Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	70
Shipping weight (kg)	31.8
Shipping Dimensions (HWD/in)	7.25 x 23.5 x 18.5
Shipping Dimensions (HWD/cm)	18.4 x 59.7 x 47
Unit weight (lbs)	63
Unit weight (kg)	28.6
Unit Dimensions (HWD/in)	3.5 x 17.5 x 13.5
Unit Dimensions (HWD/cm)	8.9 x 44.5 x 34.3
Form factors supported	2U rackmount housing
CERTIFICATIONS	
Certifications	Tested to UL, cUL, CE, NOM
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2501.