



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP48V60-3UNAFTA

External Battery Pack for UPS System - NAFTA assembled version of BP48V60RT-3U

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 48VDC external battery connector
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP48V60-3UNAFTA rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP48V60-3UNAFTA battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SM2200RMNAFTA, SM3000RMNAFTA, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP48V60-3UNAFTA external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Additional output connector allows multiple BP48V60RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Blue 2-point battery connector

Connects to UPS via	Blue 2-point battery connector
DC system voltage	48VDC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	200.6
Shipping weight (kg)	91.1
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.6 x 58.4 x 80
Unit weight (lbs)	163.1
Unit weight (kg)	74
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.3 x 44.4 x 63.5
Material of construction	Steel
Form factors supported	Rack/tower (3U)
ENVIRONMENTAL	
Operating Temperature	32-104 degrees F / 0-40 degrees C
WARRANTY	
Product warranty	2 year product warranty
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3542.