



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP72V15-2U

BP72V15-2U - External Battery Pack for UPS System

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 72VDC black 3-point external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP72V15-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation.

COMPATIBLE UPS SYSTEMS - SU3000RTXR3U, SU3000RTXL3U, SUINT3000RTXL3U, SU3000RTXL3UHV and other Tripp Lite UPS systems that specify the use of this battery pack.

Package Includes

- BP72V15-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 4 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	No, a max quantity of ONE BP72V15-2U can be connected to the host UPS system. If additional battery packs are to be connected, use an expandable model, like BP72V21RT-3U
Connects to UPS via	DC connector
DC system voltage	72VDC
Typical battery lifespan	4-6 years typical (North America)

PHYSICAL	
Shipping weight (lbs)	89.35
Shipping weight (kg)	40.6
Shipping Dimensions (HWD/in)	9.5 x 30 x 23.75
Shipping Dimensions (HWD/cm)	24.1 x 7.62 x 60.3
Unit weight (lbs)	78.1
Unit weight (kg)	35.5
Unit Dimensions (HWD/in)	3.5 x 17.5 x 20.75
Unit Dimensions (HWD/cm)	8.9 x 52.7 x 52.7
Material of construction	Steel
Form factors supported	2u rackmount housing (supports tower installation with optional 2-9U STAND accessory)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3019.