



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP72V28-3UNAFTA

External Battery Pack for UPS System - NAFTA assembled version of BP72V28RT-3U

Highlights

- Extends the runtime of select compatible Tripp Lite UPS systems with 72VDC external battery connector
- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty



Description

BP72V28-3UNAFTA rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. Additional DC connector enables the daisy-chaining of multiple external battery packs for longer extended run capability. COMPATIBLE UPS SYSTEMS - SU3000RMNAFTA, SU3000XLNAFTA, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP72V28-3UNAFTA external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY	
Expandable battery runtime	Yes, DC connector accepts daisy-chaining of multiple external battery packs for extended runtime operation
Connects to UPS via	Black 3-point battery connector

DC system voltage	72VDC
Typical battery lifespan	4-6 years typical
PHYSICAL	
Shipping weight (lbs)	203.9
Shipping weight (kg)	92.57
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.58 x 58.42 x 80.01
Unit weight (lbs)	166.45
Unit weight (kg)	75.57
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.33 x 44.45 x 63.5
Material of construction	Steel
Form factors supported	Rack/tower (3U)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3544.