



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPDM13

**Corded UPS Backplate Outlet Kit - Adds AC plug-in connection and AC output receptacles to SU6000RT3U and SU6000RT3UXR UPS for use with 240V UPS output voltage configurations**



### Highlights

- Converts Tripp Lite's hardwire SU6000RT3U UPS systems to one with AC plug and outlets
- For use with 240V UPS output voltage configurations
- 10 ft. / 3m AC input power cable with NEMA L6-30P input plug
- 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

### Description

Tripp Lite's SUPDM13 corded backplate kit converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system into one with AC plug and outlets. 10 ft./3m input line cord with L6-30P plug enables simple connection to 240V 30A mains power. Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles. Easy quick-connect wiring installs in minutes.

VOLTAGE COMPATIBILITY NOTE - SUPDM13 supports SU6000RT3U and SU6000RT3UXR applications configured for 240V nominal input voltage only (See SUPDM12 for 208V input voltage configurations).

### Applications

Ideal for 240V applications calling for Tripp Lite's SU6000RT3U and SU6000RT3UXR UPS systems where plug-in AC input and output connections are required

### Features

- Converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system to one with an AC plug and outlets
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

### Specifications

SYSTEM OVERVIEW	
Voltage compatibility	Compatible with Tripp Lite's SU6000RT3U UPS systems configured for 240V nominal input voltage
OUTPUT	
Output nominal voltage	Simultaneous 240 and 120V output
Outlet quantity / type	240V: 1 L6-30R, 2 L6-20R / 120V: 10 15/5-20R
Overload protection	120V outlets are protected by 2 separate 20A branch rated circuit breakers
INPUT	
Input connection type	NEMA L6-30P input plug

<b>Input cord length</b>	10 ft. / 3m
<b>Recommended electrical service</b>	30A 240V
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	6.6
<b>Shipping weight (kg)</b>	3
<b>Shipping Dimensions (HWD/in)</b>	5.5 x 9 x 14.25
<b>Shipping Dimensions (HWD/cm)</b>	14 x 22.9 x 36.2
<b>Unit weight (lbs)</b>	6
<b>Unit weight (kg)</b>	2.8
<b>Unit Dimensions (HWD/in)</b>	2.5 x 5 x 11
<b>Unit Dimensions (HWD/cm)</b>	6.4 x 12.7 x 28
<b>Material of construction</b>	Steel
<b>WARRANTY</b>	
<b>Product warranty</b>	2 years

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=2778](http://www.tripplite.com/products/model.cfm?txtModelID=2778).