



- ~ Receptacles turned 90° to allow space for wall transformers.
- ~ Built to meet the rugged requirements of industrial and commercial use.
- ~ All metal housing – tough extruded aluminum case with black powder-coated steel cover.
- ~ Heavy-duty cord – 14/3 SJTW wire for extreme temperature ranges.
- ~ Integral molded straight -blade (NEMA 5-15P) or twist lock (NEMA L5-15P) configuration.
- ~ Separate mounting feet with keyhole slots provide for work station mounting if desired.
- ~ Available with lighted on/off switch or red pilot light to indicate power on.
- ~ Includes 15A, 125VAC circuit breaker to prevent accidental line overload.
- ~ CSA certified and UL 1363 listed



15 Amp Industrial / Commercial Grade with 90° Receptacles

Part No.	Outlets	On-Off Switch	Pilot Light	Plug Type	Cord Length	Dimensions (Inches) LxWxH	Electrical Rating	Shipping Weight
1584H4A1RA	4	Yes	-	Straight	6'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584H4B1RA	4	Yes	-	Straight	15'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584H4C1RA	4	Yes	-	Twist Lock	6'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584H4D1RA	4	Yes	-	Twist Lock	15'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584T4A1RA	4	-	Yes	Straight	6'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584T4B1RA	4	-	Yes	Straight	15'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584T4C1RA	4	-	Yes	Twist Lock	6'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584T4D1RA	4	-	Yes	Twist Lock	15'	14 x 2 x 2	120VAC/15A	1.8 lbs
1584H6A1RA	6	Yes	-	Straight	6'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584H6B1RA	6	Yes	-	Straight	15'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584H6C1RA	6	Yes	-	Twist Lock	6'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584H6D1RA	6	Yes	-	Twist Lock	15'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584T6A1RA	6	-	Yes	Straight	6'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584T6B1RA	6	-	Yes	Straight	15'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584T6C1RA	6	-	Yes	Twist Lock	6'	17 x 2 x 2	120VAC/15A	2.0 lbs
1584T6D1RA	6	-	Yes	Twist Lock	15'	17 x 2 x 2	120VAC/15A	2.0 lbs

