



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDUNV

Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment

Highlights

Versatile PDU system supports 1U rackmount, 0U vertical mount, wall mount and under-counter installation

Supports 100-250V power distribution via 12 C13 and 2 C19 outlets

10 foot / 3m attached power cord with C20 power input connection

Included pack of 5 secured C19 adapters support plug-in connection via C14, L6-20P, L5-20P, 5-20P or 5-15P input plug

16A circuit breaker



Description

The PDUNV Universal Rackmount PDU offers multi-outlet power distribution for worldwide low and high voltage applications from 100-250V via built-in C19 and C13 outlets. 1U rackmount chassis also supports 0U vertical mount, wall mount and under-counter mount installation in a variety of applications. Attached 10 foot, 3m input cord offers a C20 plug-in connection. Pack of 5 included C19 adapters with secure locking retainer clip enables plug conversion to C14, L6-20P, L5-20P, 5-20P and 5-15P. 16A circuit breaker, grounding lug. Mounting hardware included.

Applications

Multi-outlet power distribution unit is the ideal means of powering multiple loads in 19 inch rackmount, wallmount and under-counter applications. Ideal for distribution of UPS, generator or commercially derived AC power to multiple equipment loads.

Package Includes

- 1U rackmount PDU
- Mounting hardware
- Set of 5 plug adapters
- User manual with warranty information

Features

PDUNV supports multi-outlet power distribution with worldwide compatibility for 100-250V applications

Supports standard 1U rackmount installation, with additional support for 0U vertical mount, wallmount and under-counter mount installation

Includes 2 C19 high current and 12 C13 low current outlets

Includes 10 foot, 3m attached input power cable with C20 input plug-in connection (connects to C19 100-250V)

Pack of 5 included C19 adapters with locking retainer clip enables plug conversion to C14 (connects to C13 100-250V), L6-20P (connects to L6-20R 20A 208/240V), L5-20P (connects to L5-20R 20A 120V), 5-20P (connects to 5-20R 20A 120V) and 5-15P (connects to 5-15R 15A)

Unfiltered electrical pass-through reliably distributes AC power from UPS or generator to supported equipment

Back panel grounding lug

16A circuit breaker

Specifications

SYSTEM OVERVIEW

| | |
|-------------------------------------|---|
| Voltage compatibility | 100-250V |
| Frequency compatibility | 50/60 |
| OUTPUT | |
| Output nominal voltage | 100-250V |
| Outlet quantity / type | 12 IEC-C13 & 2 IEC-C19 |
| Overload protection | 16A |
| INPUT | |
| Maximum input amps | 16A |
| Input connection type | IEC-C14, NEMA L6-20P, NEMA L5-20P, NEMA 5-20P & NEMA 5-15P |
| Input cord length | 10 feet / 3m |
| PHYSICAL | |
| Shipping weight (lbs) | 3.8 |
| Shipping weight (kg) | 1.72 |
| Shipping Dimensions (HWD/in) | 2.5 x 10 x 20.25 |
| Shipping Dimensions (HWD/cm) | 6.35 x 25.4 x 52.1 |
| Unit weight (lbs) | 3.2 |
| Unit weight (kg) | 1.45 |
| Unit Dimensions (HWD/in) | 1.75 (1U) x 17.5 x 4.25 |
| Unit Dimensions (HWD/cm) | 4.44 x 44.45 x 10.8 |
| Material of construction | Sheet metal |
| Form factors supported | 1U rackmount, 0U vertical mount, wallmount and under-counter mounting supported |
| ENVIRONMENTAL | |
| Relative Humidity | 0-95% non condensing |
| CERTIFICATIONS | |
| Certifications | Tested to UL60950 (USA), CSA (Canada), CE (EU) |
| WARRANTY | |
| Product warranty | Lifetime |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3308.