### **PS-615-HG**

Versatile power distribution strip

15A resettable circuit breaker

- 6 hospital-grade outlets and hospital-grade plug
- ▶ 15-ft. cord



# **DESCRIPTION**

Tripp Lite's PS-615-HG Power Strip offers 15 amp capacity AC power distribution in a rugged all-metal outlet strip for 120 volt applications. Features 6 Hospital Grade receptacles, 15 foot AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional use keyhole mounting tabs and flanges.

PLUG / OUTLETS: Input: NEMA 5-15PHG Hospital Grade Plug / Output: 6 NEMA5-15RHG Hospital Grade Receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

### **KEY BUYING POINTS**

- Rugged all-metal housing withstands years of use without breakage
- 6 Hospital-Grade NEMA5-15RHG output receptacles
- 15 foot AC cord with integrated, molded Hospital-Grade NEMA5-15PHG plug
- Optional use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15 amp electrical capacity with built-in resettable circuit breaker
- 120 volt, 50/60Hz electrical compatibility
- · Certified by UL (USA) and cUL (Canada)

# **TYPICAL APPLICATIONS**

 AC power distribution for computers and equipment in areas where hospital-grade input/output components are required. Not for use in critical care environments.

# PACKAGE INCLUDES

- PS-615-HG Power Strip
- User manual with warranty information

## COMPLETE SPECIFICATIONS

## SYSTEM OVERVIEW

System overview:	6 outlet power strip with hospital grade plug and outlets, 15 ft. cord
Voltage compatibility:	120VAC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	15A
Outlet quantity / type:	6 Nema 5-15R Hospital Grade
Outlet orientation:	Single row of 6
Overload protection:	15A circuit breaker
INPUT	
Input connection type:	Nema 5-15P hospital grade input plug
Input cord length (ft.):	15
Input cord length (m):	4.572
Recommended electrical service:	15A 120V
LEDS ALARMS & SWITCHES	
Switches:	No power switch
Switches: PHYSICAL	No power switch
	No power switch  1.5 x 2.5 x 12.5
PHYSICAL	
PHYSICAL Unit Dimensions (HWD/in):	1.5 x 2.5 x 12.5
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm):	1.5 x 2.5 x 12.5 3.8 x 6.35 x 31.75
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction:	1.5 x 2.5 x 12.5 3.8 x 6.35 x 31.75 Metal
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs:	1.5 x 2.5 x 12.5 3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs: Housing color:	1.5 x 2.5 x 12.5 3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  White
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs: Housing color: Receptacle color:	1.5 x 2.5 x 12.5  3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  White  White
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs: Housing color: Receptacle color: AC line cord color:	1.5 x 2.5 x 12.5  3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  White  White
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs: Housing color: Receptacle color: AC line cord color: CERTIFICATIONS	1.5 x 2.5 x 12.5  3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  White  White  White
PHYSICAL Unit Dimensions (HWD/in): Unit Dimensions (HWD/cm): Material of construction: Integrated keyhole mounting tabs: Housing color: Receptacle color: AC line cord color: CERTIFICATIONS UL1363 (Power Tap):	1.5 x 2.5 x 12.5  3.8 x 6.35 x 31.75  Metal  Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  White  White  White  UL1363

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2003 Tripp Lite. All Rights Reserved.