

Tripp Lite Power Strips & PDUs

Multiple outlets wherever you need them

PDU1215

- ▶ Designed for standard 19-inch racks (1U high)
- ▶ 12 rear-facing outlets
- ▶ 15-ft. cord
- ▶ 15-amp circuit breaker
- ▶ Switchless design



DESCRIPTION

Tripp Lite's PDU1215 AC power distribution unit offers 15 amp, 120 volt capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 1U/0U rackmount installation. Uses only 1 rack space (1U) when installed in any 19 inch rack, with the potential for 0U mounting in the cable management area of most rack enclosures. Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes. Attractive housing with all rear-facing outlets measures only 2.75 inches in depth. Unfiltered electrical pass-through without a power switch makes PDU1215 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 rear-facing NEMA5-15R outlets, 15-ft. AC power cord, 15 amp circuit breaker, grounding lug and rugged all-metal case design.

PLUG / OUTLETS - Input: NEMA 5-15P / Output: 12 NEMA5-15R (rear-facing)

ELECTRICAL - 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT - Supports 19 in. rackmount (1U/0U), wallmount, under-counter and more

KEY BUYING POINTS

- Corded AC power distribution unit with 15 amp capacity and 12 AC receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in both 1U or zero-U formats
- Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes, including zero-U rackmount capability in the cable management area or other available space within a rack enclosure
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- When placed in traditional 1U rackmount installation, attractive all-metal housing offers the appearance of a 1U blanking panel to the front, protecting the 12 rear-facing output receptacles
- 12 NEMA5-15R rear-facing output receptacles accept common NEMA5-15 equipment plugs
- 15 foot AC cord NEMA5-15P plug connection
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

TYPICAL APPLICATIONS

- Multi-outlet power distribution unit is the ideal means of powering multiple loads in 19 inch rackmount, wallmount and under-counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

PACKAGE INCLUDES

- PDU1215 Rackmount Power Strip
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	1U rackmount, 0U vertical rackmount, wallmount or under-counter Power Distribution Unit
Voltage compatibility:	120V AC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	15A
Outlet quantity / type:	12 Nema 5-15R
Outlet orientation:	12 rear facing outlets
INPUT	
Input connection type:	Nema 5-15P input plug
Input cord length (ft.):	15
Input cord length (m):	4.572
Recommended electrical service:	15A 120V
LEDS ALARMS & SWITCHES	
Switches:	No power switch
PHYSICAL	
Unit Dimensions (HWD/in):	1.75 x 17.5 x 4.5
Unit Dimensions (HWD/cm):	4.445 x 44.45 x 11.4
Material of construction:	Sheet metal
Form factors supported:	1U rackmount, 0U vertical rackmount, wall-mount and undercounter installation supported
Housing color:	Black
Receptacle color:	Black
AC line cord color:	Black
CERTIFICATIONS	
cUL / CSA (Canada):	cUL
Approvals:	UR
WARRANTY	
Product warranty:	Lifetime
SPECIAL FEATURES	
TVSS grounding:	Back panel nut and bolt grounding lug

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.
Please make note that this information was posted on 08/14/2003.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2003 Tripp Lite. All Rights Reserved.