



Model #: 3SP

Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



Highlights

3 outlets

6-ft. cord

8.6 in. overall length

Lighted master power switch

Description

The Waber-by-Tripp Lite 3SP power strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center spacing, 6-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and permits connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 3SP ideal for distributing alternate waveform UPS or generator power. Features a rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15-amp resettable circuit breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 3 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes 3SP ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

3SP Power Strip Warranty information Instruction manual

Features

Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center outlet spacing Lighted power switch with transparent snap-over guard to prevent accidental shutoff Keyhole mounting tabs support permanent installation on a wide variety of surfaces UL1363 (USA), cUL (Canada)
15-amp power handling capacity with circuit breaker 6-foot AC line cord

Specifications

| SYSTEM OVERVIEW | |
|----------------------------------|--|
| Voltage compatibility | 120VAC |
| Frequency compatibility | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps) | 15A |
| Outlet quantity / type | 3 NEMA 5-15R |
| Outlet orientation | Single row of 3 |
| Outlet spacing | 1.75 in. |
| INPUT | |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 6 |
| Input cord length (m) | 1.8288 |
| Recommended electrical service | 15A 120V |
| LEDS ALARMS & SWITCHES | |
| Switches | Illuminated 2 positon switch controls power to all outlets |
| Locking switch cover | Transparent locking switch cover prevents accidental shutoff |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 7.38 x 2.5 x 1.5 |
| Unit Dimensions (HWD/cm) | 18.7 x 6.35 x 3.8 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Keyhole mounting tabs enable mounting to a variety of surfaces |
| Receptacle Color | Black |
| AC line cord color | Black |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |
| Product warranty | Lifetime |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=1952.

©2008 Tripp Lite. All Rights Reserved.