

Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234 E-mail: saleshelp@tripplite.com

Model #: 6SP

Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



Highlights

6 outlets 6-ft. cord 13.7-in. overall length Lighted master power switch

Description

The Waber-by-Tripp Lite 6SP Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles with 1.625 inch center-to-center spacing, 6-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes 6SP ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes the 6SP ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

6SP Power Strip Warranty information Instruction manual

Features

Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications Includes 6 NEMA 5-15R output receptacles with 1.625-in. center-to-center outlet spacing Lighted power switch with transparent snap-over guard to prevent accidental shutoff Keyhole mounting tabs support permanent installation on a wide variety of surfaces UL1363 (USA), cUL (Canada) 15A power handling capacity with circuit breaker 6-foot AC line cord

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Single row of 6
Outlet spacing	1.625 in.
INPUT	
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord length (m)	1.8288
Recommended electrical service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Illuminated 2-positon switch controls power to all outlets
Locking switch cover	Transparent locking switch cover prevents accidental shutoff
PHYSICAL	
Unit Dimensions (HWD/in)	12.5 x 2.5 x 1.5
Unit Dimensions (HWD/cm)	31.75 x 6.35 x 3.8
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs enable mounting to a variety of surfaces
Receptacle Color	Black
AC line cord color	Black
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=1956.

©2008 Tripp Lite. All Rights Reserved.