UL24CB-15

- 6 outlets
- ▶ 15 ft. cord
- 12.5" length

- All metal housing
- Lighted master switch



DESCRIPTION

The Waber-by-Tripp Lite UL24CB-15 Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles with 1.625 inch center-to-center spacing, 15 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes UL24CB-15 ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15 amp resettable circuit breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG / OUTLETS - Input: NEMA 5-15P / Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

KEY BUYING POINTS

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles with 1.625 inch center-to-center outlet spacing
- · Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity with circuit breaker
- 15 foot AC line cord
- Lifetime warranty

TYPICAL APPLICATIONS

 Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes UL24CB-15 ideal for distributing alternate waveform UPS or generator power to protected equipment.

PACKAGE INCLUDES

- UL24CB-15 Power Strip
- Warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	6 outlet power strip, 15 ft. cord
Voltage compatibility:	120VAC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	15A
Outlet quantity / type:	6 Nema 5-15R outlets
Outlet orientation:	Single row of 6
Outlet spacing:	1.625 in.
INPUT	
Input connection type:	Nema 5-15P input plug
Input cord length (ft.):	15
Input cord length (m):	4.572
Input cord gauge, type:	14 gauge, SJT
Recommended electrical service:	15A 120V
LEDS ALARMS & SWITCHES	
Switches:	Lighted 2 position switch controls power to all outlets
Locking switch cover:	Transparent on/off switch cover prevents accidental turn-off
PHYSICAL	
Unit Dimensions (HWD/in):	12.5 x 2.5 x 1.5
Unit Dimensions (HWD/cm):	31.75 x 6.35 x 3.8
Material of construction:	Metal
Integrated keyhole mounting tabs:	Keyhole mounting tabs enable mounting to a variety of surfaces
Housing color:	Blue Gray
Receptacle color:	Black
AC line cord color:	Black
CERTIFICATIONS	
UL1363 (Power Tap):	UL1363
cUL / CSA (Canada):	cUL
WARRANTY	
Product warranty:	Lifetime

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.