



Model #: PDUMV15

Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter



Highlights

Digital current meter display

16 outlets

Convenient and safe covered on/off switch

15 amp breaker

15-ft. cord

48" length

Description

Tripp Lite's PDUMV15 metered power distribution unit offers 15 amp, 120V multi-outlet AC power distribution in a convenient 48-inch mountable housing. Digital current meter displays the power consumption of connected equipment. Offers vertical power distribution in rackmount, raceway, and workbench applications. Includes 16 NEMA 5-15R output receptacles, 15 ft. AC line cord, and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory, or factory environments. Unfiltered electrical pass-through makes the PDUMV15 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Included 16 NEMA5-15R outlets, 15-ft. AC power cord with 5-15P plug, 15 amp circuit breaker in rugged metal case design.

PLUG/OUTLETS-Input: NEMA 5-15P/Output: 16 NEMA 5-15R

ELECTRICAL - 120V AC, 50/60Hz, 15A

FORMAT - 48 inch mountable strip format

Applications

Ideal for horizontal or vertical raceway style metered power distribution in office, workbench, industrial, networking, and telecom applications.

Package Includes

PDUMV15 Metered Vertical PDU Mounting hardware 6 outlet safety covers

Owner's manual with warranty information

Features

Digital current montoring display

Sturdy all-metal 48-inch corded PDU

Includes hardware for Zero U configuration in rack enclosures as well as horizontal mounting in raceways and more

16 NEMA 5-15R output receptacles

Lighted power switch with locking transparent safety cover prevent accidental shutoff of connected devices

15 amp electrical capacity with circuit breaker

Specifications

Voltage compatibility 120V Frequency compatibility 50 / 60Hz OUTPUT Output VA 15A / 1800VA Output nominal voltage 120V Outlet quantity / type 16 NEMA 5-15R Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping Weight (lbs) 4.2 Shipping Dimensions (HWD/in) 3.x 48 x 1.5 Material of construction Aluminum Form factors supported Vertical (0U) mounting in rack enclosures, horziontal mount in raceways and a variety of other applications
Output VA
Output VA 15A / 1800VA Output nominal voltage 120V Outlet quantity / type 16 NEMA 5-15R Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping Dimensions (HWD/in) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction
Output nominal voltage 120V Outlet quantity / type 16 NEMA 5-15R Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Outlet quantity / type 16 NEMA 5-15R Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping Weight (Ibs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Overload protection 15A INPUT Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit bimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Maximum input amps 15A Input connection type NEMA 5-15P Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (Ibs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Input connection type Input cord length Input co
Input cord length 15 ft. LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 3.8 Unit weight (lbs) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
LEDS ALARMS & SWITCHES Front panel LEDs Digital LED current monitor display Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 51.5 x 3.5 x 2.5 Unit weight (lbs) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Front panel LEDs Digital LED current monitor display Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 51.5 x 3.5 x 2.5 (HWD/in) Jan 3 x 48 x 1.5 Material of construction Digital LED current monitor display Lighted on/off switch with integrated safety cover 51.5 x 3.5 x 2.5 Aluminum
Switches Lighted on/off switch with integrated safety cover PHYSICAL Shipping weight (lbs) 51.5 x 3.5 x 2.5 (HWD/in) Unit weight (lbs) 3.8 Unit Dimensions (HWD/in) Aluminum
PHYSICAL Shipping weight (lbs)
Shipping weight (lbs) 4.2 Shipping Dimensions (HWD/in) 51.5 x 3.5 x 2.5 Unit weight (lbs) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Shipping Dimensions (HWD/in) 51.5 x 3.5 x 2.5 Unit weight (lbs) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
(HWD/in) Unit weight (Ibs) 3.8 Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Unit Dimensions (HWD/in) 3 x 48 x 1.5 Material of construction Aluminum
Material of construction Aluminum
Form factors supported Vertical (0U) mounting in rack enclosures, horziontal mount in raceways and a variety of other applications
CERTIFICATIONS
Certifications Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant
WARRANTY
Product warranty Lifetime warranty
SPECIAL FEATURES
Appearance Silver housing

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3458.

©2008 Tripp Lite. All Rights Reserved.