

Model #: PDUMV20

Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter



Highlights

Digital current meter display 20 outlets Convenient and safe covered, on/off switch 20-amp circuit breaker 15-ft. AC power cord 60 inch length Tooless button mount installation

Description

Tripp Lite's PDUMV20 metered power distribution unit offers 20 amp, 120V multi-outlet AC power distribution in a convenient 60 inch mountable housing. Digital current meter displays the power consumption of connected equipment. Offers vertical power distribution in rackmount, raceway, and workbench applications. Tooless installation supports fast installation in button-mount compatible equipment racks. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory, or factory enviroments. Unfiltered electrical pass-through makes the PDUMV20 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 20 NEMA 5-15/20R output receptacles, 15 ft. AC line cord, lighted power switch with locking transparent cover to prevent accidental shutoff, and 20 amp circuit breaker in rugged metal case design.

PLUG/OUTLETS-Input: NEMA L5-20P/Output: 20 NEMA 5-15/20R

ELECTRICAL- 120V AC, 50/60Hz, 20A [Requires NEMA L5-20R or 5-20R(using included adapter) wall receptacle]

FORMAT- 60 inch mountable strip format

Applications

Offers vertical or horizontal multi-outlet power distribution in rack enclosures, raceways, desktops and more. Ideal for distribution of alternate, sinewave UPS and generator power, or commercially derived AC power to connected equipment.

Package Includes

PDUMV20 Metered Vertical PDU (1) L5-20P to 5-20P plug adapter Mounting hardware Six protective outlet covers Instruction manual with warranty information

Features

Corded AC power distribution unit with 20 amp capacity and 20 AC receptacles Digital current meter display Sturdy 60 inch aluminum housing Tooless installation supports fast installation in button-mount compatible equipment racks Included hardware allows for Zero-U configurations in rack enclosures

Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, network, and telecom applications Lighted power swith with locking transparent safety cover prevents accidental shutoff

20 amp electrical capacity

120V AC, 50/60Hz electrical compatibility 15 ft. power cord

Lifetime warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V
Frequency compatibility	50 / 60 Hz
OUTPUT	
Output VA	20A
Output watts	2400 watts
Output nominal voltage	120V
Outlet quantity / type	20 NEMA 5-15/20R
Overload protection	20A
INPUT	
Maximum input amps	20A
Input connection type	NEMA L5-20P with NEMA 5-20P plug adapter
Input cord length	15 feet
Recommended electrical service	20A 120V AC recommended with twist lock 20A wall receptacle
LEDS ALARMS & SWITCHES	
Front panel LEDs	Digital ammeter display
Switches	Lighted on/off switch with integrated transparent saftey cover
PHYSICAL	
Shipping weight (lbs)	5.9
Shipping Dimensions (HWD/in)	3 x 63.25 x 2.75
Unit weight (Ibs)	5.2
Unit Dimensions (HWD/in)	1.75 x 60 x 1.25
Material of construction	Aluminum
Form factors supported	Vertical
CERTIFICATIONS	
Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant
WARRANTY	
Product warranty	Lifetime
SPECIAL FEATURES	
Appearance	Black housing with digital current meter display

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3467.