



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLM915NC

Power It! Power Strip - Convenient multiple outlets for every application



Highlights

- 9 outlets (including 1 end-mounted outlet)
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 15 ft. power cord
- Rugged metal case
- Keyhole mounting slots

Description

Tripp Lite's Power It! TLM915NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 9 NEMA 5-15R outlets (including one end-mounted outlet ideal for accommodating a transformer without blocking other outlets), 15-foot AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads. Lifetime warranty.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 9 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: Corded power distribution strip

Applications

Offers a reliable, convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.

Unfiltered electrical pass-through makes the power strip ideal for distributing alternate waveform UPS or generator power to connected equipment.

Package Includes

- TLM915NC power strip
- Warranty information
- Instruction manual

Features

Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment

Includes 9 NEMA 5-15R outlets

Illuminated on/off switch provides one-touch power control for connected equipment

Transparent switch cover snaps tight to prevent accidental shutoff

Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications

- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 15-foot AC power cord
- Rugged metal case provides extra safety and durability
- UL certification
- Lifetime warranty
- Includes an end-mounted outlet ideal for accommodating a transformer without blocking other outlets

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Output watts	1800
Outlet quantity / type	9 NEMA 5-15R
Outlet orientation	Single row of 8 plus 1 end-mounted outlet
Overload protection	15A circuit breaker
Transformer accommodation	End-mounted outlet is ideal for accommodating a transformer without blocking other outlets
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	SJT 14AWG
Input cord length (ft.)	15
Input cord length (m)	4.5
Recommended electrical service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Illuminated on/off switch controls power to all outlets
Locking switch cover	Transparent switch cover snaps tight to prevent accidental shutoff
PHYSICAL	
Shipping weight (lbs)	3
Shipping weight (kg)	1.4
Shipping Dimensions (HWD/in)	15.5 x 6.5 x 2.25
Shipping Dimensions (HWD/cm)	39.4 x 16.5 x 5.7
Unit weight (lbs)	2.8
Unit weight (kg)	1.3
Unit Dimensions (HWD/in)	13.75 x 2.5 x 2
Unit Dimensions (HWD/cm)	35 x 6.35 x 5.1
Material of construction	Metal case
Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces
Receptacle Color	Light Gray
AC line cord color	Light Gray

CERTIFICATIONS

Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3465.