



## Model #: HT1010SAT3

# Home/Business Theater Surge Suppressor - Advanced-performance surge and line noise protection for all components



## **Highlights**

10 outlets / 10-ft. cord

3345 joule rating

3-line coaxial (gold) surge protection

1-line tel/modem/network (100BaseT, high-speed) surge protection

\$250,000 Ultimate Lifetime Insurance (USA and Canada only)

### **Description**

Tripp Lite's HT1010SAT3 Home/Business Theater Surge Suppressor provides advanced protection—3345 joules—stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 10 outlets (with transformer spacing and sliding safety covers), 3-line coaxial protection and 1-line tel/modem/Ethernet (100BaseT, high-speed) protection safeguard an entire home/business theater system. \$250,000Ultimate Lifetime Insurance coverage (USA and Canada only). Includes two diagnostic LEDs, color-coordinated holographic outlet/plug labels, 10-ft. cord with a right-angle plug, 6-ft. gold DSS cable, 6-ft. coaxial cable, 6-ft. phone cord and 6-ft. network cable.

#### **Applications**

Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

#### Package Includes

HT1010SAT3 Home/Business Theater Surge Suppressor 6-ft. gold DSS cable, 6-ft. coaxial cable, 6-ft. phone cord and 6-ft. network cable Instruction manual with warranty information

#### **Features**

3345 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)

\$250,000 Ultimate Lifetime Insurance (USA and Canada only) covers connected components against surge damage...for life!

10 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system

Widely spaced outlets accommodate up to 5 transformers

Sliding safety covers protect against accidental contact

Color-coordinated, holographic outlet/plug labels match outlets with component power cords

3 sets of surge-protected Type F gold coaxial connectors (with included 6-ft. gold DSS cable and 6 ft. coaxial cable) safeguard components on cable, satellite and antenna line

1-line tel/modem/Ethernet (100BaseT, high-speed) surge protection (with included 6 ft. phone cord and 6-ft. network cable) safeguards personal video recorders (PVRs) on a single dial-up or Ethernet line. Built-in splitter (1 jack in and 2 jacks out) allows simultaneous connection of two

devices sharing a single line

10-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system

2 diagnostic LEDs alert user to protection and grounding status

Keyhole slots provide convenient wall or cabinet mounting

Master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload

High-impact plastic housing (black) stands up to the most demanding environments

UL and cUL listed

Lifetime product warranty

# **Specifications**

SYSTEM OVERVIEW		
Voltage compatibility	120 VAC	
Frequency compatibility	50/60 Hz	
OUTPUT		
Output volt amp capacity (amps)	15	
Output watts	1800	
Outlet quantity / type	10 NEMA 5-15R	
Transformer accommodation	Accommodates 5 transformers	
INPUT		
Input connection type	NEMA 5-15P	
Input cord gauge, type	14 gauge, SJT	
Input cord length (ft.)	10 ft.	
Input cord length (m)	3	
Recommended electrical service	120V,15A	
Input plug features	Space-saving right-angle input plug	
LEDS ALARMS & SWITCHES		
Diagnostic LEDs	Built-in LEDs confirm protection and grounding status	
Switches	Combination AC circuit breaker and 2-position on/off power switch	
SURGE / NOISE SUPPRESSION		
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
AC suppression joule rating	3345 joules	
Clamping voltage (RMS)	150V	
AC suppression response time	< 1 ns	
UL1499 let through rating	330V - UL verified	
EMI / RFI filtering	Up to 40 dB	
PHYSICAL		
Shipping weight (lbs)	3.53	
Shipping weight (kg)	1.6	
Shipping Dimensions (HWD/in)	2.25 x 15 x 9.25	
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 23.5	
Unit weight (lbs)	2.42	
Unit weight (kg)	1.1	

Unit Dimensions (HWD/in)	1.75 x 11.75 x 4.75	
Unit Dimensions (HWD/cm)	4.5 x 29.8 x 12.1	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting	
AC line cord color	Black	
CERTIFICATIONS		
UL1449 1998 Rev. (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC Part 68	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product warranty	Lifetime	
Connected equipment insurance (USA and Canada Only	\$250,000	
DATALINE SURGE SUPPRESSION		
Coax line protection	3 line	
Telephone / Modem line protection	1 line	
Overview		
Style	Strip	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2809.

©2008 Tripp Lite. All Rights Reserved.