



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: HT10DBS

Isobar Home/Business Theater Surge Suppressor - Premium-performance surge and line noise protection for all components



Highlights

- 10 outlets / 8-ft. cord
- 3570 joule rating
- Isolated Filter Banks / all-metal housing
- 3-line coaxial (gold) surge protection
- 1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection
- \$500,000 [Ultimate Lifetime Insurance](#) (USA and Canada only)

Description

Tripp Lite's HT10DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--3570 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 10 outlets (with transformer spacing and plug-in safety covers), 3-line coaxial protection, 1-line tel/modem protection and 1-line network (100BaseT, high-speed) protection safeguard an entire home/business theater system. \$500,000 [Ultimate Lifetime Insurance](#) coverage (USA and Canada only). Includes all-metal housing, color-coordinated outlet/plug labels, three diagnostic LEDs, 8-ft. cord with a right-angle plug, 6-ft. gold coax cable, 6-ft. phone cord and 6-ft. network cable.

Applications

Perfect for medium-to-large home/business theater installations: high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more.

Package Includes

- HT10DBS Home/Business Theater Surge Suppressor
- 6-ft. DSS cable
- 6-ft. phone cord
- 6-ft. network cable
- Instruction manual with warranty information

Features

- 3570 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$500,000 [Ultimate Lifetime Insurance](#) (USA and Canada only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 10 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely spaced outlets accommodate up to 6 transformers

Four plug-in safety covers protect against accidental contact with unused outlets

3 sets of surge-protected Type F gold coaxial connectors (with included 6-ft. gold coax cable) safeguard components on cable, satellite and antenna line

1-line tel/modem and 1-line network (100BaseT, high-speed) surge protection (with included 6-ft. phone cord and 6-ft. network cable) safeguards personal video recorders (PVRs) on up to two lines simultaneously.

8-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system

3 diagnostic LEDs alert user to protection, line power and ground status

Keyhole slots provide convenient wall or cabinet mounting

Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload

All-metal housing (black) stands up to the most demanding environments

UL and cUL listed

Lifetime product warranty

Color-coordinated outlet/plug labels

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	12
Output watts	1440
Outlet quantity / type	10 NEMA 5-15R
Transformer accommodation	Accommodates 6 transformers
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	8 ft.
Input cord length (m)	2.4
Recommended electrical service	120V, 15A
Input plug features	Space-saving right-angle input plug
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm line power, protection and ground status
Switches	Combination AC circuit breaker and illuminated 2 position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	3570 joules
Clamping voltage (RMS)	140V
AC suppression response time	NM = instantaneous CM = < 1 ns
UL1499 let through rating	330V - UL verified
EMI / RFI filtering	Up to 60 dB
PHYSICAL	
Unit weight (lbs)	3.5
Unit weight (kg)	1.6
Unit Dimensions (HWD/in)	14.25 x 2.25 x 3.5

Unit Dimensions (HWD/cm)	36.2 x 2 x 5.7
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting
AC line cord color	Black
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product warranty	Lifetime
Connected equipment insurance (USA and Canada Only)	\$500,000
DATALINE SURGE SUPPRESSION	
Coax line protection	3 line
Network Ethernet line protection	1 line
Telephone / Modem line protection	1 line
Overview	
Style	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2813.