



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPER6TEL12

### Protect It! Surge Suppressor



### Highlights

- 7 outlets / 12-ft. cord
- 1270 joule rating
- Modem/fax surge protection
- \$50,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

### Description

Tripp Lite's SUPER6TEL12 surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. High-grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. SUPER6TEL12 offers 7 total outlets, 12 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Heavy grade AC suppression rated at 1270 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 3 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$50,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 3 transformer spaced outlets

SUPPRESSION: AC: 150V RMS Clamping/1270 joules/330V UL1449 Let-through Rating

Phone: Single telephone line surge suppression (RJ11 jacks, 2 wire, 1 line)

#### Package Includes

- SUPER6TEL12 Surge Suppressor
- 6-ft. telephone cord
- Instruction manual with warranty information

### Features

- 1270 joules AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with room for 3 transformer plugs without blocking outlets covers computers and all peripherals
- Phone line surge suppression protects both dialup and DSL modems, plus fax machines, cordless phones and more (pair of RJ11 jacks, 2 wire, 1 line, includes 6 ft phone cable)
- 12 foot AC line cable conveniently reaches distant outlets
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets

Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition  
 Diagnostic LEDs confirm outlet grounding and surge suppression status  
 Attractive white suppressor housing with keyhole mounting tabs allow versatile placement options  
 UL1449 Rated (330V all modes), UL1363 (Power Tap), UL497A (Communications), Meets FCC part 68 rules, cUL (Canada)  
 Exceeds IEEE 587 category A & B surge suppression specifications  
 Lifetime warranty with \$20,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada Only)

## Specifications

<b>SYSTEM OVERVIEW</b>	
<b>Voltage compatibility</b>	120 VAC
<b>Frequency compatibility</b>	50/60 Hz
<b>OUTPUT</b>	
<b>Output volt amp capacity (amps)</b>	15
<b>Output watts</b>	1800
<b>Outlet quantity / type</b>	7 NEMA 5-15R
<b>Outlet orientation</b>	Single row of 5, plus 2 side mounted outlets
<b>Transformer accommodation</b>	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total
<b>INPUT</b>	
<b>Input connection type</b>	NEMA 5-15P
<b>Input cord gauge, type</b>	14 gauge, SJT
<b>Input cord length (ft.)</b>	12 ft.
<b>Input cord length (m)</b>	3.7
<b>Recommended electrical service</b>	120V, 15A
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Diagnostic LEDs</b>	Built-in LED confirms suppressor "protection present" (green) status
<b>Switches</b>	Two position on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>AC suppression joule rating</b>	1270 joules
<b>Clamping voltage (RMS)</b>	150V
<b>AC suppression response time</b>	< 1 ns
<b>UL1499 let through rating</b>	330V - UL Verified
<b>EMI / RFI filtering</b>	Up to 20 dB
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	2
<b>Shipping weight (kg)</b>	0.9
<b>Shipping Dimensions (HWD/in)</b>	1.75 x 6 x 13
<b>Shipping Dimensions (HWD/cm)</b>	4.4 x 15.2 x 33
<b>Unit weight (lbs)</b>	1.8
<b>Unit weight (kg)</b>	0.8
<b>Unit Dimensions (HWD/in)</b>	1.5 x 2.75 x 10.25

<b>Unit Dimensions (HWD/cm)</b>	3.8 x 7 x 26
<b>Material of construction</b>	Plastic
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting tabs enable wall mounting
<b>AC line cord color</b>	Gray
<b>CERTIFICATIONS</b>	
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>UL1363 (Power Tap)</b>	UL1363
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Industry Canada (Communications)</b>	Industry Canada
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product warranty</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only)</b>	\$50,000
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone / Modem line protection</b>	1 line
<b>Overview</b>	
<b>Style</b>	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=136](http://www.tripplite.com/products/model.cfm?txtModelID=136).