



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: STRIKER

### Protect It! Surge Suppressor



### Highlights

- 7 outlets/6-ft. cord
- 750-joule surge suppression rating
- \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

### Description

Tripp Lite's STRIKER offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. AC surge suppression shields connected equipment from damage and performance problems due to transient surges. STRIKER offers 7 AC outlets, 6-ft. cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC suppression rated at 750 joules shields equipment from surges and line noise. Attractive gray housing with keyhole mounting tabs and 1 designated transformer plug outlet offer convenient protection of desktop computer equipment and accessories. \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 x NEMA5-15R/6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/750 joules/330V UL1449 Let-through Rating

#### Applications

Ideal for any desktop, network or home computing application requiring AC line surge protection.

#### Package Includes

- STRIKER Surge Suppressor
- Instruction manual with warranty information

### Features

- 750-joule AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with 1 transformer plug outlet that doesn't block remaining outlets
- 6-ft. AC line cable conveniently reaches distant outlets
- Built-in power switch and 15A circuit breaker offer power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LEDs confirm outlet grounding and surge suppression status
- Attractive gray housing with keyhole mounting tabs allows versatile placement options
- UL1449 Rated (330V all modes), UL1363 (Power Tap), cUL (Canada)

Exceeds IEEE 587 category A & B surge suppression specifications  
 Lifetime warranty with \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

## Specifications

<b>SYSTEM OVERVIEW</b>	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
<b>OUTPUT</b>	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	7 NEMA 5-15R
Outlet orientation	Single row
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets; accepts up to 4 transformers total
<b>INPUT</b>	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	6 ft.
Input cord length (m)	1.8
Recommended electrical service	120V, 15A
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	750 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
<b>PHYSICAL</b>	
Shipping weight (lbs)	1
Shipping weight (kg)	0.5
Shipping Dimensions (HWD/in)	1.75 x 4.5 x 14.9
Shipping Dimensions (HWD/cm)	4.5 x 11.4 x 37.8
Unit weight (lbs)	1.2
Unit weight (kg)	0.5
Unit Dimensions (HWD/in)	1.5 x 2.13 x 11.25
Unit Dimensions (HWD/cm)	3.8 x 5.4 x 28.6
Material of construction	Plastic

<b>Integrated keyhole mounting tabs</b>	Keyhole mounting tabs enable wall mounting
<b>AC line cord color</b>	Gray
<b>CERTIFICATIONS</b>	
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>NOM (Mexico)</b>	NOM
<b>UL1363 (Power Tap)</b>	UL1363
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product warranty</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only)</b>	\$20,000
<b>Overview</b>	
<b>Style</b>	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=133](http://www.tripplite.com/products/model.cfm?txtModelID=133).