



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SUPER7

### Protect It! Surge Suppressor



### Highlights

- 7 outlets/7 ft. cord
- 2350 joule rating
- \$75,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

### Description

The SUPER7 Surge Suppressor from Tripp Lite has 7 outlets, a 7-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2350 joules to handle the strongest surges. \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

#### Applications

Personal computers, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals, audio/visual devices, and more.

#### Package Includes

- Super 7 Surge Suppressor
- Instruction manual with warranty information

### Features

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Surge suppression rating: 2350 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lifetime product warranty

### Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15

Output watts	1800
Outlet quantity / type	7 NEMA 5-15R
Outlet orientation	Single row of 5, plus 2 side mounted outlets
Transformer accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total
<b>INPUT</b>	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	7 ft.
Input cord length (m)	2.1
Recommended electrical service	120V, 15A
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Two position on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	2350 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
<b>PHYSICAL</b>	
Shipping weight (lbs)	1.6
Shipping weight (kg)	0.7
Shipping Dimensions (HWD/in)	13 x 5.25 x 1.9
Shipping Dimensions (HWD/cm)	33 x 13.3 x 4.8
Unit weight (lbs)	1.4
Unit weight (kg)	0.6
Unit Dimensions (HWD/in)	10.25 x 2.75 x 1.5
Unit Dimensions (HWD/cm)	26 x 7 x 3.8
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
AC line cord color	Gray
<b>CERTIFICATIONS</b>	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	

<b>Product warranty</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only)</b>	\$75,000
<b>Overview</b>	
<b>Style</b>	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=131](http://www.tripplite.com/products/model.cfm?txtModelID=131).

---

©2008 Tripp Lite. All Rights Reserved.