



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: DB25

Network Surge Suppressor - Essential protection for data and communication lines

Highlights

- Complete serial port (DB25) surge protection
- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Lifetime product warranty
- Heavy duty grounding lead



Description

Tripp Lite's DB25 offers dataline surge suppression for many RS232 DB25 serial ports of data terminal and data communications equipment, including PCs, printers, modems and more. Protects pins 1-8, 20 and D shell chassis for protection of specific DB25 applications. User configurable for use with male or female captive DB25 port. Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface connections, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Lifetime warranty.

SUPPRESSION: Reversible DB25 m/f jacks, protects pins 1-8, 20 and chassis, 18V clamping

Applications

Ideal for the protection of data terminals, data communications equipment, PCs, printers, modems and more.

Features

- DB25 protects 25 pin serial connections for many RS232 DB25 serial ports of data terminal and data communications equipment, including PCs, printers, modems and more
- Protects pins 1-8, 20 and D shell chassis for protection of specific DB25 applications.
- User configurable for use with male or female captive DB25 port
- Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis
- Reversible for use with male or female captive DB25 ports
- Offers protection on all 25 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- Lifetime product warranty

Specifications

OUTPUT	
Output volt amp capacity (amps)	340 amps
INPUT	

Input connection type	DB25
Recommended electrical service	N/A
SURGE / NOISE SUPPRESSION	
Clamping voltage (RMS)	18V
DATALINE SURGE SUPPRESSION	
Additional Dataline protection	1-8, 20 & Chassis
Overview	
Style	In-Line

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=158.