



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: DB25-ALL

Network Surge Suppressor - Essential protection for data and communication lines



Highlights

- Complete serial port (DB25) surge protection
- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Lifetime product warranty
- Heavy duty grounding lead

Description

Tripp Lite's DB25-ALL offers dataline surge suppression for any DB25 serial port, regardless of cable configurations. Connects and protects all 25 pins plus D shell chassis for universal protection of any DB25 application. User configurable for use with male or female captive DB25 port. Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface connections, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Lifetime warranty.

SUPPRESSION: Reversible DB9 m/f jacks, protects pins 1-25 and chassis, 18V clamping

Applications

Ideal for the protection of data terminals, data communications equipment, PCs, printers, modems and more.

Package Includes

- DB25-ALL dataline protector
- Instruction manual and warranty information

Features

- DB25 protects 25 pin serial connections for dataline surge suppression of data terminal, data communications equipment and PCs, printers, modems and more
- Reversible for use with male or female captive DB25 ports
- Offers protection on all 25 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- Lifetime product warranty

Specifications

OUTPUT	
Output volt amp capacity (amps)	340 amps
INPUT	

Input connection type	DB25
Recommended electrical service	N/A
SURGE / NOISE SUPPRESSION	
Clamping voltage (RMS)	18V
DATALINE SURGE SUPPRESSION	
Additional Dataline protection	1-25 & Chassis
Overview	
Style	In-Line

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=159.