

Model #: TLP808TEL

Protect It! Surge Suppressor



Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234 E-mail: saleshelp@tripplite.com

Highlights

8 outlets / 8-ft. cord 2820 joule rating Modem/fax surge protection \$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

Tripp Lite's TLP808TEL surge suppressor has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2820 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. \$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Applications

Ideal for home computers and other important electrical equipment

Package Includes TLP808TEL 6-ft. telephone cord Instruction manual with warranty information

Features

8 outlets with integrated child safety covers
8-ft. cord with space-saving right-angle plug
Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
Surge suppression rating: 2820 joules
EMI/RFI noise filtering
Can accommodate up to 3 transformers without blocking remaining outlets
\$150,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)
Diagnostic LEDs indicate protection present & ground present
Keyhole supports for wall mounting
Lighted power switch
Lifetime product warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC

Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Output watts	1800W
Outlet quantity / type	8 NEMA 5-15R
Outlet orientation	Single row of 5, plus a second row of 3 for transformer accommodation
Outlet safety covers	Includes built-in sliding outlet safety covers
Transformer accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	8 ft.
Input cord length (m)	2.4
Recommended electrical service	120V,15A
Input plug features	Space-saving right angle input plug
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch
SURGE / NOISE SUPPRESSIO	N
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	2820 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 40 dB
PHYSICAL	
Shipping weight (lbs)	2.2
Shipping weight (kg)	1.0
Shipping Dimensions (HWD/in)	2.5 x 14.75 x 8.75
Shipping Dimensions (HWD/cm)	6.4 x 37.5 x 22.2
Unit weight (lbs)	1.6
Unit weight (kg)	0.7
Unit Dimensions (HWD/in)	1.6 x 9.25 x 4.25
Unit Dimensions (HWD/cm)	4.1 x 23.5 x 10.8
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting slots enable wall mounting
Receptacle Color	white

CERTIF	ICATIONS
--------	----------

CERTIFICATIONS		
UL1449 1998 Rev. (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC Part 68	
cUL / CSA (Canada)	cUL	
Industry Canada (Communications)	Industry Canada	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product warranty	Lifetime	
Connected equipment insurance (USA and Canada Only	\$150,000	
SPECIAL FEATURES		
Additional Information	Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line	
DATALINE SURGE SUPPRES	DATALINE SURGE SUPPRESSION	
Telephone / Modem line protection	1 line	
Overview		
Style	Strip	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=141.

©2008 Tripp Lite. All Rights Reserved.