



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP1008TEL

### Protect It! Surge Suppressor



### Highlights

- 10 outlets / 8-ft. cord
- 2395 joule rating
- 1 in/2 out tel/modem surge protection
- 5 transformer spaces
- \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

### Description

Tripp Lite's TLP1008TEL offers economical AC surge suppression for protection of workstations, PCs, telecom systems, home electronics and other sensitive equipment. The TLP1008TEL features 10 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs to warn of suppressor damage. The unit has a surge suppression rating of 2395 joules to shield equipment from line noise and the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

PLUG/OUTLETS: Input: NEMA5-15P/Output: 10 NEMA5-15R/8-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 5 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/2395 joules/330V UL1449

#### Applications

Ideal for home computers, TV/VCR/DVD players, stereos and other important electrical equipment

#### Package Includes

- TLP1008TEL surge suppressor
- 6-ft. RJ11 telephone cord
- Instruction manual with warranty information

### Features

- 10 outlets with integrated child safety covers
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment — built-in splitter protects two devices sharing a single line; 6-ft. telephone cord included
- Surge suppression rating: 2395 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker

Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status  
 Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression  
 Can accommodate up to 5 transformers without blocking remaining outlets  
 \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only) covers connected equipment  
 Keyhole supports for wall mounting  
 Failsafe shutdown mode  
 Lighted power switch  
 Lifetime product warranty

## Specifications

<b>SYSTEM OVERVIEW</b>	
<b>Voltage compatibility</b>	120 V AC
<b>Frequency compatibility</b>	50/60 Hz
<b>OUTPUT</b>	
<b>Output volt amp capacity (amps)</b>	15A
<b>Output watts</b>	1800W
<b>Outlet quantity / type</b>	10 NEMA 5-15R
<b>Outlet orientation</b>	Two rows of outlets, including 5 widely spaced for transformers
<b>Overload protection</b>	15A resettable circuit breaker
<b>Outlet safety covers</b>	Includes built-in sliding outlet safety covers
<b>Transformer accommodation</b>	Supports 5 large transformer plug accessories without covering remaining outlets, accepts up to 8 transformers total
<b>INPUT</b>	
<b>Input connection type</b>	NEMA 5-15P
<b>Input cord gauge, type</b>	14 gauge, SJT
<b>Input cord length (ft.)</b>	8 ft.
<b>Input cord length (m)</b>	2.4
<b>Recommended electrical service</b>	120V, 15A
<b>Input plug features</b>	Space-saving right angle input plug
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Diagnostic LEDs</b>	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
<b>Switches</b>	Two-position on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>AC suppression joule rating</b>	2395 joules
<b>Clamping voltage (RMS)</b>	150V
<b>AC suppression response time</b>	< 1 ns
<b>UL1499 let through rating</b>	330V - UL Verified
<b>EMI / RFI filtering</b>	Up to 40dB
<b>PHYSICAL</b>	
<b>Shipping Dimensions (HWD/in)</b>	14.75 x 7.75 x 2
<b>Shipping Dimensions (HWD/cm)</b>	37.5 x 19.7 x 5.1

<b>Unit weight (lbs)</b>	1.4
<b>Unit weight (kg)</b>	0.6
<b>Unit Dimensions (HWD/in)</b>	11.6 x 5 x 1.9
<b>Unit Dimensions (HWD/cm)</b>	29.5 x 12.7 x 4.8
<b>Material of construction</b>	Plastic
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting tabs enable wall mounting
<b>AC line cord color</b>	Black
<b>CERTIFICATIONS</b>	
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>UL1363 (Power Tap)</b>	UL1363
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Industry Canada (Communications)</b>	Industry Canada
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product warranty</b>	Lifetime
<b>Connected equipment insurance (USA and Canada Only)</b>	\$150,000
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone / Modem line protection</b>	1 line
<b>Overview</b>	
<b>Style</b>	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=2634](http://www.tripplite.com/products/model.cfm?txtModelID=2634).