



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP404

Protect It! Surge Suppressor



Highlights

- 4 outlets / 4-ft. cord
- 390 joule rating
- \$1000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's TLP404 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP404 offers 4 total outlets, 4 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 390 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 1 designated transformer plug outlet offers convenient protection of desktop computer equipment and accessories. \$1,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 4 NEMA5-15R/4-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/390 joules/330V UL1449

Applications

Ideal for any desktop, network or home computing application requiring AC line protection

Package Includes

- TLP404 surge suppressor
- Instruction manual with warranty information

Features

- 4 outlets
- 4-ft. cord
- Surge suppression rating: 390 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Diagnostic LED confirms surge protection status
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 2 total transformers

Keyhole supports for wall mounting
 Lighted power switch
 Lifetime warranty with \$1,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only)

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	4 NEMA 5-15R
Outlet orientation	Single row of 4 outlets
Overload protection	15A resettable combo switch / circuit breaker
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 2 transformers total
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	4 ft.
Input cord length (m)	1.2
Recommended electrical service	120V, 15A
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
Switches	Combination AC circuit breaker and 2 position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	390 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
PHYSICAL	
Shipping weight (lbs)	0.6
Shipping weight (kg)	0.3
Shipping Dimensions (HWD/in)	11 x 3.13 x 1.5
Shipping Dimensions (HWD/cm)	27.9 x 8 x 3.8
Unit weight (lbs)	0.6
Unit weight (kg)	0.3
Unit Dimensions (HWD/in)	9.5 x 1.5 x 1.5
Unit Dimensions (HWD/cm)	24.1 x 3.8 x 3.8
Material of construction	Plastic

Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
AC line cord color	Gray
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product warranty	Lifetime
Connected equipment insurance (USA and Canada Only)	\$1,000
Overview	
Style	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2631.