Waber-by-TrippLite SurgeSuppressor

Heavy-dutymetalhousing



DESCRIPTION

Model#:PM6SN1

- 6outlets/6ft.cord
- 450joulerating

The Waber -by-Tripp Lite PM6SN1 Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5 -15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installationinawidevarietyofapplications. Protectsconnected equipment from transient surges and line noise with built insurge suppression rated at 450 joules. Corded, multi -outlets trip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wallsocket. Features metal housing, lighted powers witch with integrated 15 ampresettable circuit breaker and attractive beigehousing with blackout put receptacles and power cord. Lifetime warranty.

PLUG/OUTLETS -Input:NEMA5 -15P/Output:6NEMA5 -15R

ELECTRICAL -120VAC, 50/60Hz, 15A(RequiresstandardNEMA5 -15Rwallreceptacle)

FORMAT -Cordedpowerdistributionstripwithsurgesuppression

SUPPRESSION -450joulesACsuppression

KEYBUYINGPOINTS

- Multi-outletpowerstripoffersconvenientpowerdistributioninworkbench,wallmountorfloormountapplications
- Includes6NEMA5 -15Routputreceptacles
- Lightedcombinationpowerswitchwithintegratedcircuitbreaker
- Keyholemountingtabssupportpermanentinstallationonawidevarietyofsurfaces
- UL1449(USA/400Vrating),UL1363(USA),cUL(Canada)
- 15amppowerhandlingcapacity
- 6footAClinecord
- Lifetimewarranty

TYPICALAPPLICATIONS

• Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

PACKAGEINCLUDES

- PM6SN1PowerStrip
- Warrantyinformation
- Instructionmanual

COMPLETESPECIFICATIONS

| SYSTEMOVERVIEW | |
|--------------------------------|--|
| Voltagecompatibility: | 120VAC |
| Frequencycompatibility: | 50/60Hz |
| OUTPUT | |
| Outputvoltampcapacity(amps): | 15 |
| Outputwattcapacity(watts): | 1800 |
| Outletquantity/type: | 6NEMA5 -15Routputreceptacles |
| INPUT | |
| Inputconnectiontype: | NEMA5 -15Pinputplug |
| Inputcordlength(ft.): | 6 |
| Inputcordlength(m): | 1.8 |
| Inputcordgauge,type: | 14gauge,SJT |
| Recommendedelectricalservice: | 120V15A |
| LEDSALARMS&SWITCHES | |
| DiagnosticLEDs: | Protectionpresent(green) |
| Switches: | Lightedtwopositionpowerswitchcontrolspowertoalloutlets |
| ACSURGE/NOISESUPPRESSION | |
| Protectionmodes: | Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression |
| ACsuppressionjoulerating: | 450joules |
| UL1499letthroughrating: | 400V -ULVerified |
| EMI/RFIfiltering: | Upto20dB |
| Immunity: | ConformstoIEE587/ANSIC62.41 |
| PHYSICAL | |
| Shippingweight(Ibs): | 1.5 |
| Shippingweight(kg): | 0.7 |
| Unitweight(lbs): | 1.25 |
| Unitweight(kg): | 0.6 |
| UnitDimensions(HWD/in): | 12.5x2.5x1.5 |
| UnitDimensions(HWD/cm): | 31.75x6.35x3.8 |
| Materialofconstruction: | Metal |
| Integratedkeyholemountingtabs: | Keyholemountingtabsenablewallmounting |
| Housingcolor: | Beige |
| Receptaclecolor: | Black |
| AClinecordcolor: | Black |
| CERTIFICATIONS | |
| UL14491998Rev.(ACSuppression): | UL1449 |
| UL1363(PowerTap): | UL1363 |
| cUL/CSA(Canada): | CUL |
| WARRANTY | |
| Productwarranty: | Lifetime |

ThepolicyofTrippLiteisoneofcontinuousimprovement. Specificationsaresubjecttochangewithoutnotice. Therefore,yourproductmayvaryslightlyfromwhatiscurrentlylisted. Pleasemakenotethatthisinformationwaspostedon08/04/2003.



TrippLiteWorldHeadquarters 1111W.35thStreet Chicago,IL60609USA

> CustomerSupport (773)869 -1234

© 2003TrippLite.AllRightsReserved.