



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLM606

### Protect It! Surge Suppressor



### Highlights

- 6 outlets / 6 ft. cord
- 280 joule rating
- \$5,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

### Description

Tripp Lite's TLM606 surge suppressor offers complete AC surge suppression for comprehensive protection of personal computers, home stereos, televisions, VCRs, DVD players, power tools and other electrical and electronic equipment. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM606 offers 6 total outlets, a 6 foot power cord and diagnostic LED to warn of suppressor damage. AC surge suppression rated at 280 joules shields equipment from surges and line noise. Rugged metal housing offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$5,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/280 joules/330V UL1449

#### Applications

Ideal for personal computers, TV/VCR/DVD, stereos, power tools and lamps/lighting

#### Package Includes

- TLM606 surge suppressor
- Instruction manual and warranty information

### Features

- 6 outlets
- 6 ft. cord
- Surge suppression rating: 280 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker protects against overload
- Diagnostic LED confirms suppressor "protection present" (green)
- Convenient keyhole slots allow secure mounting on wall or desk

Can accommodate up to 1 transformers without blocking adjacent outlets  
 Rugged metal case provides extra safety and durability  
 Illuminated power switch  
 \$5,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment  
 Lifetime product warranty

## Specifications

| <b>SYSTEM OVERVIEW</b>            |  |
|-----------------------------------|--|
| Voltage compatibility             | 120V AC  |
| Frequency compatibility           | 50/60 Hz   |
| <b>OUTPUT</b>                     |  |
| Output volt amp capacity (amps)   | 15   |
| Output watts                      | 1800   |
| Outlet quantity / type            | 6 NEMA 5-15R   |
| Outlet orientation                | Single row of outlets  |
| Overload protection               | 15A circuit breaker  |
| Transformer accommodation         | Supports 1 large transformer without covering adjacent outlets                     |
| <b>INPUT</b>                      |  |
| Input connection type             | NEMA 5-15P   |
| Input cord gauge, type            | 14 gauge, SJT  |
| Input cord length (ft.)           | 6 ft.  |
| Input cord length (m)             | 1.8  |
| Recommended electrical service    | 120V, 15A  |
| <b>LEDS ALARMS &amp; SWITCHES</b> |  |
| Diagnostic LEDs                   | Built-in LED confirms suppressor "protection present" (green) status               |
| Switches                          | 2 position on/off power switch   |
| <b>SURGE / NOISE SUPPRESSION</b>  |  |
| Protection modes                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating       | 280 joules   |
| Clamping voltage (RMS)            | 150V   |
| AC suppression response time      | < 1 ns   |
| UL1499 let through rating         | 330V - UL Verified   |
| EMI / RFI filtering               | Up to 20dB   |
| <b>PHYSICAL</b>                   |  |
| Shipping weight (lbs)             | 1.6  |
| Shipping weight (kg)              | .7   |
| Shipping Dimensions (HWD/in)      | 1.75 x 15.5 x 4.5  |
| Shipping Dimensions (HWD/cm)      | 4.4 x 39.4 x 11.4  |
| Unit weight (lbs)                 | 1.4  |
| Unit weight (kg)                  | .6   |
| Unit Dimensions (HWD/in)          | 1.5 x 12.5 x 2.5   |

|  |  |
|--|--|
| <b>Unit Dimensions (HWD/cm)</b>                            | 3.8 x 31.8 x 6.3   |
| <b>Material of construction</b>                            | Metal  |
| <b>Form factors supported</b>                              | Supports floor / wall / desktop placement                          |
| <b>Integrated keyhole mounting tabs</b>                    | Keyhole slots enable mounting to a variety of surfaces             |
| <b>Receptacle Color</b>                                    | Light Gray   |
| <b>AC line cord color</b>                                  | Light Gray   |
| <b>CERTIFICATIONS</b>                                      |  |
| <b>Additional International Approvals</b>                  | Complies with RoHS (Restriction of Hazardous Substances Directive) |
| <b>UL1449 1998 Rev. (AC Suppression)</b>                   | UL1449   |
| <b>UL1363 (Power Tap)</b>                                  | UL1363   |
| <b>cUL / CSA (Canada)</b>                                  | cUL  |
| <b>Approvals</b>   | Exceeds IEEE 587 category A&B specifications                       |
| <b>WARRANTY</b>  |  |
| <b>Product warranty</b>                                    | Lifetime   |
| <b>Connected equipment insurance (USA and Canada Only)</b> | \$5,000  |
| <b>Overview</b>  |  |
| <b>Style</b>   | Strip  |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=3306](http://www.tripplite.com/products/model.cfm?txtModelID=3306).