



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLM606HJ

Protect It! Surge Suppressor



Highlights

- 6 outlets / 6 ft. cord
- 1120 joule rating
- \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Description

Tripp Lite's TLM606HJ surge suppressor offers complete AC surge suppression for comprehensive protection of personal computers, home stereos, televisions, VCRs, DVD players, power tools and other electrical and electronic equipment. Heavy-duty AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM606HJ offers 6 total outlets, a 6 foot power cord and diagnostic LED to warn of suppressor damage. AC surge suppression rated at 1120 joules shields equipment from surges and line noise. Rugged metal housing offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/1120 joules/330V UL1449

Applications

Ideal for personal computers, TV/VCR/DVD, stereos, power tools and lamps/lighting

Package Includes

TLM606HJ surge suppressor
Instruction manual and warranty information

Features

- 6 outlets
- 6 ft. cord
- Surge suppression rating: 1120 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker protects against overload
- Diagnostic LED confirms suppressor "protection present" (green)
- Convenient keyhole slots allow secure mounting on wall or desk

Can accommodate up to 1 transformers without blocking adjacent outlets
 Rugged metal case provides extra safety and durability
 Illuminated power switch
 \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment
 Lifetime product warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Single row of outlets
Overload protection	15A circuit breaker
Transformer accommodation	Supports 1 large transformer without covering adjacent outlets
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	6 ft.
Input cord length (m)	1.8
Recommended electrical service	120V, 15A
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
Switches	2 position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1120 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20dB
PHYSICAL	
Shipping weight (lbs)	1.6
Shipping weight (kg)	.7
Shipping Dimensions (HWD/in)	1.75 x 15.5 x 4.5
Shipping Dimensions (HWD/cm)	4.4 x 39.4 x 11.4
Unit weight (lbs)	1.4
Unit weight (kg)	.6
Unit Dimensions (HWD/in)	1.5 x 12.5 x 2.5

Unit Dimensions (HWD/cm)	3.8 x 31.8 x 6.3
Material of construction	Metal
Form factors supported	Supports floor / wall / desktop placement
Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces
Receptacle Color	Light Gray
AC line cord color	Light Gray
CERTIFICATIONS	
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product warranty	Lifetime
Connected equipment insurance (USA and Canada Only)	\$75,000
Overview	
Style	Strip

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3459.