



Model #: TLM626

Protect It! Surge Suppressor



Highlights

6 outlets / 6 ft. cord
1208 joule rating
\$75,000 Ultimate Lifetime Insurance (USA & Canada only)
Rugged metal case

Description

Tripp Lite's TLM626 surge suppressor offers complete AC surge suppression for comprehensive protection of workstations, personal computers, home stereos, televisions, VCRs, DVD players and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLM626 offers 6 right-angle outlets, a 6 foot power cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC surge suppression rated at 1208 joules shields equipment from surges and line noise. Rugged metal housing with 2 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$75,000 Ultimate Lifetime Insurance (USA & Canada Only).

PLUG/OUTLETS: Input - 6 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R right-angle outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/1208 joules/330V UL1449

Applications

Ideal for personal computers, TV/VCR/DVD, stereos and lamps/lighting

Package Includes

TLM626 surge suppressor Instruction manual and warranty information

Features

6 right-angle outlets

6 ft. cord

Surge suppression rating: 1208 joules

EMI/RFI noise filtering

15 amp resettable circuit breaker protects against overload

Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status

Convenient keyhole slots allow secure mounting on wall or desk

Can accommodate up to 2 transformers without blocking adjacent outlets
Rugged metal case provides extra safety and durability
Illuminated power switch
\$75,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment
Lifetime product warranty

Specifications

SYSTEM OVERVIEW		
Voltage compatibility	120V AC	
Frequency compatibility	50/60 Hz	
OUTPUT		
Output volt amp capacity (amps)	15	
Output watts	1800	
Outlet quantity / type	6 NEMA 5-15R	
Outlet orientation	Single row of outlets	
Overload protection	15A resettable combo switch / circuit breaker	
Transformer accommodation	Supports 2 large transformers without covering adjacent outlets	
INPUT		
Input connection type	NEMA 5-15P	
Input cord gauge, type	14 gauge, SJT	
Input cord length (ft.)	6 ft.	
Input cord length (m)	1.8	
Recommended electrical service	120V,15A	
LEDS ALARMS & SWITCHES		
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status	
Switches	Combination AC circuit breaker and 2 position on/off power switch	
SURGE / NOISE SUPPRESSION		
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
AC suppression joule rating	1208 joules	
Clamping voltage (RMS)	150V	
AC suppression response time	< 1 ns	
UL1499 let through rating	330V - UL Verified	
EMI / RFI filtering	Up to 20dB	
PHYSICAL		
Shipping weight (lbs)	2.5	
Shipping weight (kg)	1.1	
Shipping Dimensions (HWD/in)	2.25 x 15 x 6	
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 15.2	
Unit weight (lbs)	1.8	
Unit weight (kg)	.8	
Unit Dimensions (HWD/in)	1.5 x 12.25 x 2.25	

Unit Dimensions (HWD/cm)	3.8 x 31.1 x 5.7	
Material of construction	Metal	
Form factors supported	Supports floor / wall / desktop placement	
Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces	
Receptacle Color	Light Gray	
AC line cord color	Black	
CERTIFICATIONS		
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)	
UL1449 1998 Rev. (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product warranty	Lifetime	
Connected equipment insurance (USA and Canada Only	\$75,000	
Overview		
Style	Strip	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3305.

©2008 Tripp Lite. All Rights Reserved.