



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TRAVELCUBE

1 AC outlet, direct plug-in surge suppressor with built-in tel/modem surge protection



Highlights

- 1 AC outlet
- Direct plug-in design
- Built-in tel/modem surge protection
- 950 joule rating
- Diagnostic LED displays protection status
- \$10,000 [Ultimate Lifetime Insurance](#) (US & Canada only)

Description

The TRAVELCUBE is designed for convenient portable and economical surge protection. Small and powerful, the TRAVELCUBE features 950 joules and carries \$10K of insurance as well as a lifetime product warranty. Throw it in a briefcase or purse and have quality surge protection wherever you need it — hotel room, dorm, client office — anywhere!

Applications

Ideal for use with laptops, fax machines, electronic notepads, personal organizers and other portable electronic devices

Package Includes

- TRAVELCUBE surge suppressor
- Bonus 6-ft. telephone cord

Features

- Portable wall-mount cube stores easily in any bag or briefcase
- 1 NEMA5-15R AC outlet
- 950 joules of protection shields equipment from harmful surges, spikes and line noise
- Diagnostic LED displays protection status
- Built-in tel/modem surge protection
- Bonus 6-ft. phone cord included
- UL 1449 rated
- Lifetime warranty with \$10,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15

Output watts	1800
Outlet quantity / type	1 NEMA 5-15R
INPUT	
Input connection type	NEMA 5-15P input plug
Input cord length (ft.)	Direct plug-in
Recommended electrical service	120V, 15A
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (red) status
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	950 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20dB
PHYSICAL	
Shipping weight (lbs)	0.2
Shipping weight (kg)	0.1
Shipping Dimensions (HWD/in)	4 x 3.25 x 2.4
Shipping Dimensions (HWD/cm)	10.2 x 8.25 x 6.1
Unit weight (lbs)	0.18
Unit weight (kg)	0.1
Unit Dimensions (HWD/in)	2.75 x 1.9 x 1.25
Unit Dimensions (HWD/cm)	7 x 4.8 x 3.2
Material of construction	Plastic
Form factors supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product warranty	Lifetime
Connected equipment insurance (USA and Canada Only)	\$10,000
SPECIAL FEATURES	
Appearance	Ultra-compact portable direct plug in protector in an attractive, grey lightweight enclosure
DATALINE SURGE SUPPRESSION	
Telephone / Modem line protection	1 line
Overview	
Style	Direct Plug-in

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2559.

©2008 Tripp Lite. All Rights Reserved.