



**Back-UPS ES 350**  
**Part Number : BE350U**



[Print](#)

**Product Overview**

Description	APC Back-UPS ES, 350VA/200W, Input 120V/ Output 120V, Interface Port USB
Features	Add Surge Protected Outlets, Audible Alarms, Building wiring fault indicator, Hot Swap Batteries, Lightning and Surge Protection, Modem Protection, Resettable circuit breaker, Software, Status Indicator LED's, Unattended Safe & Graceful Shutdown, USB Connectivity, User Replaceable batteries
Includes	CD with software, Free trial of anti-virus : firewall : email privacy : system recovery and online backup software, User Manual, USB cable, Velcro Cord Management Straps, Wall-mounting template

**Options**

Optional Service	<a href="#">Click here to view optional Service.</a>
------------------	--

**Documentation**

User Manual & Installation Guides	<a href="#">APC Safety Guide (120V)</a> <a href="#">Back-UPS ES - Back-UPS ES 350/500; User Manual</a>
-----------------------------------	---

**Communications & Management**

Interface port	USB
Control panel	LED Status display with On Line : On Battery
Audible alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Included Software	<a href="#">APC PowerChute Personal Edition</a>

**Output**

Output power capacity	350 VA
Output power capacity	200 Watts
Nominal output voltage	120 V
Output Connections	(3)NEMA 5-15R (3)NEMA 5-15R (Surge)



**Input**

Nominal input voltage	120 V
Input frequency	60 Hz +/- 1Hz



Input Connection Type NEMA 5-15P

Cord Length 6 feet (1.83 meters )

Input voltage range for main operations 96 - 136 V

### Surge Protection and Filtering

Surge energy rating 365 joules

Dataline protection RJ-11 Modem/Fax/DSL protection (two wire single line)

### Runtime

Typical backup time at half load 8.1 minutes (100 Watts)

Typical backup time at full load 1.6 minutes (200 Watts)

Runtime Chart [Back-UPS ES](#)

### Batteries

Battery type Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time \*\* 16 hour(s)

### Physical

Maximum height dimensions 3.30 inches ( 8.38 cm)

Maximum width dimensions 10.90 inches ( 27.69 cm)

Maximum depth dimensions 6.90 inches ( 17.53 cm)

Net weight 9.20 lbs ( 4.18 kg)

Shipping Weight 10.73 lbs ( 4.88 kg)

Shipping Height 4.70 inches ( 11.94 cm)

Shipping Width 15.00 inches ( 38.10 cm)

Shipping Depth 8.90 inches ( 22.61 cm)

Color Charcoal

Units per Pallet 120.0

UPC Code 731304118534

### Environmental

Operating Environment 0 - 40 °C (32 - 104°F)

Operating Relative Humidity 0 - 95%

Operating Elevation 0-10000 feet (0-3000 m)

Storage Temperature -15 - 45 °C (5 - 113°F)

Storage Relative Humidity 0 - 95% Non-condensing

Storage Elevation 0-10000 feet (0-3000 m)

Audible noise at 1 meter from surface of unit 40 dBA

### Conformance

Approvals cUL Listed, UL Listed

Standard warranty

2 years repair or replace

Equipment protection policy

Lifetime : \$50000

\*\* The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.