



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SM1050NAFTA

Smart Pro Tower UPS System - NAFTA assembled version of SMART1050



Highlights

- 1050VA line interactive tower UPS system
- Enhanced USB communications port
- Corrects brownouts and overvoltages from 75 to 147V
- 6 outlets
- \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's SM1050NAFTA intelligent, line interactive UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 23 minutes half load runtime and 8 minutes at full load during power failures. 1050VA/705 watt power handling capability supports a variety of networking, telecom and various other application types, including the support of multiple network workstations. Includes a total of 6 UPS supported outlets. Supports remote monitoring of UPS and site power conditions via built-in USB monitoring port. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Built-in audible alarm and 5 front panel LEDs indicate status of line power, battery power, battery low/replace, voltage regulation and load level. Wall mountable with UPSWM wallmount bracket. Network-grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Attractive, small-footprint tower housing uses less than 53 square inches of floor or desktop space. Two year warranty with \$250,000 [connected equipment insurance](#).

Applications

Ideal for the protection of file servers, network accessories and telecommunications equipment. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems. Ideal for sensitive electronic applications in areas where brownouts and overvoltages are common.

Package Includes

- SMART 1050 UPS System
- USB monitoring cable
- PowerAlert unattended shutdown and UPS/Power monitoring software
- Instruction manual with warranty information

Features

- 1050VA/705 watt power handling capability supports a variety of networking, telecom and various other application types
- Built-in voltage regulation and battery support prevents equipment damage, data loss and downtime
- Large internal batteries offer 23 minutes half load runtime and 8 minutes at full load during power failures
- Automatic Voltage Regulation (AVR) circuits with two boost and one voltage reduction level maintains usable 120V nominal output over an input voltage range of 75-147V
- Includes a total of 6 NEMA5-15R outlets
- Includes 1 USB communications port for remote monitoring of UPS status and site power conditions

Communications port enables safe unattended shutdown without data loss during extended power failures

Communications port supports messaging of UPS and line power status, including on-battery, low-battery, power-restored, AC line voltage, DC battery voltage and battery capacity

Communications port supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment

PowerAlert UPS monitoring and unattended shutdown software with complete cabling included

Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again

Notification of system status via 5 LEDs and multi-function audible alarms

Wall mountable with UPSWM wallmount bracket

Attractive small footprint beige tower housing uses less than 53 square inches

Hot-swappable/user replaceable batteries allow on-site battery replacement

Cold start capability enables UPS turn-on in battery mode during blackout conditions

UL (USA), cUL (Canada), NOM (Mexico), Class B (Emmissions)

\$250,000 [Ultimate Lifetime Insurance](#)

2 year manufacturers product warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	60Hz
OUTPUT	
Output VA	1050
Output watts	705
Output nominal voltage	120V AC
Output voltage regulation	LINE MODE: Sine wave line voltage 120V (-18% / +8%), BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	6 NEMA 5-15R
Overload protection	12A input breaker
INPUT	
Maximum input amps	6.7A /760 watts
Input connection type	NEMA 5-15P
Input cord length	6 ft., 16 gauge
Recommended electrical service	15A 120V
BATTERY	
Full load runtime	8 minutes (1050VA)
Half load runtime	23 minutes (525VA)
DC system voltage	18 VDC
Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	2-4 hours to 90%
VOLTAGE REGULATION	

Voltage regulation description	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V
Overvoltage correction	Input voltages between 128 and 147VAC are reduced by 12%
Direct pass through	Input voltages between 108 and 127VAC are passed on to connected equipment unchanged
Brownout correction	Input voltages between 108 and 127VAC are passed on to connected equipment unchanged
Severe brownout correction	Input voltages between 75 and 92VAC are boosted by 30%
LEDS ALARMS & SWITCHES	
Front panel LEDs	Includes 5 front panel LEDs to indicate BATTERY CHARGE LEVEL, AC LINE POWER STATUS, VOLTAGE REGULATION STATUS, UPS LOAD LEVEL and BATTERY LOW / REPLACE information
Alarms	Audible alarm with 15 second delay sounds to indicate loss of utility power. Alarm can be silenced by pressing front panel alarm cancel button. Once silenced, alarm will re-sound when approximately 2 minutes runtime remain.
Switches	Includes 2 front panel switches — one main on/off power switch and one dual function "alarm cancel" / "self test" button
SURGE / NOISE SUPPRESSION	
AC surge suppression	480 joules
AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	31
Shipping weight (kg)	14.1
Shipping Dimensions (HWD/in)	15 x 10.75 x 11.25
Shipping Dimensions (HWD/cm)	38.1 x 27.3 x 28.6
Unit weight (lbs)	29
Unit weight (kg)	13.2
Unit Dimensions (HWD/in)	11.75 x 7.25 x 7.25
Unit Dimensions (HWD/cm)	29.8 x 18.4 x 18.4
Material of construction	Polycarbonate
Form factors supported	Tower
Cooling method	Convection
Battery Access	Battery access door allows user replacement of UPS batteries
ENVIRONMENTAL	
Operating Temperature	+32 to +104 degrees Fahrenheit, 0 to +40 degrees Celsius
Storage Temperature	+5 to +122 degrees Fahrenheit, -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing

Line mode BTU/hr. (Max.)	61.5
Battery mode BTU/hr. (Max.)	208.4
COMMUNICATIONS	
Network monitoring port	Built-in USB port supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status messaging. Interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment. Supports reboot of all connected devices at once via software interface. Compatible with Tripp Lite's PowerAlert software.
Software and cabling included	Includes PowerAlert UPS monitoring and auto-shutdown software and cabling
WatchDog compatibility	Compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	2-4 milliseconds
Low voltage transfer to battery power	Switches to battery power as line voltage decreases to 75 volts or less. Resets back to line power mode as line voltage increases to 79V or higher.
High voltage transfer to battery power	Switches to battery power as line voltage increases to 147 volts or higher. Resets back to line power mode as line voltage decreases to 143V or less.
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), cUL (Canada), Class B (emissions), NOM (Mexico)
WARRANTY	
Product warranty	2 year product warranty
Connected equipment insurance (USA and Canada Only)	\$250,000 connected equipment insurance (USA / Canada only)
Optional coverage	3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information.
SPECIAL FEATURES	
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance	Attractive gray tower UPS

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3533.